Blue Star #2701

Multipurpose Lubricant

Features:

- Highly water washout resistant
- Water insoluble
- Very low separation rate
- Excellent adhesion provides better "stay-ability" than most greases
- · Additives protect against rust, oxidation and extreme pressure loads

Description:

BLUE STAR accommodates a wide range of lubrication needs for agriculture, industry, and marine and automotive fleet applications. This product will pump through a cartridge gun at zero temperatures, yet is suitable for both high and low speed bearings. It has a high affinity for metal, forming a tough film and offering maximum protection. BLUE STAR is a completely waterproof lubricating grease, offering superior resistance to washout and is unaffected even by boiling salt water. It will maintain a protective coating on metal surfaces, which will prevent rust and corrosion even under the most difficult conditions.

BLUE STAR is suitable for most bearing applications, ball or roller, high or low speed, sealed or open.

Applications:

- Fifth Wheels
- Wheel Bearings
- Water Pumps
- Ball Joints
- Universal JointsPilot Bearings
- Electric Motors
 - Steering Linkage

Solutions:

- Perfect to maintain fleets
- Maintains truck's fifth wheel hitches
- · Perfect to keep all bearings greased and operating smoothly

Product Characteristics: Texture: Smooth, stringy Odor: Mild petroleum Vapor Pressure: <0.0013 kPa (<0.01 mm Hg) [room temperature] Thickener: Anhydrous calcium soap Color: Blue Worked 60 penetration D-217: 265-295 Dropping Point D-566, °F/°C 295 (146) Rust Prevention D-1743 Pass Oxidation Stability D-942, psi drop: 5.0 @ 100 hrs Timken OK Load, D-2509, lb: 55 Approx Temp Range: 0.-250°F(-18 to 121°C) Wheel Bearing Leakage D-1263: Pass Over 2000 Viscosities @100°F: Viscosity Index: 120 Vapor Density: >10 (Air=1) Flash Point: >150°C(>302°F)[Estimated] Evaporation Rate: <1 (n-butyl acetate =1) NGLI Grade: 2 Store in a dry place and/r in Storage: closed container. Transport Information: Proper Shipping Name: Not available UN Number: Not regulated Class: Not available

Directions:

For best performance, fully purge the competitor grease out before applying appropriate amount of BLUE STAR grease. Reapply as needed.

Pictograms:



Signal Word: WARNING

Personal Protective Equipment Required:



Health	1
Flammability	1
Reactivity	0
Personal Protection	В



