







SAFETY DATA SHEET

1. Product and Company Identification

| | | | |
|-----------------------------|---|-----------------------------|----------------|
| PRODUCT NUMBER: | 1424 | COMPANY PHONE: | 1-800-241-8180 |
| PRODUCT NAME: | CITRA-SOLV AEROSOL | EMERGENCY TELEPHONE: | 1-800-241-8180 |
| PRODUCT DESCRIPTION: | Aerosol Degreaser, Spot Remover, & Deodorizer | INFOTRAC: | 1-800-535-5053 |
| COMPANY INFORMATION: | PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004 | | |

2. Hazards Identification

| | | | | | | |
|---|--------------------------------------|----------------|--|---|---|---|
| GHS CLASSIFICATION: Aspiration Hazard - Category 1 Skin Irritation - Category 2 Eye Irritation - Category 2 Skin Sensitization - Category 1 Flammable Aerosols - Category 1 Gases under pressure - Liquefied gas | SIGNAL WORD: DANGER | SYMBOL: |  |  |  |  |
|---|--------------------------------------|----------------|--|---|---|---|

HAZARD STATEMENT (S):

Keep out of reach of children.
Read label and SDS before use.
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Causes skin and serious eye irritation.

PRECAUTIONARY STATEMENT:

Prevention:

Avoid breathing mist/spray.
Wash hands thoroughly after handling.
Wear protective gloves.
Wear eye or face protection.
Contaminated clothing must not be allowed out of the workplace.
Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Response:

IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs get medical attention.
Take off contaminated clothing and wash before reuse.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: Get medical attention.

Storage:

Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Store locked up.

Disposal:

Dispose of contents and container in accordance with all local, regional, and national regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

Not applicable.

3. Composition / Information on Ingredients

| CHEMICAL NAME | CAS | Concentration % by Weight |
|---------------|-----------|---------------------------|
| D-limonene | 5989-27-5 | >=90 = 95 |
| Propane | 74-98-6 | >=10 <= 20 |
| Butane | 106-97-8 | >=1 <= 5 |

4. First Aid Measures

EMERGENCY OVERVIEW

WARNING: Extremely flammable. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed. Keep away from heat and flame. Can cause nervous system depression.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION:

Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION:

Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

5. Fire Fighting Measures**SUITABLE FIRE EXTINGUISHING MEDIA:**

Use water spray, fog, or foam.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

HAZARDOUS THERMAL DECOMPOSITION PRODUCTS:

Carbon Dioxide. Carbon Monoxide.

SPECIFIC FIRE-FIGHTING METHODS:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area, if this can be done without risk. Use water spray to keep fire-exposed containers cool.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

6. Accidental Release Measures**PERSONAL PRECAUTIONS:**

Put on appropriate personal protective equipment (see Section 8).

ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP METHODS:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams, or other bodies of water. Absorb spill with inert material. **DO NOT use clay-type absorbent materials.** Absorb unrecoverable product. Transfer contaminated absorbent, soil, and other materials to containers for disposal.

7. Handling and Storage

Do not use or store near heat, sparks, or open flame. Exposure to temperatures above 120°F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin, or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

8. Exposure Controls / Personal Protection

| | | |
|----------------|-----------|----------|
| Butane | ACGIH TLV | 1000 ppm |
| Propane | ACGIH TLV | 1000 ppm |

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile, or neoprene).

Respiratory Protection: When respiratory protection is required, use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

ENGINEERING CONTROLS:

Good general ventilation required.

9. Physical & Chemical Properties

| | | | |
|----------------------------------|-------------------------|-------------------------------|-----------------|
| APPEARANCE | Clear spray/mist. | AUTO IGNITION TEMP | Not available. |
| BOILING POINT | Not available. | COLOR | Colorless |
| DECOMPOSITION TEMPERATURE | Not available. | EVAPORATION RATE | Not available. |
| EXPLOSIVE LIMIT RANGES | Not available. | EXPLOSIVE PROPERTIES | Not available. |
| FLASH POINT | 120°F (Liquid Portion). | MELTING/FREEZING POINT | Not available. |
| ODOR | Citrus. | ODOR THRESHOLD | Not available. |
| VOC CONTENT (Wt. %): | 98 | OXIDIZING PROPERTIES | Not available. |
| PARTITION COEFF | Not available. | PHYSICAL STATE | Liquid. |
| RELATIVE DENSITY | 0.8 | SOLUBILITY (WATER) | Emulsifies. |
| VAPOR DENSITY | Not available. | VAPOR PRESSURE | Not available. |
| VISCOSITY | Not available. | pH | Not applicable. |

10. Stability & Reactivity Information**REACTIVITY:**

Under normal conditions of storage and use, hazardous reactions will not occur.

CHEMICAL STABILITY:

Stable under normal conditions.

INCOMPATIBLE MATERIALS:

Acids, strong oxidizers, inorganic clays (clay-type absorbents).

CONDITIONS TO AVOID:

High temperatures, open flames, sparks, welding.

DECOMPOSITION PRODUCTS:

CO, CO₂. Vapors may ignite at temperatures exceeding flash point.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

Skin contact, inhalation, ingestion.

ACUTE/POTENTIAL HEALTH EFFECTS:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing, and redness.

SKIN: May cause skin irritation. Prolonged or repeated contact may dry the skin and cause sensitization. Symptoms may include redness, burning, drying of skin, and skin burns.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause nose, throat, and respiratory tract irritation, coughing and headache.

INGESTION: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

CHRONIC / LONG TERM EFFECTS:

None known.

TARGET ORGAN EFFECTS:

Skin.

CARCINOGENIC INFORMATION:

This material is not listed as a carcinogen by IARC, NTP, or OSHA.

ACUTE TOXICITY VALUES:

Not available.

12. Ecological Information

Not available.

13. Disposal Consideration

Waste must be disposed of in accordance with federal, state, and local environmental control regulations. See label for further instructions.

14. Transportation Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

| | |
|-----------------------------|---------------------|
| UN number | 1950 |
| Proper shipping name | Aerosols, flammable |
| Class | 2.1 |
| Packing group | - |

15. Regulatory Information

If identified components of this product are **CERCLA** hazardous substances and/or listed under **Sections 302, 304, or 313 of Title III** of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under **California Proposition 65** (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312:

Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure (X) Reactive () Not Applicable ()

T.S.C.A. Status:

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

RCRA Status:

Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s): D001

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.