

1. Product and Company Ider					
PRODUCT NUMBER:	2448	COMP	ANY PHONE:	1-8	00-241-8180
PRODUCT NAME:	FIRM GRIP PART A	EMER	GENCY TELEPHONE:	1-8	00-241-8180
PRODUCT DESCRIPTION:	Three-Part Epoxy Skid-Resista Coating	nt Floor INFOT	RAC:	1-8	00-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004	/			
2. Hazards Identification					
GHS CLASSIFICATION:	SI	IGNAL WORD:	SYMBOL:		
Skin Irritation: Category 2	w	ARNING			AV.
Eye Irritation: Category 2A					₹
Skin Sensitization: Category 1 Chronic hazards to aquatic env	ironment: Category 2				
HAZARD STATEMENTS:					•
May cause an allergi	c skin reaction.				
Causes skin irritation					
Causes serious eye i					
PRECAUTIONARY STATEME	vith long-lasting effects.				
Keep container tight					
	eeded, have product container or l	abel at hand.			
Keep out of reach of					
Read label before us	e. /gas/mist/vapors/spray.				
Wash skin thoroughly		of the workplace.			
Wash skin thoroughly Contaminated work of Avoid release to the	y after handling. slothing should not be allowed out o environment.				
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glove	y after handling. clothing should not be allowed out of environment. es/protective clothing/eye protectio				
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glove IF ON SKIN: Wash w	y after handling. clothing should not be allowed out of environment. es/protective clothing/eye protectio with soap and water.	on/face protection.	act lanses if present and e	asy to do Continue	ripsing
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glove IF ON SKIN: Wash w IF IN EYES: Rinse of	y after handling. clothing should not be allowed out of environment. es/protective clothing/eye protectio	on/face protection. nutes. Remove cont	act lenses, if present and e	asy to do. Continue	rinsing.
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate	y after handling. clothing should not be allowed out of environment. es/protective clothing/eye protectio with soap and water. autiously with water for several min	n/face protection. nutes. Remove cont tention.	act lenses, if present and e	asy to do. Continue	rinsing.
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage.	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protectio with soap and water. autiously with water for several min ash occurs: Get medical advice/att d clothing and wash before reuse.	n/face protection. nutes. Remove cont tention.	act lenses, if present and e	asy to do. Continue	rinsing.
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke	y after handling. Sothing should not be allowed out of environment. es/protective clothing/eye protectio with soap and water. autiously with water for several min ash occurs: Get medical advice/at id clothing and wash before reuse. ed up.	n/face protection. nutes. Remove cont tention.	act lenses, if present and e	asy to do. Continue	rinsing.
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/at and clothing and wash before reuse. ed up. of contents and container as instruct	n/face protection. nutes. Remove cont tention.	act lenses, if present and e	asy to do. Continue	rinsing.
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locka Disposal: Dispose of 3. Composition / Information	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/at and clothing and wash before reuse. ed up. of contents and container as instruct	n/face protection. nutes. Remove cont tention.			
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. Hautiously with water for several min ash occurs: Get medical advice/at ad clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients	n/face protection. nutes. Remove cont tention.	act lenses, if present and e	Concentratio	rinsing. on % by Weight 0-90
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. Hautiously with water for several min ash occurs: Get medical advice/at ad clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients	n/face protection. nutes. Remove cont tention.	CAS	Concentratio	on % by Weight
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. Hautiously with water for several min ash occurs: Get medical advice/at ad clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients	n/face protection. nutes. Remove cont tention.	CAS 25068-38-6	Concentratio	on % by Weight 0-90
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. Hautiously with water for several min ash occurs: Get medical advice/at ad clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients	n/face protection. nutes. Remove cont tention.	CAS 25068-38-6	Concentratio	on % by Weight 0-90
Wash skin thoroughly Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. Hautiously with water for several min ash occurs: Get medical advice/at ad clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients	on/face protection. nutes. Remove cont tention. cted in Section 13.	CAS 25068-38-6 2461-15-6	Concentration	on % by Weight 0-90 0-20
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentio water for 15-20 minut	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att id clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients and epoxy resin ane on. Drench the affected area imme- tes. Remove contact lenses while	on/face protection. nutes. Remove cont tention. <u>cted in Section 13.</u>	CAS 25068-38-6 2461-15-6 water. Protect unexposed	Concentration 8 1 d eye. Flush expose	on % by Weight 0-90 0-20 d eye gently using
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attention water for 15-20 minut SKIN: Wash hands and exp	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att d clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients and epoxy resin ane on. Drench the affected area imme	on/face protection. nutes. Remove cont tention. <u>cted in Section 13.</u>	CAS 25068-38-6 2461-15-6 water. Protect unexposed	Concentration 8 1 d eye. Flush expose	on % by Weight 0-90 0-20 d eye gently using
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locko Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentio water for 15-20 minur SKIN: Wash hands and exp adverse occur.	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att id clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients and epoxy resin ane on. Drench the affected area imme- tes. Remove contact lenses while	on/face protection. nutes. Remove cont tention. <u>cted in Section 13.</u>	CAS 25068-38-6 2461-15-6 water. Protect unexposed	Concentration 8 1 d eye. Flush expose	on % by Weight 0-90 0-20 d eye gently using
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locko Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentio water for 15-20 minut SKIN: Wash hands and exp adverse occur. INHALATION:	y after handling. Southing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att id clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients and epoxy resin ane on. Drench the affected area imme- tes. Remove contact lenses while	ediately with plenty o rinsing.	CAS 25068-38-6 2461-15-6 water. Protect unexposed aminated clothing. Seek m	Concentratio 8 1 d eye. Flush exposed nedical attention if irr	on % by Weight 0-90 0-20 d eye gently using itation, rash, or othe
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attention water for 15-20 minur SKIN: Wash hands and exp adverse occur. INHALATION: Move exposed to free comfortable position.	y after handling. slothing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att id clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients ind epoxy resin ane on. Drench the affected area imme- tes. Remove contact lenses while sosed skin with soap and plenty of	ediately with plenty o rinsing.	CAS 25068-38-6 2461-15-6 water. Protect unexposed aminated clothing. Seek m	Concentratio 8 1 d eye. Flush exposed nedical attention if irr	on % by Weight 0-90 0-20 d eye gently using itation, rash, or othe
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attention water for 15-20 minury adverse occur. INHALATION: Move exposed to free comfortable position. INGESTION:	y after handling. slothing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att id clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients ind epoxy resin ane on. Drench the affected area imme- tes. Remove contact lenses while sosed skin with soap and plenty of	ediately with plenty or rinsing. water. Remove cont	CAS 25068-38-6 2461-15-6 water. Protect unexposed aminated clothing. Seek m ng is difficult, give oxygen.	Concentration 8 1 d eye. Flush exposed nedical attention if irr Loosen clothing an	on % by Weight 0-90 0-20 d eye gently using itation, rash, or othe d place exposed in a
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attention water for 15-20 minur SKIN: Wash hands and exp adverse occur. INHALATION: Move exposed to fres comfortable position. INGESTION: Rinse mouth with wa	y after handling. slothing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att ed clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients ane on. Drench the affected area imme- tes. Remove contact lenses while boosed skin with soap and plenty of sh air. Give artificial respiration, if i	ediately with plenty or rinsing. water. Remove cont	CAS 25068-38-6 2461-15-6 water. Protect unexposed aminated clothing. Seek m ng is difficult, give oxygen.	Concentration 8 1 d eye. Flush exposed nedical attention if irr Loosen clothing an	on % by Weight 0-90 0-20 d eye gently using itation, rash, or othe d place exposed in a
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attention water for 15-20 minut SKIN: Wash hands and exp adverse occur. INHALATION: Move exposed to free comfortable position. INGESTION: Rinse mouth with wa MOST IMPORTANT SYMPTOI Shortness of breath,	y after handling. Stothing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att id clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients and epoxy resin ane on. Drench the affected area immet tes. Remove contact lenses while bosed skin with soap and plenty of sh air. Give artificial respiration, if in ter. Do not induce vomiting. Never MS/EFFECTS, ACUTE AND DEL/ headache, nausea, dizziness, irrita	en/face protection. nutes. Remove cont tention. cted in Section 13. ediately with plenty o rinsing. water. Remove cont necessary. If breath er give anything by m AYED: ation- all routes of ex	CAS 25068-38-6 2461-15-6 water. Protect unexposed aminated clothing. Seek m ng is difficult, give oxygen. outh to an unconscious per posure. Acute pneumocon	Concentration 8 1 2 eye. Flush exposed nedical attention if irr Loosen clothing an rson. Seek medical iosis or silicosis from	on % by Weight 0-90 0-20 d eye gently using itation, rash, or othe d place exposed in a attention.
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentio water for 15-20 minut SKIN: Wash hands and exp adverse occur. INHALATION: Move exposed to free comfortable position. INGESTION: Rinse mouth with wa MOST IMPORTANT SYMPTOI Shortness of breath, exposure to crystallin substance is possibly	y after handling. slothing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att id clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients and epoxy resin ane on. Drench the affected area imme- tes. Remove contact lenses while bosed skin with soap and plenty of sh air. Give artificial respiration, if the ter. Do not induce vomiting. Nevee MS/EFFECTS, ACUTE AND DEL/ headache, nausea, dizziness, irrita- te silica dust has occurred. Lungs / carcinogenic to humans. Persons	ediately with plenty or rinsing. water. Remove cont ediately with plenty or rinsing. water. Remove cont necessary. If breath er give anything by m AYED: ation- all routes of ex may be affected by r s with impaired respi	CAS 25068-38-6 2461-15-6 water. Protect unexposed aminated clothing. Seek m ng is difficult, give oxygen. outh to an unconscious per posure. Acute pneumocon epeated or prolonged expo	Concentration 8 1 d eye. Flush expose nedical attention if irr Loosen clothing an rson. Seek medical iosis or silicosis from osure to fibers, result	on % by Weight 0-90 0-20 d eye gently using itation, rash, or othe d place exposed in a attention.
Wash skin thoroughly Contaminated work of Avoid release to the of Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store locke Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Bisphenol-a-(epichlorhydrin) an (2-ethylhexyl) oxy (methy) oxira 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentio water for 15-20 minur SKIN: Wash hands and exp adverse occur. INHALATION: Move exposed to fres comfortable position. INGESTION: Rinse mouth with wa MOST IMPORTANT SYMPTOI Shortness of breath, exposure to crystallin substance is possibly substance. Smoking	y after handling. Stothing should not be allowed out of environment. es/protective clothing/eye protection with soap and water. autiously with water for several min ash occurs: Get medical advice/att id clothing and wash before reuse. ed up. of contents and container as instruct on Ingredients and epoxy resin ane on. Drench the affected area immet tes. Remove contact lenses while bosed skin with soap and plenty of sh air. Give artificial respiration, if is ter. Do not induce vomiting. Never MS/EFFECTS, ACUTE AND DEL/ headache, nausea, dizziness, irritat te silica dust has occurred. Lungs	ediately with plenty or rinsing. water. Remove cont ediately with plenty or rinsing. water. Remove cont necessary. If breath er give anything by m AYED: ation- all routes of ex may be affected by r s with impaired respi /.	CAS 25068-38-6 2461-15-6 water. Protect unexposed aminated clothing. Seek m ng is difficult, give oxygen. outh to an unconscious per posure. Acute pneumocon epeated or prolonged expor ratory function may be more	Concentration 8 1 d eye. Flush expose nedical attention if irr Loosen clothing an rson. Seek medical iosis or silicosis from osure to fibers, result	on % by Weight 0-90 0-20 d eye gently using itation, rash, or othe d place exposed in attention.

CONTROL PARAMETERS:			
CONTROL PARAMETERS: OSHA/PEL: Not establi	shed.		
	shed.		
RECOMMENDED MONITORING:			
If this product contains in	ngredients with exposure limits, pers		cal monitoring may be required to determine
the effectiveness of the	ventilation or other control measures	and/or the necessary to use respirate	bry equipment. Reference can be made of
European Standard EN			agents for the determination of hazardous
substance			
substance.		available in the immediate vicinity of	fuse or handling Provide exhaust ventilation
ENGINEERING CONTROLS:		e available in the immediate vicinity of	f use or handling. Provide exhaust ventilation
ENGINEERING CONTROLS: Emergency eyewash for			
ENGINEERING CONTROLS: Emergency eyewash for		ions of vapor and mist below the app	licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor	ntrols to keep the airborne concentra		licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E	ntrols to keep the airborne concentra Exposure-OELS).		licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor	ntrols to keep the airborne concentra Exposure-OELS).		licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E	ntrols to keep the airborne concentra Exposure-OELS).		licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E	ntrols to keep the airborne concentra Exposure-OELS).		licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E	ntrols to keep the airborne concentra Exposure-OELS).		licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E	ntrols to keep the airborne concentra Exposure-OELS).		licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E	ntrols to keep the airborne concentra Exposure-OELS).		licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUIN	ntrols to keep the airborne concentra Exposure-OELS). PMENT:	ions of vapor and mist below the app	
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUI	ntrols to keep the airborne concentra Exposure-OELS). PMENT:	ions of vapor and mist below the app	
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUI	ntrols to keep the airborne concentra Exposure-OELS). PMENT:	ions of vapor and mist below the app	licable workplace exposure limits indicated
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh	ions of vapor and mist below the app	te eyewear. Wear equipment for eye
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh	ions of vapor and mist below the app	te eyewear. Wear equipment for eye
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh	ions of vapor and mist below the app	te eyewear. Wear equipment for eye
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	te eyewear. Wear equipment for eye
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU)
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh pproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac	ty fitting safety goggles are appropriate standards such as NIOSH (US) or d resistant to the substance. Select gocrdance with applicable laws and go	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh pproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac	ty fitting safety goggles are appropriate standards such as NIOSH (US) or d resistant to the substance. Select gocrdance with applicable laws and go	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh pproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac	ty fitting safety goggles are appropriate standards such as NIOSH (US) or d resistant to the substance. Select gocrdance with applicable laws and go	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUII EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh pproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac	ty fitting safety goggles are appropriate standards such as NIOSH (US) or d resistant to the substance. Select gocrdance with applicable laws and go	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh pproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac	ty fitting safety goggles are appropriate standards such as NIOSH (US) or d resistant to the substance. Select gocrdance with applicable laws and go	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh pproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac	ty fitting safety goggles are appropriate standards such as NIOSH (US) or d resistant to the substance. Select gocrdance with applicable laws and go	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh pproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac	ty fitting safety goggles are appropriation of the substance. Select of the substance.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acoust touching outer service. Avoid ski	tly fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select of cordance with applicable laws and go n contact with used gloves. Wear pro	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acoust touching outer service. Avoid ski	tly fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select of cordance with applicable laws and go n contact with used gloves. Wear pro	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acoust touching outer service. Avoid ski	tly fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select of cordance with applicable laws and go n contact with used gloves. Wear pro	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acoust touching outer service. Avoid ski	tly fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select of cordance with applicable laws and go n contact with used gloves. Wear pro	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acoust touching outer service. Avoid ski	tly fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select of cordance with applicable laws and go n contact with used gloves. Wear pro	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acoust touching outer service. Avoid ski	tly fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select of cordance with applicable laws and go n contact with used gloves. Wear pro	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal	tly fitting safety goggles are appropria d resistant to the substance. Select g cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal	tly fitting safety goggles are appropria d resistant to the substance. Select g cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal	tly fitting safety goggles are appropria d resistant to the substance. Select g cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal	tly fitting safety goggles are appropria d resistant to the substance. Select g cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE	ntrols to keep the airborne concentra Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh oproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal	tly fitting safety goggles are appropria d resistant to the substance. Select g cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa	ntrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tight oproved under appropriate governme Select glove material impermeable are of contaminated gloves after use in ac- but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US)	ty fitting safety goggles are appropria th standards such as NIOSH (US) or d resistant to the substance. Select g cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartrid	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa	ntrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tight oproved under appropriate governme Select glove material impermeable are of contaminated gloves after use in ac- but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US)	ty fitting safety goggles are appropria th standards such as NIOSH (US) or d resistant to the substance. Select g cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartrid	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N	htrols to keep the airborne concentration exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governmes Select glove material impermeable are of contaminated gloves after use in act but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen	ty fitting safety goggles are appropria tstandards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bool laboratory practices. Use proper glove tective clothing. ment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N	htrols to keep the airborne concentration exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governmes Select glove material impermeable are of contaminated gloves after use in act but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen	ty fitting safety goggles are appropria tstandards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bool laboratory practices. Use proper glove tective clothing. ment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N	htrols to keep the airborne concentration exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governmes Select glove material impermeable are of contaminated gloves after use in act but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen	ty fitting safety goggles are appropria tstandards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bool laboratory practices. Use proper glove tective clothing. ment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withous RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M	htrols to keep the airborne concentrates exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governmes Select glove material impermeable are of contaminated gloves after use in ace but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withous RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N	htrols to keep the airborne concentrates exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governmes Select glove material impermeable are of contaminated gloves after use in ace but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M	htrols to keep the airborne concentrates exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governmes Select glove material impermeable are of contaminated gloves after use in ace but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M	htrols to keep the airborne concentration exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governmes Select glove material impermeable are of contaminated gloves after use in act but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M	htrols to keep the airborne concentrates exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governmes Select glove material impermeable are of contaminated gloves after use in ace but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house	ions of vapor and mist below the app ty fitting safety goggles are appropria tstandards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M Avoid contact with skin,	Atrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acc put touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house eyes, and clothing. Before re-wearing	ions of vapor and mist below the app ty fitting safety goggles are appropria ant standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique without RESPIRATORY PROTE appropriate, use a full-fa When necessary, use A	Atrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acc put touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house eyes, and clothing. Before re-wearing	ions of vapor and mist below the app ty fitting safety goggles are appropria ant standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bool laboratory practices. Use proper glove tective clothing. ment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M Avoid contact with skin, 9. Physical & Chemical Propertio	Atrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acc put touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house eyes, and clothing. Before re-wearing	ty fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks ig wash contaminated clothing.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are liges as a backup to engineering controls. and immediately after handling the product.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M Avoid contact with skin,	Atrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acc put touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house eyes, and clothing. Before re-wearing	ions of vapor and mist below the app ty fitting safety goggles are appropria ant standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks	te eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bool laboratory practices. Use proper glove tective clothing. ment shows air-purifying respirators are lges as a backup to engineering controls.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EVE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose or removal technique withor RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENICM Avoid contact with skin, 9. Physical & Chemical Propertite Appearance:	Antrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac pout touching outer service. Avoid ski ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house eyes, and clothing. Before re-wearing es	ty fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks ig wash contaminated clothing.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are liges as a backup to engineering controls. and immediately after handling the product. Not determined.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M Avoid contact with skin, 9. Physical & Chemical Propertio	Atrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tight poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in acc put touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house eyes, and clothing. Before re-wearing	ty fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks ig wash contaminated clothing.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are liges as a backup to engineering controls. and immediately after handling the product.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M Avoid contact with skin, 9. Physical & Chemical Properti Appearance: Physical State/Color:	htrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house eyes, and clothing. Before re-wearing Light yellow.	ty fitting safety goggles are appropriate the standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks ig wash contaminated clothing. Explosive Limit – lower (%): Explosive Limit – upper (%):	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are gles as a backup to engineering controls. and immediately after handling the product.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose or removal technique withor RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENIC M Avoid contact with skin, 9. Physical & Chemical Propertit Appearance:	Antrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac pout touching outer service. Avoid ski ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipmen MEASURES: Perform routine house eyes, and clothing. Before re-wearing es	ty fitting safety goggles are appropria the standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks ig wash contaminated clothing.	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are liges as a backup to engineering controls. and immediately after handling the product. Not determined.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EYE PROTECTIVE EQUID EYE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENICM Avoid contact with skin, 9. Physical & Chemical Properti Appearance: Physical State/Color:	htrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipment MEASURES: Perform routine house eyes, and clothing. Before re-wearing es Light yellow. Slight epoxy odor.	ions of vapor and mist below the app ty fitting safety goggles are appropria nt standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks ig wash contaminated clothing. Explosive Limit – lower (%): Explosive Limit – upper (%): Vapor Pressure @20°:	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are liges as a backup to engineering controls. and immediately after handling the product.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EVE PROTECTIVE EQUID EVE PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique witho RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENICM Avoid contact with skin, 9. Physical & Chemical Properti Appearance: Physical State/Color: Odor:	htrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipment MEASURES: Perform routine house eyes, and clothing. Before re-wearing es Light yellow. Slight epoxy odor. Not determined.	ions of vapor and mist below the app ty fitting safety goggles are appropria nt standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks ig wash contaminated clothing. Explosive Limit – lower (%): Explosive Limit – upper (%): Vapor Pressure @20°: Vapor Density:	Ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and bod laboratory practices. Use proper glove tective clothing. Imment shows air-purifying respirators are leges as a backup to engineering controls. and immediately after handling the product.
ENGINEERING CONTROLS: Emergency eyewash for or other engineering cor above. (Occupational E PERSONAL PROTECTIVE EQUID EVERSONAL PROTECTIVE EQUID EVERSONAL PROTECTION: Fa protection tested and ap SKIN PROTECTION: S degradation. Dispose o removal technique withor RESPIRATORY PROTE appropriate, use a full-fa When necessary, use N GENERAL HYGIENICM Avoid contact with skin, P. Physical & Chemical Properti Appearance: Physical State/Color:	htrols to keep the airborne concentrates Exposure-OELS). PMENT: ace shield (8-inch minimum) with tigh poproved under appropriate governme Select glove material impermeable ar of contaminated gloves after use in ac but touching outer service. Avoid skii ECTION: Not required under normal ace particle respirator type N100 (US IIOSH approved breathing equipment MEASURES: Perform routine house eyes, and clothing. Before re-wearing es Light yellow. Slight epoxy odor.	ions of vapor and mist below the app ty fitting safety goggles are appropria nt standards such as NIOSH (US) or d resistant to the substance. Select go cordance with applicable laws and go n contact with used gloves. Wear pro conditions of use. Where risk assess o or type P3 (EN143) respirator cartric keeping. Wash hands before breaks ig wash contaminated clothing. Explosive Limit – lower (%): Explosive Limit – upper (%): Vapor Pressure @20°:	ate eyewear. Wear equipment for eye EN 166 (EU) glove material based on rates of diffusion and ood laboratory practices. Use proper glove tective clothing. sment shows air-purifying respirators are liges as a backup to engineering controls. and immediately after handling the product.

Melting/Freezing Point: Boiling Point/Range: Partition Coeff (n-octanol/water):

Solubility:

Auto-Ignition Temperature:

Flash Point (closed cup):

Not determined.

>260° C (500°F)

Not determined.

Insoluble in water.

252°C (486°F) (PMCC)

Not determined.

 10. Stability & Reactivity Information REACTIVITY: Nonreactive under normal conditions. CHEMICAL STABILITY: Stable under normal conditions. Upon prolonged storage the material may crystallize which is reversible condition: crystallized material or liquefied back by heating slowly to 50°C for 6-24 hours. POSSIBLE HAZARDOUS REACTIONS: Masses of more than one-pound (0.5 kg) product plus an aliphatic amine will cause irreversible polymerization with considerable heat bui Material will polymerize in contact with Sodium hydroxide. INCOMPATIBLE MATERIALS: Acids, bases, oxidizing agents, hydrogen fluoride, acetylene, and ammonia. CONDITIONS TO AVOID: Avoid elevated temperatures, potentially violent decomposition can occur above 350°C. HAZARDOUS DECOMPOSITION PRODUCTS: 25068-38-6: Strong oxidizing, acids, amines, and bases. 11. Toxicological Information 	
Nonreactive under normal conditions. CHEMICAL STABILITY: Stable under normal conditions. Upon prolonged storage the material may crystallize which is reversible condition: crystallized material of liquefied back by heating slowly to 50°C for 6-24 hours. POSSIBLE HAZARDOUS REACTIONS: Masses of more than one-pound (0.5 kg) product plus an aliphatic amine will cause irreversible polymerization with considerable heat bui Material will polymerize in contact with Sodium hydroxide. INCOMPATIBLE MATERIALS: Acids, bases, oxidizing agents, hydrogen fluoride, acetylene, and ammonia. CONDITIONS TO AVOID: Avoid elevated temperatures, potentially violent decomposition can occur above 350°C. HAZARDOUS DECOMPOSITION PRODUCTS: 25068-38-6: Strong oxidizing, acids, amines, and bases.	
Stable under normal conditions. Upon prolonged storage the material may crystallize which is reversible condition: crystallized material of liquefied back by heating slowly to 50°C for 6-24 hours. POSSIBLE HAZARDOUS REACTIONS: Masses of more than one-pound (0.5 kg) product plus an aliphatic amine will cause irreversible polymerization with considerable heat bui Material will polymerize in contact with Sodium hydroxide. INCOMPATIBLE MATERIALS: Acids, bases, oxidizing agents, hydrogen fluoride, acetylene, and ammonia. CONDITIONS TO AVOID: Avoid elevated temperatures, potentially violent decomposition can occur above 350°C. HAZARDOUS DECOMPOSITION PRODUCTS: 25068-38-6: Strong oxidizing, acids, amines, and bases.	
 POSSIBLE HAZARDOUŚ REACTIONS: Masses of more than one-pound (0.5 kg) product plus an aliphatic amine will cause irreversible polymerization with considerable heat bui Material will polymerize in contact with Sodium hydroxide. INCOMPATIBLE MATERIALS: Acids, bases, oxidizing agents, hydrogen fluoride, acetylene, and ammonia. CONDITIONS TO AVOID: Avoid elevated temperatures, potentially violent decomposition can occur above 350°C. HAZARDOUS DECOMPOSITION PRODUCTS: 25068-38-6: Strong oxidizing, acids, amines, and bases. 	ild-up.
Material will polymerize in contact with Sodium hydroxide. INCOMPATIBLE MATERIALS: Acids, bases, oxidizing agents, hydrogen fluoride, acetylene, and ammonia. CONDITIONS TO AVOID: Avoid elevated temperatures, potentially violent decomposition can occur above 350°C. HAZARDOUS DECOMPOSITION PRODUCTS: 25068-38-6: Strong oxidizing, acids, amines, and bases.	
CONDITIONS TO AVOID: Avoid elevated temperatures, potentially violent decomposition can occur above 350°C. HAZARDOUS DECOMPOSITION PRODUCTS: 25068-38-6: Strong oxidizing, acids, amines, and bases.	
HAZARDOUS DECOMPOSITION PRODUCTS: 25068-38-6: Strong oxidizing, acids, amines, and bases.	
11. Toxicological Information	
ACUTE TOXICITY:	
Oral: 25068-38-6 LD50 Oral-rat->5000 mg/kg	
Dermal: 2461-15-6 LD50 Oral-rabbit-20,000 mg/kg Inhalation: :ow volatility: not to be significant route of exposure.	
CHRONIC TOXICITY:	
Inhalation: May cause respiratory irritation. SKIN CORROSION IRRITATION:	
(guinea pig) Causes allergic skin reactions 1408-60-7	
SERIOUS EYE DAMAGE/IRRITATION: (rabbit) causes serious eye irritation, corneal injury is not likely.	
RESPIRATORY OR SKIN SENSITIZATION: May cause skin sensitization in some individuals.	
CARCINOGENIC INFORMATION: N/A, Not listed by IARC, NTP, OSHA	
REPRODUCTIVE TOXICITY: No additional information.	
STOT (single and repeated exposure): 2461-15-6: Inhalation - may cause respiratory irritation.	
ADDITIONAL TOXICOLOGICAL INFORMATION:	
No additional information.	
12. Ecological Information ECOTOXICITY:	
2461-15-6: LC50-Carassius(goldfish)-14 mg/l-24 h	
PERSISTENCE AND DEGRADABILITY:	
25068-38-6: Result: According to the results of test of biodegradability this product is not readily biodegradable. 1217-11-7: long term degradation products may arise.	
BIOACCUMULATIVE POTENTIAL:	
BCF=31, Log Pow=3 (low potential to bioaccumulate in aquatic organisms). MOBILITY IN SOIL:	
No additional information.	
OTHER ADVERSE EFFECTS:	
OTHER ADVERSE EFFECTS: No additional information.	
No additional information. 13. Disposal Consideration	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or containers	liners
No additional information. 13. Disposal Consideration	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or conta must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or conta must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or containers as usual product. Product or containers to be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or contar must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated.	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or contar must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated. UN NUMBER:	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or containers and use the disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated. UN NUMBER: ADR,AND,DOT,IMDG,IATA: 3082 LIMITED QUANTITY :	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or containers and the disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated. UN NUMBER: ADR,AND,DOT,IMDG,IATA: 3082	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or contar must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated. UN NUMBER: ADR,AND,DOT,IMDG,IATA: 3082 LIMITED QUANTITY : None. Non Bulk RQ (if applicable): none	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or contar must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated. UN NUMBER: ADR,AND,DOT,IMDG,IATA: 3082 Non Bulk RQ (if applicable): none RQ (if applicable): none Proper shipping name: Environmentally Proper shipping name: Environmentally	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or contar must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated. UN NUMBER: ADR,AND,DOT,IMDG,IATA: 3082 LIMITED QUANTITY : None. Non Bulk RQ (if applicable): none Proper shipping name: Environmentally Proper shipping name: Environmentally Hazardous substance, liquid, n.o.s. Hazardous substance, liquid, n.o.s.	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or conta must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated. UN NUMBER: ADR,AND,DOT,IMDG,IATA: 3082 LIMITED QUANTITY : None. Bulk: RQ (if applicable): none Proper shipping name: Environmentally Proper shipping name: Environmentally Hazardous substance, liquid, n.o.s. Hazardous substance, liquid, n.o.s. Hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or containers and product or properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information VIS DOT: Not regulated. VIN NUMBER: ADR, AND, DOT, IMDG, IATA: 3082 LIMITED QUANTITY : None. Non Bulk RQ (if applicable): none Proper shipping name: Environmentally Hazardous substance, liquid, n.o.s. Hazardous substance, liquid, n.o.s. Hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A- (reaction product: bisphenol-A-	
No additional information. 13. Disposal Consideration Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or conta must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardou waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. 14. Transportation Information US DOT: Not regulated. UN NUMBER: ADR,AND,DOT,IMDG,IATA: 3082 LIMITED QUANTITY : None. Bulk: RQ (if applicable): none Proper shipping name: Environmentally Proper shipping name: Environmentally Hazardous substance, liquid, n.o.s. Hazardous substance, liquid, n.o.s. Hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-	

Bulk: EmS No: F-A, S-F Marine Pollutant(if applicable): yes Non Bulk

Marine Pollutant (if applicable): yes

15. Regulatory Information US FEDERAL REGULATIONS:

SARA 311/312 (Specific toxic chemical listings): Acute health hazard.

- SARA 313 (Specific toxic chemical listings): None of the ingredients are listed.
- RCRA (hazardous waste code): None of the ingredients are listed.
- TSCA (Toxic Substances Control Act): All ingredients are listed.

CERCLA (Comprehensivce Environmental Response, Compensation, and Liability Act): None of the ingredients are listed. PROPOSITION 65 (California):

PROPOSITION 65 (California):

Chemicals known to cause cancer: None of the ingredients are listed.

- Chemical known to cause reproductive toxicity for females: None of the ingredients are listed.
- Chemicals known to cause reproductive toxicity for males: None of the ingredients are listed.
- Chemicals known to cause developmental toxicity: None of the ingredients are listed.

CANADA:

Canadian Domestic Substances List (DSL): None of the ingredients are listed.

16. Other Information

N/A = Not Applicable; N/D = Not Determined

	NFPA	Health Hazards: 2	Flammability: 1	Instability: 0	Physical & Chemical Properties:
	HMIS	Health Hazards: 3	Flammability: 1	Physical hazards: 0	Personal protection:

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.



1. Product and Company Ide							
PRODUCT NUMBER:	2448		COMPAN	Y PHONE:		1-800-24	11-8180
PRODUCT NAME:	FIRM GRIP P	ART B	EMERGE	NCY TELEPHON	E:	1-800-24	11-8180
PRODUCT DESCRIPTION:	Three-Part Ep Coating	boxy Skid-Resistant Flo				1-800-535-5053	
COMPANY INFORMATION:	PRO CHEM,	ss Lakes Parkway					
2. Hazards Identification							
GHS CLASSIFICATION:		SIGNAL WORD:	SYMBOL:				
Skin corrosion/irritation, catego	ory 2	DANGER					NV
Eye irritation, category 2	-						
Skin sensitization, category 1	llau dia anala						
Specific target organ toxicity fo exposure, category 1	llowing single			$\mathbf{\vee}$	$\mathbf{\vee}$	$\mathbf{\vee}$	$\mathbf{\vee}$
Acute toxicity(oral, dermal, inha	alation),						
category 1	,,						
Reproductive toxicity, category							
Chronic hazards to the aquatic	environment,						
category 2 HAZARD STATEMENTS:							
HAZARD STATEMENTS: Harmful if swallowed							
Causes skin burns a							
Causes serious eye							
May cause an allergi							
May cause respirator							
Suspected of damag		unborn child.					
PRECAUTIONARY STATEME Keep container tight							
		duct container or label a	at hand				
Keep out reach of ch							
Read label before us							
Avoid breathing dust		spray.					
Wash skin thoroughly	v after handling						
Contaminated work of	clothing should no	ot be allowed out of the	workplace.				
Contaminated work of Avoid release to the	clothing should no environment.						
Contaminated work of Avoid release to the Wear protective glov	clothing should no environment. es/protective clot	hing/eye protective/face					
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w	clothing should no environment. es/protective cloth vith soap and wat	hing/eye protective/face er.	e protection.	lenses, if present	and easy to do	. Continue rinsin	g.
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca	Clothing should no environment. es/protective clot vith soap and wat autiously with wat	hing/eye protective/face	e protection. Remove contact		and easy to do	Continue rinsin	g.
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse of IF INHALED: Remov If skin irritation or a re	clothing should no environment. es/protective clotl vith soap and wat autiously with wat re victim to fresh a ash occurs. Get	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attentiol	e protection. Remove contact comfortable for b		and easy to do	Continue rinsin	g.
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse of IF INHALED: Remov If skin irritation or a ra Take off contaminate	clothing should no environment. es/protective clotl vith soap and wat autiously with wat re victim to fresh a ash occurs. Get	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attentiol	e protection. Remove contact comfortable for b		and easy to do	Continue rinsin	g.
Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a r Take off contaminate Collect spillage.	clothing should no environment. es/protective cloti vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed clothing and wa	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attentiol	e protection. Remove contact comfortable for b		and easy to do	Continue rinsin	g.
Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse of IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed clothing and wa ed up.	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.		and easy to do	. Continue rinsin	g.
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed clothing and wa ed up. ated place. Keep	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attentiol	e protection. Remove contact comfortable for b n.		and easy to do	. Continue rinsin	ıg.
Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse c IF INHALED: Remov If skin irritation or a r Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventile Disposal: Dispose of 3. Composition / Information	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed clothing and wa ed up. ated place. Keep of contents and co	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	eathing.			
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed clothing and wa ed up. ated place. Keep of contents and co	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	cas		oncentration %	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed clothing and wa ed up. ated place. Keep of contents and co	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	cas 14807-96-6		oncentration % 30-35	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7		oncentration % 30-35 15-20	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,41-methylenebis (cyclohexyla	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7 1761-71-3		oncentration % 30-35 15-20 18-23	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,41-methylenebis (cyclohexyla Nonyphenol	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3		oncentration % 30-35 15-20 18-23 3-6	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,4 ¹ -methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6		oncentration % 30-35 15-20 18-23 3-6 2-3	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,41-methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an leron(II,III) oxide	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9		oncentration % 30-35 15-20 18-23 3-6 2-3 <2	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,4 ¹ -methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an leron(II,III) oxide Silica amorphous, fumed, crys	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9 112945-52-5		oncentration % 30-35 15-20 18-23 3-6 2-3 <2 <1	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,4 ¹ -methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an leron(II,III) oxide Silica amorphous, fumed, crys	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9		oncentration % 30-35 15-20 18-23 3-6 2-3 <2	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,4 ¹ -methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an leron(II,III) oxide Silica amorphous, fumed, crys Benzyl alcohol	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9 112945-52-5		oncentration % 30-35 15-20 18-23 3-6 2-3 <2 <1	
Contaminated work of Avoid release to the Wear protective glov IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,4 ¹ -methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an Ieron(II,III) oxide Silica amorphous, fumed, crys Benzyl alcohol 4. First Aid Measures	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ad clothing and wa ed up. ated place. Keep of contents and co on Ingredients	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9 112945-52-5		oncentration % 30-35 15-20 18-23 3-6 2-3 <2 <1	
Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,4 ¹ -methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an Ieron(II,III) oxide Silica amorphous, fumed, crys Benzyl alcohol 4. First Aid Measures EMERGENCY OVERVIEW	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed clothing and wa ed up. ated place. Keep of contents and co on Ingredients mine) d epoxy resin t,-free	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n. d. n Section 13.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9 112945-52-5 100-51-6		oncentration % 30-35 15-20 18-23 3-6 2-3 <2 <1 15-20	by Weight
Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,41-methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an leron(II,III) oxide Silica amorphous, fumed, crys Benzyl alcohol 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentior rinsing.	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed up. ated place. Keep of contents and co on Ingredients umine) d epoxy resin t,-free	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n. d. Section 13.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9 112945-52-5 100-51-6 ng water for 15-2	0 minutes. Ren	oncentration % 30-35 15-20 18-23 3-6 2-3 <2 <1 15-20 nove contact lens	by Weight
Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,41-methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an Ieron(II,III) oxide Silica amorphous, fumed, crys Benzyl alcohol 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentio rinsing. SKIN: Wash hands and exp	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed up. ated place. Keep of contents and co on Ingredients d epoxy resin t,-free	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse. container tightly closed ontainer as instructed ir	e protection. Remove contact comfortable for b n. d. Section 13.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9 112945-52-5 100-51-6 ng water for 15-2 used skin gently u	0 minutes. Ren	oncentration % 30-35 15-20 18-23 3-6 2-3 <2 <1 15-20 nove contact lensity vater for 15-20 m	by Weight ses while ninutes. Seek
Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,41-methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an Ieron(II,III) oxide Silica amorphous, fumed, crys Benzyl alcohol 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentio rinsing. SKIN: Wash hands and exp medical advice if disc	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed up. ated place. Keep of contents and co on Ingredients d epoxy resin t,-free	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse.	e protection. Remove contact comfortable for b n. d. Section 13.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9 112945-52-5 100-51-6 ng water for 15-2 used skin gently u	0 minutes. Ren	oncentration % 30-35 15-20 18-23 3-6 2-3 <2 <1 15-20 nove contact lensity vater for 15-20 m	by Weight ses while ninutes. Seek
Contaminated work of Avoid release to the Wear protective glow IF ON SKIN: Wash w IF IN EYES: Rinse ca IF INHALED: Remov If skin irritation or a ra Take off contaminate Collect spillage. Storage: Store lock Store in a well-ventila Disposal: Dispose of 3. Composition / Information CHEMICAL NAME Hydrous magnesium silicate Titanium dioxide 4,4 ¹ -methylenebis (cyclohexyla Nonyphenol bisphenol-A-(epichlorhydrin)an Ieron(II,III) oxide Silica amorphous, fumed, crys Benzyl alcohol 4. First Aid Measures EMERGENCY OVERVIEW EYES: Seek medical attentio rinsing. SKIN: Wash hands and exp	clothing should no environment. es/protective clot vith soap and wat autiously with wat re victim to fresh a ash occurs. Get ed up. ated place. Keep of contents and co on Ingredients d epoxy resin t,-free	hing/eye protective/face er. ter for several minutes. air and keep at rest in a medical advice/attention ash before reuse. container tightly closed ontainer as instructed ir	e protection. Remove contact comfortable for b n. d. Section 13.	CAS 14807-96-6 13463-67-7 1761-71-3 84852-15-3 25068-38-6 1317-61-9 112945-52-5 100-51-6 ng water for 15-2 used skin gently u	0 minutes. Ren	oncentration % 30-35 15-20 18-23 3-6 2-3 <2 <1 15-20 nove contact lensity vater for 15-20 m	by Weight ses while ninutes. Seek

comfortable position.
INGESTION:
Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Seek medical attention. MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:
Shortness of breath, headache, nausea, dizziness, irritation-all routes of exposure. Acute pneumoconiosis or silicosis from overwhelming
exposure to crystalline silica dust has occurred. Lungs may be affected by repeated or prolonged exposure to fibers, resulting in fibrosis. This
substance is possible carcinogenic to humans. Persons with impaired respiratory function may be more susceptible to the effects of this substance. Smoking can increase the risk of lung injury.
INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:
If seeking medical attention, provide SDS document to physician. Physician should treat symptomatically.
5. Fire-Fighting Measures
SUITABLE FIRE EXTINGUISHING MEDIA:
Dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam. Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition. If large quantities of combustibles are involved, use water in flooding quantities as spray and fog. Use water
spray to knock down vapors.
UNSUITABLE FIRE EXTINGUISHING MEDIA:
For safety reasons unsuitable extinguishing agents: Do not use water on material itself; water or foam may cause frothing. SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:
Avoid inhaling gases, fumes, dust, mist, and aerosols. Avoid contact with skin, eyes, and clothing.
SPECIFIC FIRE-FIGHTING METHODS:
If material not on fire and not involved in fire: keep sparks, flames, and other sources of ignition away. Keep material out of water sources and sewers. Build dikes to contain flow as necessary. Avoid inhaling gases, fumes, dust, mist, vapor, and aerosols. Avoid contact with skin, eyes,
and clothing. Move product containers away from fire. Avoid generating dust, fine dust dispersed in air in sufficient concentrations, and in the
presence of an ignition source is a potential dust explosion hazard.
SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS: Wear protective eyewear, gloves, and clothing. Refer to Section 8.
6. Accidental Release Measures PERSONAL PRECAUTIONS:
Water spill: Neutralize with agricultural lime (CaO), crushed limestone (CaCO3) or sodium bicarbonate (naHCO3). If dissolved, in region of 10
ppm or greater concentration, apply activated carbon at ten times the spilled amount. Land spill: Dig a pit, pond, lagoon, holding area (should be
sealed with an impermeable flexible membrane liner) to contain liquid or solid material. Dike surface flow using soil, sand bags, foamed polyurethane, or foamed concrete. Absorb bulk liquid with fly ash or cement powder. Neutralize as noted for water spill. Ensure adequate
ventilation. Ensure that air-handling systems are operational.
ENVIRONMENTAL PRECAUTIONS:
Should not be released into environment. Prevent from reaching drains, sewer, or waterway. Collect contaminated soil for characterization per Section 13.
METHODS & MATERIALS FOR CONTAINMENT & CLEAN UP:
Sweep up and shovel. Soak up with inert absorbent material and dispose of as hazardous waste. Wear protective eyewear, gloves, and
clothing. Personal protection: P2 filter respirator for harmful particles. Dust deposits should not be allow to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e. clearing
dust surface with compressed air). Collect solids in powder form using vacuum with HEPA filter. Do not handle broken packages unless
wearing appropriate chemical protective equipment. Wash away any material which may have contacted the body with copious amounts of
water and soap. Refer to Section 8. Always obey local regulations. If necessary, use trained response staff or contractor. Evacuate personnel to safe areas. Containerize for disposal. Refer to Section 13. Keep in suitable closed containers for disposal. Sufficient concentrations, and in
the presence of an ignition source is a potential dust explosion hazard.
REFERENCE TO OTHER SECTIONS:
None.
7. Handling and Storage
SAFE HANDLING:
Avoid contact with skin, eyes, and clothing. Follow good hygiene procedures when handling chemical materials. Do not take working clothes home. Refer to Section 8. Follow proper disposal methods. Combustible dusts formation is a risk. Refer to Section 13. Do not eat, drink,
smoke, or use personal products when handling chemical substance.
SAFE STORAGE & INCOMPATIBILITIES:
Store in a cool location. Keep away from food and beverages. Protect from freezing and physical damage. Provide ventilation for containers. Keep container tightly sealed. Store away from incompatible materials. Avoid storage near extreme heat, ignition sources or open flame.
8. Exposure Controls / Personal Protection
CONTROL PARAMETERS: 14807-96-6, hydrous magnesium silicate, OHSA PEL TWA 2.0 mg/m ³ , NIOSH TWA 2.0 mg/m ³ , ACGIH TLV TWA 2.0 mg/m ³
13463-67-7, Titanium dioxide, ACGIH TLV: 10, OSHA PEL:10
112945-52-5, Silica, amorphous, fumed, cryst-free, ACGIH TLV TWA: 10 mg/m ³ (inhaled particles)OSHA PEL TWA: 15 mg/m ³ (total dust)
ENGINEERING CONTROLS: Emergency eyewash fountains and safety showers should be available in the immediate vicinity of use or handling. Provide exhaust ventilation
or other engineering controls to keep the airborne concentrations of vapor and mist below the applicable workplace exposure limits indicated
above. (Occupational Exposure-OELS). It is recommended that all dust control equipment such as local exhaust ventilation and material
transport systems involved in handling of this product contain explosive relief vents or an explosive suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a
manner to prevent the escape of dust into the work area (i.e. there is no leakage from the equipment) Use under a fume hood.
PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Face shield (8-inch minimum) with tightly fitting safety goggles are appropriate eyewear. Wear equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU)

SKIN PROTECTION: Select glove material impermeable and resistant to the substance. Select glove material based on rates of diffusion and degradation. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Use proper glove removal technique without touching outer service. Avoid skin contact with used gloves. Wear protective clothing.

RESPIRATORY PROTECTION: Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN143) respirator cartridges as a backup to engineering controls. When necessary use NIOSH approved breathing equipment.

GENERAL HYGIENIC MEASURES: Perform routine housekeeping. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes, and clothing. Before re-wearing wash contaminated clothing.

9. Physical & Chemical Properties

Appearance:		Flammability(solid/gas):	Not determined.
Physical State/Color:	Med viscosity liquid & colors	Explosive Limit – lower (%):	Not available.
Odor:	Ammonia.	Explosive Limit – upper (%):	Not available.
Odor Threshold:	Not determined.	Vapor Pressure @20°:	Not determined.
pH:	Not determined.	Vapor Density:	Not determined.
Melting/Freezing Point:	Not determined.	Relative Density:	1.77
Boiling Point/Range:	Not determined.	Solubility:	Not available.
Partition Coeff (n-octanol/water):	Not determined.	Auto-Ignition Temperature:	Not determined.
Density:	Not determined.	Decomposition Temperature:	Not determined.
Flash Point (closed cup):	Not determined.	Evaporation Rate:	Not determined.

10. Stability & Reactivity Information

REACTIVITY:

Nonreactive under normal conditions.

CHEMICAL STABILITY:

Stable under normal conditions. Chemically inert, properties are inert; affected by change in pH.

POSSIBLE HAZARDOUS REACTIONS:

None under normal conditions.

INCOMPATIBLE MATERIALS:

Strong acids, strong bases, oxidizing agents, hydrogen fluoride. CONDITIONS TO AVOID:

Incompatible materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

Magnesium oxide, Titanium oxides, carbon oxides, nitrogen oxides, ammonia. When heated to decomposition it emits acrid smoke and irritating fumes.

11. Toxicological Information

ACUTE TOXICITY:

Oral: 13463-67-7 LD50:>5,000 mg/kg Species: Rat Method: Estimated Inhalation: 13463-67-7 LC 50 rat-male and female. The substance can be absorbed into the body by inhalation. Dermal: >1/000 mg/kg LD50 rabbit-male and female 84852-15-3 Dermal LD50 rabbit 2031 mg/kg Oral: 84852-15-3, LD50 oral-Rat-male and female-1412 mg/kg CHRONIC TOXICITY: Inhalation: May cause respiratory irritation. CORROSION IRRITATIÓN: Dermal: Section 2, Classified as skin irritant. Ocular: Section 2, Classified as eye irritant. SENSITIZATION: Classified as a skin sensitizer. STOT (Single Target Organ): Classified as respiratory irritant. NUMERICAL MEASURES: No additional information. CARCINOGENIC INFORMATION: IARC Group 3(not classifiable) Monograph 68(1997)(listed under Amorphous silica) **MUTAGENICITY:** Hamster lungs DNA inhibition. Hamster ovary sister chromatid exchange. **REPRODUCTIVE TOXICITY:** Classified as possible causing reproductive harm to fertility or unborn child. 12. Ecological Information ECOTOXICITY: Fish (acute 84852-15-3): 96 hr LC50 Pimephales promelas: 0.135 MG/L {flow-through}: 96 hr LC50 lepomis macrochirus: 0.1351 mg/l {flowthrough} Crustacea (acute 84852-15-3): 48 hr EC50 Daphnia magna: 0.14 mg/l Algae (acute 84852-15-3): 96 hr EC50 Pseudokirchneriella subcapitata: 0.36-0.48 mg/l {static}: 72 hr EC50 Pseudokirchneriella subcapitata: 0.16-0.72 mg/l {static}; 72 hr EC50 Desmodesmus subspicatus: 1.3 mg/l PERSISTENCE AND DEGRADABILITY: Aerobic-Exposure time 28 d result:<10%-according to the results of tests of biodegradable this product is not readily biodegradable 84852-15-3: aerobic-exposure time 28 d result: 62% readily biodegradable. There is no data for the product regarding degradability.

BIOACCUMULATIVE POTENTIAL:

BCF *84852<u>-15-3): 271 species: fish</u>

No additional information.

13. Disposal Consideration

Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as usual product. Product or containers must not be disposed together with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must also consult local, regional, and national hazardous waste regulations. Ensure complete and accurate classification. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

14. Transportation Information			
UN NUMBER:			
2735 UN PROPER SHIPPING NAME:			
Amines, Liquid, corrosive, NOS	(4.4 ¹ methylne bis cyclo ł	exanamine)	
LIMITED QUANTITY :		ioxalialitito)	
None.			
Bulk:	Non Bulk		
RQ (if applicable): none Proper shipping name: Environmentally			
Hazardous substance, liquid, n.o.s.			
Average molecular weight <=700)			
Hazard Class: 8	Hazard class: 8		
Packing Group: II Marine Pollutant(84852-15-3):	Packing Group: Marine Pollutan		
Marine Politiani(64652-15-3).		l (04002-10-3 <i>)</i> .	
15. Regulatory Information			
US FEDERAL REGULATIONS:			
SARA 311/312 (Specific toxic			a testi se di se des Obersi sel Osteren Nereda baral)
RCRA (hazardous waste cod			ntration (listed under Chemical Category Nonylphenol)
TSCA (Toxic Substances Co			
CERCLA (Comprehensivce E			bility Act): None of the ingredients are listed.
PROPOSITION 65 (California):	44007 00 0 h la		
Chemicals known to cause on Chemical known to cause re			lients are listed
Chemicals known to cause r			
Chemicals known to cause d			
CANADA:			
Canadian Domestic Substan Canadian NPRI Ingredientn I			are listed
Canadian NPRI Ingredient Di			
	, 	5	
16. Other Information			
GHS Full Text Phrases: None Abbreviations and Acronyms:			
IMDG: International Maritime Code for Da	naerous Goods		
IATA: International Air Transport Associat			
GHS: Globally Harmonized System of cla			
ACGIH; American Conference of Governm			
CAS: Chemical Abstracts Service (divisio NFPA: National Fire Protection Association		al Society)	
HMIS: Hazardous Materials Identification			
ACGIH: American Conference of Government			
WHMIS: Workplace Hazardous Materials	Information System (CAN	IADA)	
DNEL: Derived No-Effect level (Reach) PNEC: Predicted No-Effect Concentration	(Reach)		
CFR: Code of Federal Regulations (USA)			
SARA: Superfund Amendments and Real			
RCRA: Resource Conservation and Reco			
TSCA: Toxic Substance Control Act (USA NPRI: National Pollutant Release Invento			
DOT: US Department of Transportation			
CAS: Chemical Abstracts Service (Divisio		cal Society)	
NFPA: National Fire Protection Association			
HMIS: Hazardous Materials Identification			
WHMIS: Workplace Hazardous Materials DNEL: Derived No-Effect Level (Reach)	information System (CAN	IADA)	
HMIS Health Hazards: 3	Flammability: 1	Physical hazards: 0	Personal protection: X
DISCLAIMER:	· · · · ·	de la compte d'action de	

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or

completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.