

Greasomatic #2723

Single-Point Automatic Lubricator System



Features:

- Low cost electro-mechanical, single-point automatic lubricator
- Can be up to 6 feet away from point of lubrication
- Motor-driven, positive-displacement pump
- 73 psi operating pressure
- Contains 120 cc of lubricant
- Power Supply: Sealed chemical generator
- Single-use pump
- Easy dial programming, up to 7 output timing settings
- Working temperature range from 32°F to 104°F
- Plastic design makes it ideal for hazardous, wet or corrosive locations in standard ambient temperatures



Description:

The GREASOMATIC reduces production downtime by lubricating your equipment while it is still in operation. This system is powered by a simple chemical reaction. Upon activation, the combination of galvin and electrolyte creates a steady release of hydrogen gas, which powers the piston to discharge the grease of your choosing. Each unit has a translucent window to monitor the level of lubricant. This system uses easy dial programming, with up to 7 output timing settings. Not only does the use of an automatic lubricator save money by reducing man hours, it prevents over and under lubrication problems related to manual lubrication. A small, precise amount of fresh lubricant is delivered at regular intervals directly to the lube point. This closed system prevents airborne contaminants from getting in the grease.

Applications:

- Fans
- Compressors
- Pumps
- Motors & engines
- Crushers
- Packing machinery
- Conveyors
- Elevators
- HVAC equipment
- Open gears
- Blowers
- Chain drives

For Use By:

- Printing Industry
- Manufacturing Companies
- Poultry Plants
- Cement & Stone Industry
- Airports
- Steel Plants
- Pulp & Paper Industry
- Elevator Repair
- Recycling plants
- HVAC Industry
- Bottling Plants
- Waste Management Sites

Directions:

- Set time: Turn black control knob clockwise until white triangle points to time setting you want.
- Lock in time: Push red button down until it is level with yellow dial.
- Activate: Turn black control knob clockwise 10 or 12 times until it spins freely and you hear a clicking sound.
- Record: Enter replacement date on cartridge and in your records.
- Install: Pre-charge remote lines with the same grease. Screw GREASOMATIC into fitting until hand-tight.

Greasomatic Kit Includes:

- 1 mounting clamp
- 1- 6' x 5/16" OD, prefilled tubing
- 2-Quick connect tubing fittings

Transportation Information:

Proper Shipping Name:	Not regulated as a hazardous material.
UN Number:	Not regulated as a hazardous material.
Class:	Not regulated as a hazardous material.

Pictograms:



PRODUCT UNDER GHS

Signal Word:

Not a GHS-controlled substance.

Personal Protective Equipment Required:

