



# KOTE

# #1767

## Chain and Cable Dressing



### Features

- VOC Compliant
- Penetrates, lubricates and protects
- Provides friction reduction and wear resistance
- Fortified with Molybdenum Disulfide
- Salt spray resistant
- Residual film protects in harsh chemical environments

### Description

Kote Chain and Cable Dressing is a foaming lubricant fortified with Molybdenum Disulfide that withstands extreme temperature and high pressure. When applied to wire ropes and cables, the Moly and other additives plate the strands to provide anti-wear and rust protection extending their life. The thick formula base with tackifier helps prevent throw-off and weather wash-out. It has been tested to withstand salt spray for 72 hours making it a great option for coastal facilities. This product has excellent penetrating action to chains, cables, pins, links and bushings of chains, leaving a lubricating film, which reduces friction, wear and corrosion.

### Applications

- Chains
- Booms
- Conveyors
- Wire Rope
- Bearings
- Mining
- Construction
- Road Equipment
- Hoist
- Cables
- Cranes
- Rollers
- Railroads
- Steel Mills
- Material Handlers
- Saws
- Tow Lines
- Winches
- Shipyards
- Factories
- Containerized Shippers

### Directions

Shake well before using. Make the can rattle 30 seconds before using. For proper spraying, the can should be near room temperature (about 72°F/22°C). Parts to be sprayed should be reasonably clean and dry. Spray, holding can 12 to 14 inches from point to be lubricated. Make sure arrow on spray tip points away. For point lubrication, use plastic tube extension, insert into nozzle – for reaching places where a spray pattern is not desired. Spray may be applied by holding can upside down, sideways, right side up...in almost any position. If spray tip should close remove and clean in solvent.

### Product Characteristics

Container Size	15 oz Can
Appearance	Thick Black Liquid
Odor	Petroleum Odor
pH	N/A
Spray Pattern	Foaming
Flash Point (Concentrate)	> 220°F (T.O.C)
Specific Gravity	0.865
Flammability	Flammable Spray
VOC%	42.21%
NFPA Code 30B Rating	Level 1 Aerosol
DOT Proper Shipping Name	CONSUMER COMMODITY, ORM-D
Storage	Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F
Transportation Information	
Class #	55
UN number	UN1950

# Product Information Sheet

Health	2
Flammability	4
Physical Hazard	0