

# PRO STRIP #1606

## Aerosol Paint & Varnish Remover



### Features:

- Clinging gel with fast blistering action
- Quickly blisters lacquers, enamels, shellacs and acrylics with attaching substrates such as wood, metal, masonry, stone or ceramics
- Blistered paint can be scraped off or flushed away with water
- Leaves no film or residue
- Facilitates gasket removal

### Description:

PRO STRIP is a powerful clinging gel that quickly blisters lacquers, enamels, shellacs and acrylics without attacking substrates such as wood, metal, masonry, stone or ceramics. The blistered paint can then be easily scraped off or flushed away with water. It also allows for easier gasket removal. Just spray on and let stand for 3-5 minutes for the product to soak into the gasket, allowing the active ingredients to work and release it from its seated surface.



### Applications:

- Gaskets
- Shellacs
- Lacquers
- Acrylics
- Enamels
- Latex

### Product Characteristics:

Appearance:	Liquid, aerosol
Odor:	Not available
Flash Point:	15.0°F (-9.4°C) estimated
Flammability Limit-lower (%):	10.5% estimated
Flammability Limit-upper (%):	17.6% estimated
Vapor Pressure:	2386.71 psig @70°F estimated
Auto-Ignition Temperature:	1007.48°F (541.93°C) estimated
Vapor Density:	Not available
VOC (weight%):	Not available
Viscosity:	98.4 estimated
Initial Boiling Point/Range:	-16.28°F (-26.82°C) estimated
Density:	0.16 g/cm <sup>3</sup> estimated
Storage:	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Pressured container.
Transport Information:	
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1L capacity)
UN Number:	UN1950
Class:	2.1
Packing Group:	Not applicable

### DOT Pictogram:



### Directions:

Clean off dirt, grease or heavy oil. Make certain surface is dry. To avoid possible skin contact, do not stand downwind of spray or mist during application. Hold can 8 to 10 inches from surface. Apply a heavy, even coat to entire surface. Allow product to remain on surface for several minutes, even after blistering action has occurred. Remove residue with a scraper, putty knife, cloth or a strong water spray. If necessary, repeat application after surface is dry. Clean valve by turning can upside down and applying short burst.

### Pictograms:



**Signal Word:**  
DANGER

### Personal Protective Equipment Required:

