PRO CHEM, INC.
1475 BLUEGRASS LAKES PKWY.
ALPHARETTA, GA 30004
EMERGENCY/INFO # (800) 241-8180
ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET

ULTRA AIR 9000 / 1371

MARCH 2009

HEALTH	2
FIRE	3
REACTIVITY	1
P.P.E.	

Complies With USDL Safety and Health Regulations, (29 CFR 1910.200)

SECTION 1 – Chemical and Company Identification

CHEMICAL FAMILY: Air Freshener

SECTION 2 – Composition on Ingredients

Hazardous ingredients as defined by OSHA, 29 CFR 1910.1200:

COMPONENTS	CAS #	OSHA-PEL	ACGIH-TLV	LC_{50}	LD_{50}	% BY WT
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	100 mg/L	7060 mg/kg, oral rat	10-25
Isobutane	106-97-8	N/E	1000 ppm	N/E	N/E	20-30
Propane	74-98-6	1000 ppm, TWA	2500 ppm	280000 ppm 4h, rat	N/E	20-30
Hexylene Glycol	107-41-5	25 ppm	25 ppm, ceiling	NA	3700 mg/Kg oral, rat	10-25

SECTION 3 – Hazards Information

FLAMMABLE LIQUID! Contents under pressure: do not expose to fire or extreme heat.
Potential Health Effects:
ROUTES OF ENTRY: **EYE:** Y **SKIN:** Y **INHALATION:** Y **INGESTION:** Y
HEALTH HAZARDS: May cause eye and skin irritation, as well as respiratory irritation. May cause stomach distress.
SIGNS/SYSTEMS OF OVEREXPOSURE: High vapor concentrations or excessive intentional inhalation may cause upper respiratory tract irritation, sleepiness and/or dizziness, and eye irritation. Prolonged skin contact may cause mild redness and swelling. Contact with eyes may cause irritation, experienced as discomfort or pain, excessive blinking and tear production, with marked excess redness and swelling. Corneal injury may occur. This product can be absorbed through the skin.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Skin contact may aggravate an existing skin condition.

SECTION 4 – First Aid Measures

EYES: Immediately rinse eyes with plenty of water, occasionally lifting upper and lower lids, until no evidence of product remains. Obtain medical attention if irritation persists.
SKIN: Rinse affected area with plenty of water until no evidence of product remains; obtain medical attention if irritation persists.
INHALATION: Not a normal route of harmful exposure. If symptoms develop, move victim to fresh air. If symptoms persist obtain medical attention.
INGESTION: Treat symptomatically and supportively. Maintain airway and respiration. If vomiting occurs, keep head below hips to prevent aspiration. Dilute by rinsing the mouth and giving water or milk to drink is generally recommended. If unconscious, the victim should not be given anything to drink. Contact physician or local poison control center.

SECTION 5 – Fire Fighting Measures

EXTINGUISHING MEDIA: Alcohol type or all-purpose foam for large fires, C02 or dry chemicals
FIRE FIGHTING PROTECTION: Self-contained air supply suggested.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Contents under pressure. Container may explode with heat. Cool containers with spray and remove source of ignition if safe.

SECTION 6 – Accidental Release Measures

Before attempting clean up refer to hazard data given above. Remove sources of ignition. Although chance of a significant spill or leak is unlikely in aerosol containers, in the event of such an occurrence, absorb spilled material with non-flammable absorbent such as sand or vermiculite.

SECTION 7 – Handling and Storage

Keep out of reach of children. Store in a cool dry place, away from heat or open flames. Exposure to temperatures above 120°F may cause container to burst.

SECTION 8 – Exposure Controls/Personal Protection

GLOVES: Not normally required.
EYE PROTECTION: Not normally required.
RESPIRATORY PROTECTION: Not normally required.
VENTLATION: Local: Not required.
OTHER PROTECTIVE EQUIPMENT: None required.
PROTECTIVE WORK/HYGIENE PRACTICES: Follow labeling instructions.

SECTION 9 – Physical and Chemical Properties

APPEARANCE/ODOR: Clear, colorless liquid; fragrant
SPECIFIC GRAVITY: 0.70 @ 20°C **PRESSURE:** 20°C: 70 psig

SECTION 10 – Stability and Reactivity

CONDITIONS TO AVOID: Aerosol containers are unstable at temperatures above 120°F /49°C, avoid open flames and very hot surfaces.
INCOMPATIBLE MATERIALS: Oxidizing agents, caustics, and acids
HAZARDOUS DECOMPOSITION PRODUCTS: May include and are not limited to oxides of carbon when heated to decomposition.
HAZARDOUS POLYMERIZATION CONDITIONS: None known

SECTION 11 – Toxicological Information

Carcinogenic: Non hazardous by WHIMS/ OSHA criteria
Teratogenicity, Mutagenicity, Reproductive Effects: No data available

SECTION 12 – Ecological Information

Discharge, treatment, or disposal may be subject to national state or local laws.

SECTION 13 – Disposal Consideration

Do not reuse empty containers. This container may be recycled in a few and growing number of communities where steel aerosol can recycling is available. Before offering for recycling, empty the can by using the product according to label. DO NOT PUNCTURE CAN! If recycling is not available discard the containers into the trash.

THIS INFORMATION MUST BE ON ALL MSDS'S COPIED AND DISTRIBUTED FOR THIS MATERIAL.

NO WARRANTY IS EXPRESSED / IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE / USER ASSUMES ALL RISKS ASSOCIATED WITH USE.

PRO CHEM, INC.
1475 BLUEGRASS LAKES PKWY.
ALPHARETTA, GA 30004
EMERGENCY/INFO # (800) 241-8180
ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET

ULTRA AIR 9000 / 1371

MARCH 2009

HEALTH	2
FIRE	3
REACTIVITY	1
P.P.E.	

Complies With USDL Safety and Health Regulations, (29 CFR 1910.200)

SECTION 14 – Transport Information

	SHIPPING NAME	STATUS	CLASS	ID #	PKNG GRP
DOT	Consumer Commodity	Regulated	ORM-D		N/A
IATA (AIR)	Aerosols, Flammable	Regulated	2.1	UN1950	N/A
IMDG (VESSEL)	Aerosols	Regulated	2	UN1950	N/A

National Motor Freight Classification and LTL Class: 57100 Sub 3 Class 60

SECTION 15 – Regulatory Information

SARA Chemicals: This product contains the following SARA 313/312/304/311/312 chemicals: NONE
OSHA Classification: Hexylene Glycol
TSCA Inventory Listing: (Toxic Substances Control Act) - All ingredients are listed on the chemical substance inventory exempt California Proposition 65- NONE
FEDERAL AND STATE REGULATIONS: Hexylene Glycol, Dipropylene Glycol
Pennsylvania
New Jersey
Illinois
Massachusetts
Rhode Island
Minnesota
Workplace Hazardous Materials Information System: WHMIS Classification: Class D-Division 2B, Class B-Division 5
Flammable liquid, Class A: Compressed Gas

SECTION 16 – Other Information

NA= Not Applicable N.E= Not Established
Disclaimer: This information is provided in good faith, but no warranty, expressed or implied is made. The manufacturer believes that it is accurate to the best of its knowledge, and relates only to specific material designated herein.

THIS INFORMATION MUST BE ON ALL MSDS'S COPIED AND DISTRIBUTED FOR THIS MATERIAL.

NO WARRANTY IS EXPRESSED / IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE / USER ASSUMES ALL RISKS ASSOCIATED WITH USE.