

Anti-Seize Lubricant

**Features**

- Withstands extreme pressure
- Suitable for temperatures from -110°F to +1050°F and pressures to 100,000 psi
- Clings to hot metals
- Weather resistant – for use both indoors and outdoors
- Contains Molybdenum Disulfide



**Description**

MOLY-LUB BULK is packaged as an alternative to our convenient aerosol in a 40-pound pail. MOLY-LUB BULK does not contain any graphite, silicone, oil or grease and leaves a long lasting dry film lubricant that will not attract dust and provides a tenaciously adherent coating. MOLY-LUB BULK is resistant to water, oil, alkalis and most acids and protects against moisture, rust, corrosion, and galling of metal parts. It resists salt water penetration and helps machinery run smoother and longer. Prevents friction, fretting, wear, sticking, galling, seizing, binding, and chattering.

**Applications**

- Internal combustion engine components
- Chain lubrication
- High speed gears & chains
- Paper and corrugated converting
- Wire drawing
- Brazing
- Machine tools
- Automotive
- Chemical plants
- Wood working
- Stop-off coating
- Conveyors & bearings
- Pump assemblies
- Foundries
- Sewing trades

**Directions**

Parts to be coated should be clean and dust free. Agitate before and during use. Spraying produces the most uniform and precisely controlled film thickness. Use a commercial spray gun of one quart capacity or less, or an air pressure sprayer with 40-50 lbs. pressure. Make sure working area is adequately ventilated. A single wet pass of spray usually deposits a film of about 0.0002 to 0.0003 inches thick; this thickness gives best adhesion and wear life. Dipping is an excellent application method if a high degree of film uniformity is not essential. Always keep container closed when not in use.

**Product Characteristics**

Appearance	Grey/black liquid
Fragrance	Sweet solvent
Flash Point	None to boil
Specific Gravity (H <sub>2</sub> O=1 @75°F)	1.2
Total VOC %	14.8%
Solubility in water	Negligible
Boiling Point	~108°F
Vapor Density (Air=1)	>1
Storage	Store in a cool, dry area away from heat or open flame and below 120°F.
<b>Transportation information</b>	
Shipping Description	HAZARDOUS SHIPPING: Poisonous Liquid, Organic, N.O.S. (Dichloromethane), 6.1, UN 2810, PGIII

Health	2
Flammability	1
Reactivity	1
Personal Protection	G