



Pro Tools MP Silicone

#1492

Industrial Grade Dry Silicone Spray

Product Information Sheet

Features

- Lubricates and protects
- High viscosity
- Hexane free
- Fast drying
- Food processing acceptability: H1
- No chlorinated or fluorinated solvents or ozone depleters
- Does not cause gumming
- Colorless, odorless, and non-staining
- Resistant to temperatures in excess of 500°F



Description

PRO TOOLS MP SILICONE is an aerosol silicone spray that is one of the most versatile, high performance, multipurpose products available. This formula is excellent for use as both a coating and a lubricant. Use this product on moving parts, as a weather and water barrier, as an electrical insulator, and to prevent sticking, squeaking, and freezing of doors, windows, locks, and assemblies. This product is intended for use in inedible processing areas of official establishments operating under the Federal meat, poultry, shell egg grading and egg products inspection programs provided that it is not used to mask odors resulting from unsanitary conditions, and that any characteristic odor or fragrance does not penetrate into an edible product area.

Applications

- Maintenance shops
- Detailing cars
- Battery terminals and cables
- Cutting tables and conveyors
- Door locks
- Hinges

Directions

Clean surface to be treated. Remove cap and spray a thin film on surface from 8-10 inches away. Wipe away excess with a clean cloth. For hard-to-reach areas, insert extension tube provided and spray as needed.

Note: May harm painted or waxed finishes. Always test in an inconspicuous area before use.

Product Characteristics

Appearance	Clear, colorless spray
Odor	Petroleum
Flash Point	Not available
Specific Gravity (conc. only)	0.71
Vapor Pressure	Not available
Solubility in water	Insoluble
Evaporation rate (water=1)	>1
Boiling Point	Not available
pH	N/A
Vapor Density	Not available
VOC Content, wt %	96% (US federal/CARB/OTC/LADCO)
% Volatile, wt %	96
NFPA CODE 30B RATING	Level 3 aerosol
Storage	Do not store at temperatures above 130°F. Keep out of reach of children. Avoid food contamination.
Transportation information	
Class #	60
NFMC	50244

Health	2
Flammability	3
Reactivity	0
Personal Protection	B