



Slip-Ez

#1263

Aerosol Food Grade Silicone Lubricant



Features

- Non staining – fast drying
- Heat stable from -40°F to over 392°F
- Non-chlorinated, safe on plastics
- Highest food acceptability rating (H1)
- Colorless, odorless & stainless
- Reduces friction and wear
- High viscosity

Description

SLIP-EZ is a silicone aerosol that lubricates, protects, reduces friction and makes everything slide and glide easier. It forms a slick, water-repellent, non-adherent surface coating. SLIP-EZ deposits a stick-free surface wherever needed. It saves time, money, clean-up, causes less jamming and aids in the prevention of corrosion. It will not discolor or damage fabrics, metals, rubber or plastic surfaces. Can be used to lubricate moving parts in food processing and packaging plants. Can be used on non-food contact surfaces of ovens and grills to prolong time between cleaning. Dry silicone formula prevents jamming and production slowdown on bottling and packaging lines.

Applications

- Conveyors
- Slicing equipment
- Guide rails
- Cutting dies
- Mold release
- Scrambler tables
- Meat and poultry plants
- Packaging plants
- Bottling plants
- Ovens
- Heating and sealing equipment
- Vending machines
- Locks
- Sewing machines
- Dairies
- Grocery stores
- Container molding operations

Directions

Thoroughly clean surfaces to be treated. Use steel wool on metals, and wipe with a good, compliant cleaning solvent if necessary.

Clean rubber and plastic surfaces with detergent solution, rinse, and dry thoroughly. Spray a thin, light silicone film; avoid overspraying. Remove excess with a clean cloth. Renew when necessary.

ATTENTION: Do not allow spray, mist or coating to cover floors; they may become slippery, especially when wet.

Product Characteristics

Appearance	Compressed liquefied gas, colorless
Odor	Solvent
Physical State	Gas
Form	Aerosol
Flash Point	-156°F Propellant
Specific Gravity	0.582
pH	N/A
Solubility	Negligible
Freezing Point	Not available
Boiling Point	33.8°F estimated
Density	0.5819 g/cm ³ estimated
Pressure	60-70 psig @ 70°F
NFPA CODE 30B RATING	Level 3 aerosol
Storage	Store in a cool, dry area away from heat, sparks, or open flame. Do not store, incinerate, or heat this material above 120°F. Avoid exposure to long periods of sunlight. Keep out of reach of children.
Transportation information	
Class #	65
NFMC	90960

Product Information Sheet

Health	1
Flammability	4
Reactivity	0
Personal Protection	B