

Oil-Based Silicone Release Agent

Features

- Effective release agent that reduces friction
- Colorless, stainless, water-repellant
- Deposits a stick-free surface
- Odorless
- Food Processing Acceptability: H2
- Helps speed production rates
- Preserves electrostatic build-up
- Lubricates locks, windows, doors
- 15% active silicone



Description

SLIP-EZ BULK is an oil-based silicone lubricant that is an excellent release agent for use with all mold materials such as steel, aluminum, epoxy resins, rubber, concrete and elastomers. It has no corrosive or other harmful effect on the mold. A thin coating of SLIP-EZ BULK does not alter dimensions or detail in the mold. It also eliminates sticking of foreign matter to metal surfaces such as snowplows, concrete trucks, and various machinery.

Applications

- Furniture industry
- Wood shops
- Vending machines
- Packaging and processing equipment
- Textile industry
- Carpenters
- Plastic industry
- Rubber industry
- Automotive
- Lumber yards

Directions

Clean surface prior to application. Use steel wool or wire brush and good detergent. Wipe dry with clean cloth or allow to air dry. Spray thin coat of undiluted product using trigger or pressure sprayer and holding 10-15 inches away from surface.

Product Characteristics

Appearance	Clear, colorless liquid
Odor	Solvent
Flash Point (method used)	110°F (T.O.C.)
Specific Gravity _(H2O=1)	0.78
Evaporation Rate _(butyl acetate=1)	N/E
Vapor Pressure _(mmHg)	N/E
Solubility in water	Insoluble
pH Concentrate	N/A
Boiling Point	300-400°F
Vapor Density _(Air=1)	N/E
Storage	Store in a cool, dry place. Keep container closed when not in use.
Transportation information	
Class #	60
NFMC	50244

Product Information Sheet

Health	2
Flammability	2
Reactivity	0
Personal Protection	G