



White Lube

#1723

Aerosol White Lithium Grease

Product Information Sheet

Features

- Heat stable to 350°F
- Penetrates into gears as a liquid then sets up to a thick grease
- Contains no chlorinated solvents
- No Hexane or CFC's
- White lubricant is non-staining
- Withstands extreme temperatures (up to 350°F)



Description

WHITE LUBE sprays as a deep penetrating oil that flows and creeps into areas which are difficult to lubricate. Then, as the solvent carrier evaporates, the liquid forms into thick water-resistant grease that is also resistant to high temperatures. After setting up, the grease will not wash away with water while providing non-staining lubrication which guards surfaces against rust and corrosion. It is an excellent product for industrial and automotive uses.

Applications

- Hoists
- Cams
- Conveyors
- Linkages
- Dryers
- Pumps
- Threads
- Slide Bearings
- Chain Drivers
- Wire Rope
- Gears
- Winches
- Rollers
- O-Rings
- Fittings
- Ovens
- Valves
- Manifold Heat Valves

Directions

Shake well before using. Spray on a clean, dry surface from a distance of 6 to 8 inches. Insert extension tube into actuator orifice for pinpoint application. Tube package included in carton. Repeat application periodically.

Product Characteristics

Appearance	White compressed liquefied gas
Odor	Solvent
Flash Point (method used)	-156°F, Propellant
Specific Gravity (H ₂ O=1)@70°F	0.7221 estimated
pH	N/A
Solubility in water	Partially
Boiling Point	368°F/ 187.2°C
Density	.722 g/cm ³ est.
Vapor Pressure (psig@70°F)	70-90 psig
Storage	Store in a cool area away from heat and sources of ignition. Avoid long exposure to sunlight and keep in a well ventilated place.
Transportation information	
Proper Shipping Name	Consumer Commodity
Hazard Class	ORM-D

Health	1
Flammability	3
Reactivity	0
Personal Protection	B