

# INTRINSICALLY SAFE PERMISSIBLE #445301

## Dual Light With Dual Magnet



### Features:

- ETLus and MSHA listed Intrinsically Safe Permissible
- Flashlight – Floodlight – Dual-Light
- LED technology
- Momentary or constant-on flashlight
- Sharp focused flashlight beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-light (flashlight and floodlight at same time) for maximum versatility IP-67 Waterproof
- Impact and chemical resistant
- Powerful integrated magnets built into the base and pocket clip for multiple hands-free options
- Engineered polymer housing
- Non-slip grip
- Dual body switches
- Built-in pocket/belt clip
- Includes removable lanyard
- 3 AA batteries (not included)

### Description:

INTRINSICALLY SAFE PERMISSIBLE FLASHLIGHT is ETLus and MSHA listed Intrinsically Safe Permissible. It uses an LED rated at 160 lumens that work in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 170 meters. A 130 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination.

Additionally, both the flashlight and the floodlight can be turned on at the same time for maximum versatility at 260 lumens. The dual body switches provide momentary or constant-on functionality for the flashlight and on/off functionality for the floodlight. Additionally, the integrated magnets located in the base of the handle and the pocket clip, provide for almost limitless hands-free usage.

### Specifications:

- High Lumens: 160
- Floodlight Lumens: 130
- High DL Lumens: 260
- High Beam Distance (m): 170
- High Candela: 7,250
- Drop Rating: 2 m
- Water Rating: IP-67 Dustproof/Waterproof
- High Runtime (h): 19
- High Flood Runtime (h): 19
- High Dual-Light Runtime (h): 4.5
- Floodlight Color: White
- Switch Function: Dual Body Switch - Momentary or Constant-on Flashlight, Constant-on Floodlight
- Light Source: LED
- Case Material: Engineered Polymer
- Dimensions:
  - Length: 7.0 in (178 mm)
  - Weight: 6.9 oz (196 g)
  - Handle Diameter: 1.1 x 1.5 in (28 x 38 mm)
  - Head Diameter: 1.8 in (46 mm)

### Applications:

- Industrial
- Automotive
- Public Safety
- Military
- Law Enforcement
- Utilities

