

# 4-N-1 BULK #2707

## Penetrating Oil & Demoisturant



### Features:

- Lubricates and creates waterproof film
- High dielectric strength of 39,000 volts, non-conductive
- Non-flammable
- Contains no chlorinated solvents, perchloroethylene or methylene chloride
- Dries wet electric contacts
- Displaces water and moisture from electrical parts and prevents malfunction in equipment exposed to high humidity
- Frees rusted nuts and bolts
- Food Processing Acceptability: H2
- Available in: 1 Gallon Jugs (#270707) and 22 oz. Bottles (#270701)



### Description:

4-N-1 BULK is a high dielectric, non-flammable liquid that protects against industrial and atmospheric pollution, dust, abrasive matter and chemical fumes. It forms a non-drying, invisible film that prevents moisture-induced deterioration and malfunctions on electrical components and circuitry without any loss in conductivity. It creeps along surfaces and into cracks to lubricate, prevent rust, and loosen frozen parts. It leaves a water-displacing shield and a lubricating film to make anything run smoother. 4-N-1 BULK has unlimited uses in automotive, marine, railroad and construction industries.

### Applications:

- Motors
- Hinges
- Molds
- Generators
- Screws
- Linkages
- Lug Nuts
- Bearings
- Fasteners
- Engine Parts
- Frozen Nuts
- Relays
- Bolts
- Starters
- Threaded Parts
- Switches
- Clamps
- Tools
- Gears
- Plugs

### Product Characteristics:

Appearance:	Liquid
Odor:	No data available
Boiling Point:	Estimated 189°C
Relative Density:	No data available
Freezing Point:	No data available
Density:	No data available
Flash Point:	Estimated 75°C
Oxidizing Properties:	No data available
pH:	No data available
Storage:	Store in a well-ventilated place. Keep cool. Store locked up
<b>Transport Information:</b>	
Proper Shipping Name:	Not regulated
UN Number:	Not regulated
Class:	Not regulated
Packing Group:	Not regulated

### Directions:

For best performance and fullest protection, first clean object with degreaser solvent to remove grease, oil and debris. This will prevent material from becoming contaminated, especially when used in a dip tank. Apply as a spray, brush on or use in a dip tank. Allow wetted-out rusted parts to be immersed in solution for several minutes. Always keep container closed to prevent evaporation or contamination.

### Pictograms:



### Signal Word:

DANGER.

### Personal Protective Equipment Required:



**DOT Placard:**  
Not regulated.

**VOC Compliant:**  
Yes.