



SAFETY DATA SHEET

1. Product and Company Identification

| | | | |
|-----------------------------|---|-----------------------------|----------------|
| PRODUCT NUMBER: | 1358 | COMPANY PHONE: | 1-800-241-8180 |
| PRODUCT NAME: | AirMatic Mulberry Fusion | EMERGENCY TELEPHONE: | 1-800-241-8180 |
| PRODUCT DESCRIPTION: | Metered Aerosol Odor Neutralizer | INFOTRAC: | 1-800-535-5053 |
| COMPANY INFORMATION: | PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004 | | |

2. Hazards Identification

GHS CLASSIFICATION:
Flammable aerosols: Category 1
Serious eye damage/eye irritation: Category 2
Specific target organ toxicity, single exposure: Category 3 narcotic effects
Environmental hazards: Not classified.
OSHA defined hazards: Not classified.

SIGNAL WORD:
DANGER

SYMBOL:



HAZARD STATEMENTS:

Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS:

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Collect spillage.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

| CHEMICAL NAME | CAS | CONCENTRATION % by WEIGHT |
|--|----------|---------------------------|
| Acetone | 67-64-1 | 40-60 |
| Diethylene Glycol Monoethyl Ether | 111-90-0 | 10-20 |
| Propane | 74-98-6 | 10-20 |
| Isobutane | 75-28-5 | 2.5-10 |
| Other components below reportable levels | | 2.5-10 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

EYES: Rinse with water. Get medical attention if irritation develops and persists.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

INHALATION:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

INGESTION:

Rinse mouth. Get medical attention if symptoms occur.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

GENERAL:

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Powder. Alcohol resistant foam. Carbon dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

SPECIFIC FIRE-FIGHTING METHODS:

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion, do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and, in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during cleanup. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

ENVIRONMENTAL PRECAUTIONS:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, watercourses or onto the ground.

METHODS AND MATERIALS FOR CONTAINMENT & CLEANUP:

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see Section 13 of the SDS.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING:

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not reuse empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| COMPONENTS | TYPE | VALUE |
|-----------------------|------|------------------------------------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m ³ 1000 ppm |
| Propane (CAS 74-98-6) | PEL | 1800 mg/m ³ 1000 ppm |

US. ACGIH Threshold Limit Values

| COMPONENTS | TYPE | VALUE |
|-------------------------|------|----------|
| Acetone (CAS 67-64-1) | STEL | 750 ppm |
| | TWA | 500 ppm |
| Isobutane (CAS 75-28-5) | STEL | 1000 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| COMPONENTS | TYPE | VALUE |
|-------------------------|------|------------------------------------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m ³ 250 ppm |
| Isobutane (CAS 75-28-5) | TWA | 1900 mg/m ³ 800 ppm |
| Propane (CAS 74-98-6) | TWA | 1800 mg/m ³ 1000 ppm |

US. Workplace Environmental Exposure Level (WEEL) Guides

| COMPONENTS | TYPE | VALUE |
|--|------|---------------------------------|
| Diethylene Glycol Monoethyl Ether (CAS 111-90-0) | TWA | 140 mg/m ³ 25 ppm |

*For sampling details, please see the source document.

BIOLOGICAL LIMIT VALUES:

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------|---------|-------------|----------|---------------|
| Acetone (CAS 67-64-1) | 50 mg/l | Acetone | Urine | * |

PERSONAL PROTECTIVE EQUIPMENT:



Eye/Face Protection: If contact is likely, safety glasses with side shields are recommended.

Skin Protection: Hand protection: Wear appropriate chemical resistant gloves. **Other:** Wear suitable protective clothing.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: When using, do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

APPROPRIATE ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

9. Physical & Chemical Properties

| | | | |
|-----------------------------------|--|---|-----------------------------|
| Physical State: | Gas. | Specific Gravity: | 0.731 estimated. |
| Color: | Not available. | Vapor Density: | Not available. |
| Odor: | Not available. | Vapor Pressure: | 270.48 psig @70°F estimated |
| Odor Threshold: | Not available. | Relative Density: | Not available. |
| pH: | Not available. | Solubility (water): | Not available. |
| Melting/Freezing Point: | Not available. | Auto-Ignition Temperature: | Not available. |
| Boiling Point/Range: | 132.89 °F (56.05 °C) estimated | Decomposition Temperature: | Not available. |
| Viscosity: | Not available. | Explosive limit - lower (%): | Not available. |
| Flash Point: | -156.0 °F (-104.4 °C) PROPELLANT estimated | Explosive limit - upper (%): | Not available. |
| Evaporation Rate: | Not available. | Flammability limit – lower (%): | 1.6 % estimated. |
| Form: | Aerosol. | Flammability limit – upper: | 14.5 % estimated |
| Flammability (solid, gas): | Not applicable. | Partition Coeff (n-octanol/water): | Not available. |

10. Stability & Reactivity Information

REACTIVITY:

The product is stable and non-reactive under normal conditions of use, storage and transport.

CHEMICAL STABILITY:

Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

CONDITIONS TO AVOID:

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

Eyes: Causes serious eye irritation.

Skin: No adverse effects due to skin contact are expected.

Inhalation: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Ingestion: Expected to be a low ingestion hazard.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

ACUTE TOXICITY:

Narcotic effects.

| Product | Species | Test Results |
|-------------------|------------|--|
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Guinea pig | 38240.6719 mg/kg, Days estimated 14125.5508 mg/kg, 24 Hours estimated 17.8804 ml/kg, 24 Hours estimated |
| | Rabbit | 54936.9336 mg/kg, 24 Hours estimated 27101.6855 mg/kg, 2 Hours estimated 17.8804 ml/kg, 24 Hours estimated |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 4417.8569 mg/l, 120 Minutes estimated 185.7143 %, 120 Minutes estimated |
| | Rat | 3410.7402 mg/l/4h estimated 89.5798 mg/l, 4 Hours estimated |
| <i>Oral</i> | | |
| LD50 | Guinea pig | 32212.9023 mg/kg estimated |

| Components | Species | Test Results |
|---|----------------|---|
| | Mouse | 39089.7422 mg/kg estimated |
| | Rabbit | 36296.2305 mg/kg estimated |
| | Rat | 8460.8516 mg/kg estimated 3.7262 ml/kg estimated |
| Acetone (CAS 67-64-1) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Guinea pig | > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours |
| | Rabbit | > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours |
| <i>Inhalation</i> | | |
| LC50 | Rat | 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l |
| <i>Oral</i> | | |
| LD50 | Rat | 5800 mg/kg 2.2 ml/kg |
| Diethylene Glycol Monoethyl Ether (CAS 111-90-0) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Guinea pig | 5900 mg/kg, Days |
| | Rabbit | 8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours 7714 mg/kg |
| <i>Oral</i> | | |
| LD50 | Guinea pig | 4970 mg/kg |
| | Mouse | 6031 mg/kg |
| | Rabbit | 5600 mg/kg |
| | Rat | 5600 mg/kg 5.4 ml/kg |
| Isobutane (CAS 75-28-5) | | |
| Acute | | |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes 52%, 120 Minutes |
| | Rat | 1355 mg/l |
| Propane (CAS 74-98-6) | | |
| Acute | | |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes 52%, 120 Minutes |
| | Rat | 1355 mg/l 658 mg/l/4h |

* Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Prolonged skin contact may cause temporary irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Causes serious eye irritation.

RESPIRATORY SENSITIZATION:

Not available.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

CARCINOGENICITY:

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

REPRODUCTIVE TOXICITY:

This product is not expected to cause reproductive or developmental effects.

SPECIFIC TARGET ORGAN TOXICITY (single exposure):

May cause drowsiness and dizziness.

SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):

Not classified.

ASPIRATION HAZARD:

Not likely, due to the form of the product.

CHRONIC EFFECTS:

Prolonged inhalation may be harmful.

12. Ecological Information

ECOTOXICITY:

Toxic to aquatic life with long lasting effects.

| PRODUCT | SPECIES | | TEST RESULTS |
|--|---------|--|------------------------------------|
| Mulberry Fusion | | | |
| Aquatic | | | |
| Crustacea | EC50 | Daphnia | 9811.0371 mg/l, 48 hours estimated |
| Fish | LC50 | Fish | 3723.9939 mg/l, 96 hours estimated |
| COMPONENTS | SPECIES | | TEST RESULTS |
| Acetone (CAS 67-64-1) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 21.6 - 23.9 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |
| Diethylene Glycol Monoethyl Ether (CAS 111-90-0) | | | |
| Aquatic | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | > 10000 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:

No data available.

Partition coefficient n-octanol / water (log Kow):

| | |
|-----------------------------------|-------|
| Acetone | -0.24 |
| Diethylene Glycol Monoethyl Ether | -0.54 |
| Isobutane | 2.76 |
| Propane | 2.36 |

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration

DISPOSAL INSTRUCTIONS:

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste-disposal company.

US RCRA Hazardous Waste U List: Reference:

Acetone (CAS 67-64-1) U002

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

CONTAMINATED PACKAGING:

Empty containers should be taken to an approved waste-handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not reuse empty containers.

14. Transportation Information

DOT: UN Number: UN1950
UN Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity).

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1



Packing Group: Not applicable.

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Special Provisions: N82

Packaging Exceptions: 306

Packaging Nonbulk: None.

Packaging Bulk: None.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA: UN Number: UN1950
UN Proper Shipping Name: Aerosols, flammable.

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1



Packing Group: Not applicable.

Environmental Hazards: Yes.

ERG Code: 10L

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Other Information:

Passenger and Cargo Aircraft: Allowed.

Cargo Aircraft Only: Allowed.

Packaging Exceptions: LTD QTY

IMDG: UN NUMBER: UN1950

UN Proper Shipping Name: AEROSOLS

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

Packing Group: Not applicable.

Environmental Hazards:

Marine pollutant: Yes.

EmS: F-D, S-U

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:

Not applicable.



15. Regulatory Information

US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4):

Acetone (CAS 67-64-1) Listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

Hazard categories Immediate Hazard – Yes.

Delayed Hazard – No.

Fire Hazard – Yes.

Pressure Hazard – No.

Reactivity Hazard – No.

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting): Not regulated.

OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List : Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US STATE REGULATIONS

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. California Proposition 65: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

INTERNATIONAL INVENTORIES:

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|-------------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information**DISCLAIMER:**

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.