

# BELT LUBE #2294

## Expandable Hub Belt Lubricant



### Features:

- Non-flammable, non-corrosive, odorless
- Ready-to-use formula
- Economical
- Environmentally friendly
- Less greasy and longer lasting than most comparable products
- Penetrates deeply into belts to keep surfaces soft and pliable

### Description:

BELT LUBE guards against the damage caused by ultraviolet rays, environmental conditions and everyday use. This product helps belts resist cracking, dulling, hardening and fading and increases pliability. Its protective shield helps maintain a long lasting attractive appearance on a variety of surfaces that is non-greasy and long lasting. BELT LUBE also makes surfaces anti-static to repel dust and dirt.



### Applications:

- Expandable Hubs
- Belts

### For Use By:

- Retread Plants

### Product Characteristics:

Appearance:	Milky emulsion
Odor:	Odorless
VOC:	0
Relative Density:	1.0
Vapor Pressure:	Not available
Solubility (water):	Complete
pH:	4 – 5
Flash Point:	None
Explosive Properties:	Not available
Decomposition Temp:	Not available
Storage:	Do not use or store near heat, sparks or open flame. Keep out of reach of children.
<b>Transport Information:</b>	
UN Number:	Not regulated.
Proper Shipping Name:	Not regulated.
Class:	Not regulated.
Packing Group:	Not regulated.

### Directions:

For Expandable Hubs:

1. Apply with a swab and bucket.
2. Cover a strip 3" and 8 mm wide at each belt edge along the rim flanges.

At least once a week, clean the belt on the expandable rims with a wire brush, a putty knife and a clean shop cloth. A brass, non-sparking putty knife is recommended to avoid scratching the aluminum parts.

For Belt Lubrication:

1. Apply a little at a time to inner surface of belt while machinery is in motion.
2. Spray using a back and forth motion until the surface is completely wet. On most belts, the spray may be applied to the sheaves, pulleys or directly onto the belt itself.
3. Repeat application occasionally to maintain full power and optimize belt life.

NOTE: In many instances, protective guards must be removed in order to apply belt dressing properly. In such cases, please use extreme care to prevent accidents. Be sure to replace guards after treatment.

CAUTION: Use only as directed. Avoid overspray onto floors, equipment controls or any surface which may become hazardous if slippery.

### Pictograms:



### Signal Word:

WARNING

### Personal Protective Equipment Required:



### DOT Placard:

Not regulated.

### VOC Compliant:

Yes.