BRAKE AWAY II #1830

Aerosol Non-Chlorinated Brake Parts Cleaner



Features:

- · High pressure delivery system allows for thorough cleaning of all brake surface parts
- Dissolves grease, oils, tar, asphalt, resins, brake fluid and many other soils
- Does not contain chlorinated solvents that can contaminate waste oil
- Does not contain 1,1,1 Trichloroethane or Perchloroethylene
- Instantly degreases and leaves no residue

Description:

BRAKE AWAY II is a powerful, non-chlorinated, low odor solvent blend which is formulated to dry quickly. With its technologically advanced formula, it will safely and efficiently clean all brake parts. Safe on most metals, this product is also an excellent degreaser for metal parts. In addition, this product instantly degreases and leaves no residue on equipment.

Areas of Use:

Generators

Air Compressors

Forklifts

• Electric Motors and Components



Applications:

Springs

• Brake Linings

- Chains
- Disc Brake Pads
- · Drums and Cylinders
- CV Joints

Product Characteristics:

104401 01141401011011001		
Appearance:		Not available
Odor:		Not available
Vapor Density:		2 [air = 1]
Vapor Pressure:		101.3 kPa [20°C]
Density:		6.30 lb/gal
Density VOC:		2.84 lb/gal
pH:		7
Viscosity, Kinematic:		<0.205 cm2/s [40°C]
VOC (%):		45%
Flammability (solid/gas):		Flash point below 73°F/23°C
Evaporation Rate:		5.6 [butyl acetate = 1]
tempe	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place.	
Transport Information:		
UN Number:		UN1950
Proper Shipping Name:		Aerosols
Class:		2.1
Packing Group:		N/A

DOT Placard:

N/A

VOC Compliancy:

VOC Restricted States: CA, CO, CT, DE, MI, NY, OH, RI & UT

Directions:

Remove cap and insert extension tube provided into spray tip. Hold can upright and keep tip pointed at dot on valve cup. Spray parts liberally and allow to run off. Air or towel dry with clean, soft wiper. Repeat if necessary. Protect rubber, fiberglass and plastic parts from over spray.

IMPORTANT: Do not spray on hot or warm surfaces. This product will affect certain plastics, various elastomers and some paints. Always test in an inconspicuous area to check product for compatibility.

Pictograms:









Signal Word:

DANGER.

Personal Protective Equipment Required:



