






SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1703	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	DRI LUB	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	Aerosol Dry Lubricant and Release Agent	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Physical Hazards: Flammable aerosols: Category 1 Health Hazards: Serious eye damage/eye irritation: Category 2A Specific target organ toxicity, single exposure: Category 3 narcotic effects Aspiration hazard: Category 1 OSHA defined hazards: Not classified.	SIGNAL WORD: DANGER	SYMBOL:			
---	--------------------------------------	----------------	---	---	---

HAZARD STATEMENTS:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS:

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection.

Response: IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. IF EXPOSED OR CONCERNED: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

ENVIRONMENTAL HAZARDS:

Hazardous to the aquatic environment, acute hazard: Category 2

Hazardous to the aquatic environment, long-term hazard: Category 2

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Butane	106-97-8	20 - 40
Propane	74-98-6	20 - 40
Acetone	67-64-1	10 - 20
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	10 - 20
Ethyl Alcohol	64-17-5	2.5 - 10
n-Heptane	142-82-5	2.5 - 10
Methylcyclohexane	108-87-2	0.1 - 1
Other components below reportable levels		2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL INFORMATION: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

INGESTION: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Alcohol resistant foam. Powder. Carbon dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

SPECIFIC FIRE-FIGHTING METHODS:

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure buildup. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

SPECIAL PROTECTIVE EQUIPMENT/INSTRUCTIONS/PRECAUTIONS FOR FIRE FIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during cleanup. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, See section 8 of the SDS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, See section 13 of the SDS.

ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP METHODS:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, watercourses or onto the ground.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING:

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not reuse empty containers. Avoid breathing gas. Avoid contact with eyes. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection

OCCUPATIONAL EXPOSURE LIMITS

US. OSHA TABLE Z-1 LIMITS FOR AIR CONTAMINANTS (29 CFR 1910.1000)

COMPONENTS	CAS #	TYPE	VALUE
Acetone	(CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
Ethyl Alcohol	(CAS 64-17-5)	PEL	1900 mg/m ³ 1000 ppm
Methylcyclohexane	(CAS 108-87-2)	PEL	2000 mg/m ³ 500 ppm
n-Heptane	(CAS 142-82-5)	PEL	2000 mg/m ³ 500 ppm
Propane	(CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm

US. ACGIH THRESHOLD LIMIT VALUES

COMPONENTS	CAS #	TYPE	VALUE
Acetone	(CAS 67-64-1)	STEL TWA	500 ppm 250 ppm
Butane	(CAS 106-97-8)	STEL	1000 ppm

Ethyl Alcohol	(CAS 64-17-5)	STEL	1000 ppm
Methylcyclohexane	(CAS 108-87-2)	TWA	400 ppm
n-Heptane	(CAS 142-82-5)	STEL TWA	500 ppm 400 ppm
US. NIOSH: POCKET GUIDE TO CHEMICAL HAZARDS COMPONENTS			
	CAS #	TYPE	VALUE
Acetone	(CAS 67-64-1)	TWA	590 mg/m ³ 250 ppm
Butane	(CAS 106-97-8)	TWA	1900 mg/m ³ 800 ppm
Ethyl Alcohol	(CAS 64-17-5)	TWA	1900 mg/m ³ 1000 ppm
Methylcyclohexane	(CAS 108-87-2)	TWA	1600 mg/m ³ 400 ppm
n-Heptane	(CAS 142-82-5)	Ceiling TWA	1800 mg/m ³ 440 ppm 350 mg/m ³ 85 ppm
Propane	(CAS 74-98-6)	TWA	1800 mg/m ³ 1000 ppm
ACGIH BIOLOGICAL EXPOSURE INDICES:			
COMPONENTS	VALUE	DETERMINANT	SPECIMEN
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine
* - For sampling details, please see the source document.			
APPROPRIATE ENGINEERING CONTROLS:			
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.			
INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT :			
			
Face/Eye Protection: Wear safety glasses with side shields (or goggles).			
Skin Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Wear suitable protective clothing.			
Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter/organic vapor cartridge or an air-supplied respirator.			
Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.			
General Hygiene Considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

9. Physical & Chemical Properties			
Physical State:	Gas	Flammability Limit–lower (%)	2% estimated
Form:	Aerosol	Flammability Limit–upper (%):	9.6% estimated
Color:	Not available	Explosive Limit – lower (%):	Not available
Odor:	Not available	Explosive Limit – upper (%):	Not available
Odor Threshold:	Not available	Vapor Pressure:	60 - 80 psig @20°C estimated
pH:	Not available	Vapor Density:	Not available
Melting/Freezing Point:	Not available	Relative Density:	Not available
Boiling Point/Range:	132.89°F (56.05°C) estimated	Solubility(water):	Not available
Partition Coefficient (n-octanol/water):	Not available	Auto-Ignition Temp:	Not available
Viscosity:	Not available	Decomposition Temperature:	Not available
Explosive Properties:	Not explosive	Evaporation Rate:	Not available
Flash Point:	-156.0 °F (-104.4°C) PROPELLANT estimated	Oxidizing Properties:	Not oxidizing
Flammability (solid, gas):	Not available		

10. Stability & Reactivity Information	
REACTIVITY:	The product is stable and nonreactive under normal conditions of use, storage and transport.

CHEMICAL STABILITY:

Material is stable under normal conditions.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

CONDITIONS TO AVOID:

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information**INFORMATION ON LIKELY ROUTES OF EXPOSURE**

EYES: Causes serious eye irritation.

SKIN: No adverse effects due to skin contact are expected.

INHALATION: May cause drowsiness and dizziness. Headache. Nausea, vomiting.

INGESTION: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision.

ACUTE TOXICITY:

May be fatal if swallowed and enters airways. Narcotic effects.

COMPONENTS	SPECIES	TEST RESULTS
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
	Rabbit	> 9.4 ml/kg, 24 Hours
		> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
<i>Oral</i>		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LD50	Mouse	1237 mg/l, 120 Minutes
	Rat	52%, 120 Minutes
		1355 mg/l
Ethyl Alcohol (CAS 64-17-5)		
Acute		
<i>Inhalation</i>		
LC50	Cat	85.41 mg/l, 4.5 Hours
	Mouse	43.68 mg/l, 6 Hours
		> 60000 ppm
	Rat	79.43 mg/l, 134 Minutes
		> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
<i>Oral</i>		
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Pig	>5000 mg/kg
	Rat	10470 mg/kg
		7800 ml/kg
Methylcyclohexane (CAS 108-87-2)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	>2000 mg/kg, 24 Hours
<i>Inhalation</i>		
Vapor		
LC100	Rabbit	59.9 mg/l
LC50	Dog	>4071 ppm, If <1L: Consumer Commodity Hours
		>16.3 mg/l, If <1L: Consumer Commodity Hours
	Mouse	>6564 ppm, If <1L: Consumer Commodity Hours
		>26.3 mg/l, If <1L: Consumer Commodity Hours
	Rat	>6564 ppm, If <1L: Consumer Commodity Hours
		>26.3 mg/l, If <1L: Consumer Commodity Hours
LC50	Rat	16 mg/l, 4 Hours

Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)

Acute		
<i>Dermal</i>		
LD50	Guinea pig; Rabbit Rabbit	> 9.4 ml/kg, 24 Hours >1900 mg/kg, 24 Hours
<i>Inhalation</i>		
LD50	Rat	>5000 mg/m ³ , 4 Hours >4980 mg/m ³ >4980 mg/m ³ , 4 Hours >4.96 mg/l, 4 Hours 13700 ppm, 4 Hours
Oral LD50	Rat	4820 mg/kg
n-Heptane (CAS 142-82-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	>2000 mg/kg, 4 Hours
<i>Inhalation</i>		
LC50	Rat	>29.29 mg/l, 4 Hours
Oral LD50	Rat	5000 mg/kg
PROPANE (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52%, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Prolonged skin contact may cause temporary irritation.

SERIOUS EYE DAMAGE/EYE IRRITATION:

Causes serious eye irritation.

RESPIRATORY SENSITIZATION:

Not a respiratory sensitizer.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

Not applicable.

CARCINOGENIC INFORMATION: Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity: Not listed.

OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1001-1050): Not regulated.

US. NATIONAL TOXICOLOGY PROGRAM (NTP) REPORT ON CARCINOGENS: Not listed.

REPRODUCTIVE TOXICITY:

This product is not expected to cause reproductive or developmental effects.

SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE:

May cause drowsiness and dizziness.

SPECIFIC TARGET ORGAN TOXICITY REPEATED EXPOSURE:

Not classified.

ASPIRATION HAZARD :

May be fatal if swallowed and enters airways.

CHRONIC EFFECTS:

Prolonged exposure may cause chronic effects.

12. Ecological Information

ECOTOXICITY: Toxic to aquatic life with long lasting effects.

COMPONENTS	SPECIES	TEST RESULTS
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
Ethyl Alcohol (CAS 64-17-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Fathead minnow (Pimephales promelas)
Methylcyclohexane (CAS 108-87-2)		
Aquatic		
Fish	LC50	Striped bass (Morone saxatilis)
n-Heptane (CAS 142-82-5)		
Aquatic		
Fish	LC50	Mozambique tilapia (Tilapia mossambica)

* Estimates for product may be based on additional component data not shown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:**Partition coefficient n-octanol / water (log Kow):**

Acetone	-0.24
Butane	2.89
Ethyl Alcohol	-0.31
Methylcyclohexane	3.61
n-Heptane	4.66
Propane	2.36

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration**DISPOSAL INSTRUCTIONS:**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (See: Disposal instructions).

CONTAMINATED PACKAGING:

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not reuse empty containers.

14. Transportation Information

DOT: UN NUMBER: UN1950

UN PROPER SHIPPING NAME: Aerosols, flammable (each not exceeding 1 L capacity)

TRANSPORT HAZARD CLASS(ES)

Class: 2.1

Subsidiary Risk:

Label(s): 2.1

PACKING GROUP: Not applicable.

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

SPECIAL PROVISIONS: N82

PACKAGING EXCEPTIONS: 306

PACKAGING NON BULK: None.

PACKAGING BULK: None.



This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA: UN NUMBER: UN1950

UN PROPER SHIPPING NAME: Aerosols, flammable

TRANSPORT HAZARD CLASS(ES)

Class: 2.1

Subsidiary Risk:

Label(s): 2.1

PACKING GROUP: Not applicable

ENVIRONMENTAL HAZARDS: Yes.

ERG CODE: 10L

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

OTHER INFORMATION:

PASSENGER AND CARGO AIRCRAFT: Allowed with restrictions.

CARGO AIRCRAFT ONLY: Allowed with restrictions.

PACKAGING EXCEPTIONS: LTD QTY

IMDG: UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS

TRANSPORT HAZARD CLASS(ES)

Class: 2.1

Subsidiary Risk:

Label(s): None.

PACKING GROUP: Not applicable.

ENVIRONMENTAL HAZARDS:

Marine pollutant: Yes.

EmS: F-D, S-U

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.



PACKAGING EXCEPTIONS: LTD QTY
TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:
Not applicable.

15. Regulatory Information

US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

SARA 304 Emergency Release Notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories:

Immediate Hazard – Yes.

Delayed Hazard – No.

Fire Hazard – Yes.

Pressure Hazard – No.

No Reactivity Hazard – No.

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous Chemical: No

SARA 313 (TRI reporting): Not regulated.

OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35% WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US STATE REGULATIONS

US California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)):

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)

US. Massachusetts RTK - Substance List:

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Ethyl Alcohol (CAS 64-17-5)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act:

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Ethyl Alcohol (CAS 64-17-5)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law:

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Methylcyclohexane (CAS 108-87-2)

Ethyl Alcohol (CAS 64-17-5)

n-Heptane (CAS 142-82-5)

Propane (CAS 74-98-6)

US. Rhode Island RTK:

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987

Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/ Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

INTERNATIONAL INVENTORIES		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.