

EASY PATCH #3479

Versatile, Durable Repair Patch



Features:

- Repairs angled, curved, dented, flat, jointed & irregular surfaces
- No mixing, no mess, no measuring
- Tested to 250 PSI
- Adheres to any surface except polypropylene Low VOC
- Temperature range after cured is -30°F to +365°F
- Rot proof
- Waterproof
- Self-adhering
- Safe for use in areas with food contact
- 3 sizes available: 3" x 6"; 6" x 9" and 9" x 12"



Description:

EASY PATCH is a versatile, easy-to-use, durable repair material with hundreds of uses. This specially formulated patch is reinforced with fiberglass and is activated by ultraviolet light (both natural sunlight and UV lamp). Simply peel off the film to expose the sticky resin, apply it to the prepared surface needing repair and expose to sunlight. It cures in about 10 minutes to a rock-hard, durable, corrosion-resistant surface that can be drilled, sanded or painted, making this a quick and easy solution for all your repair problems. It has been tested by an independent laboratory and is appropriate for use in areas with food contact.

Applications:

- Damaged Wood
- Rusty Metal
- Gutters
- Fiberglass
- Concrete
- Copper
- Plastic
- Drywall
- Flashing
- Roof Tiles
- Hitches
- Autos
- HVAC
- Utility Housing
- PVC

Areas of Use:

- Industrial
- Utilities
- Plumbing
- Construction
- Municipalities
- Trucking Companies
- DOT
- Water Treatment Plants
- Landscaping Companies
- Marine
- Tooling
- Manufacturing

Product Characteristics:

Appearance:	Soft, tacky material
Odor:	Sweet
Boiling Point:	Not available
Explosive Limits:	Not available
Vapor Pressure:	4.5 (styrene)
Flash Point:	840°F
Vapor Density:	3.6 (styrene)
Evaporation Rate:	0.00
Solubility	Not soluble in water
Viscosity	Solid state
Storage:	For maximum storage life and to maintain material workability, store below 72°F (22°C). Material is packaged in special bags impermeable to styrene. Do not puncture bag. Reseal after partial use. Store locked up.
Transport Information (DOT):	
Proper Shipping Name:	Not available
UN Number:	Not available
Class:	Not available
Packing Group:	Not available

Directions:

Rough up area needing repair. Remove film backing from both sides of patch and press firmly to dry, prepared surface. Expose to sunlight or UV source to cure.

EASY PATCH may not stick to polypropylene. When used inside where sunlight cannot reach the repair area, a UV flashlight (Spec: 350-400 mns/75 mm/11 w) must be used for proper curing.

Pictograms:



Signal Word:
DANGER.

Personal Protective Equipment Required:



DOT Placard:
Not available.