ECO LIFT #2420

Floating Lift Station Degreaser and Odor Barrier



Features:

- Quickly dissolves and dissipates heavy grease and fat accumulations
- 100% natural and biodegradable formula
- Does not allow the grease to re-solidify
- No petroleum distillates or hazardous solvents
- Stays on the water's surface and rises and falls with the water level for continuous contact
- Contains a special color indicator to provide visual of the product level in lift stations
- Will not interfere with the bacterial action in sewage treatment plants
- · Creates an odor absorbing barrier and leaves a pleasant scent
- Will not emulsify grease



Description:

ECO LIFT is made from 100% natural ingredients such as d-Limonene and soybean derivatives that keep lift station surfaces free of grease. It coats the walls and surfaces of the lift stations to remove heavy grease accumulations quickly and safely. The special, nonemulsifying formula floats on the surface of the water, so it continues to remove deposits as the water level changes.

This product contains a soybean oil derivative and has a slow evaporation rate. It will remain on the surface of wastewater to penetrate fat, grease and dirt and then strip them away from the surface.

Effective Against:

• Floating Greaseballs • Heavy Oil Accumulation • Problematic Odors • Will not allow grease to re-solidify

Product Characteristics:

Appearance:		Clear, green liquid		
Odor:		Citrus fruit		
Vapor Pressure:		No data available		
Specific Gravity:		0.88 g/ml		
Solubility:		Insoluble in water		
Flash Point:		>210°F Closed cup		
VOC:		<6%		
Viscosity:		No data available		
Storage:	Store	Store in a well-ventilated place. Keep		
	cool. Store locked up.			
Transport Information:				
UN Number:			Not regulated for transport	
Proper Shipping Name:		ame:	Not regulated for transport	
Class:			Not regulated for transport	
Packing Group:		·	Not regulated for transport	

DOT Placard: VOC Compliant:

MMABLE GAS

VOC Compliant: Yes.

Directions:

Pour ECO LIFT into the lift station. Use approximately 1/2 gallon for every square foot of wastewater surface area. Always maintain a protective layer of 1 to 3 inches of ECO LIFT above water level.

Pictograms:



Signal Word: WARNING

Personal Protective Equipment Required:



