

# Electro Solv #1616

## Aerosol Safety Solvent



### Features:

- Noncorrosive, nonconductive, nonflammable
- Powerful flushing action
- Safe for cleaning energized electrical equipment
- Dries super fast and residue free
- 30.0 kV dielectric strength (ASTM D-877)
- No petroleum distillates
- Dual spray valve



### Description:

ELECTRO SOLV is a fast drying, nonflammable, solvent cleaner and degreaser spray. It contains trichloroethylene, an accepted replacement for 1,1,1 Trichloroethane under the EPA SNAP program. Powerful flushing action penetrates through and removes grease, grime, dirt, tar, wax and other contaminants. The dielectric strength and nonflammability of the product allows it to be used on electrical equipment and machines, even while energized. Dries fast and residue free. ELECTRO SOLV features a dual spray valve, which eliminates the need for extension tubes.

### Applications:

- Industrial Equipment
- Generators
- Windings
- Engine Parts and Motors
- Gas, Water and Electrical Meters
- Gears and Bearings
- Production Machinery
- Power Tools
- Electrical Motors
- Refrigeration Equipment
- Assemblies of Electrical Equipment
- Heating and Air Conditioning Equipment

### Product Characteristics:

Appearance:	Clear, colorless liquid.
Odor:	Ether-like odor.
Vapor Pressure:	55-75 psig @70°F estimated.
Specific Gravity:	1.454 estimated.
Solubility:	Not available.
Flash Point:	None to boiling.
VOC:	96.45%
Viscosity:	Not available.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

### Transport Information:

Proper Shipping Name:	Aerosols, nonflammable, (each not exceeding 1 L capacity).
UN Number:	UN1950
Class:	2.2
Packing Group:	Not applicable.

### DOT Placard:



### Directions:

Saturate part to be cleaned. Wipe or allow to air dry. For heavily encrusted areas, brush, then rinse off with a second application. May remove some paints, pre-testing is suggested.

**Note:** Energized equipment use only. Do not use on motorized vehicle maintenance and solvent sensitive plastic surfaces or materials. May remove some paints. Always test first on scrap material or on a small inconspicuous area. Tilt forward for jet stream that shoots 8 feet to reach remote objects and small devices. Push down for regular spray to cover surface areas.

### Pictograms:



### Signal Word:

Danger.

### Personal Protective Equipment Required:

