





SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1474	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	EXPANDO	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	Expanding Insulating Foam Sealant In Convenient Aerosol	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Flammable aerosols: Category 1 Skin corrosion/irritation: Category 2 Serious eye damage/eye irritation: Category 2A Sensitization, respiratory: Category 1 Sensitization, skin: Category 1 Carcinogenicity: Category 2 Specific target organ toxicity, repeated exposure: Category 2 Environmental hazards: Not classified. OSHA defined hazards: Not classified.	SIGNAL WORD: DANGER	SYMBOL:		
---	--------------------------------------	----------------	---	---

HAZARD STATEMENTS:

Extremely flammable aerosol. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response:

IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF EXPOSED OR CONCERNED: Get medical advice/attention. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash before reuse.

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Butane	106-97-8	10-20
Dimethyl Ether	115-10-6	10-20
Methylene bisphenol isocyanate (MDI)	101-68-8	10-20
Propane	74-98-6	2.5-10
Other components below reportable levels		60-80

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

EYES: Rinse with water. Get medical attention if irritation develops and persists.

SKIN: In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

INHALATION:

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

INGESTION:

Rinse mouth. Get medical attention if symptoms occur.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Dermatitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing.

Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Prolonged exposure may cause chronic effects.
INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:
Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Dry powder. Carbon dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Water.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

SPECIFIC FIRE-FIGHTING METHODS:

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area, if you can do so without risk. In the event of fire and/or explosion, do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP METHODS:

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flames, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak, if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements, or confined areas. Following product recovery, flush area with water. For waste disposal, see Section 13 of the SDS. Avoid discharge into drains, watercourses or onto the ground.

7. Handling and Storage

SAFE HANDLING:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate, or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

COMPONENTS	TYPE	VALUE
Dimethyl Ether (CAS 115-10-6)	STEL	2 ppm
	TWA	0.75 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)


COMPONENTS	TYPE	VALUE
Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)	Ceiling	0.2 mg/m ³
		0.02 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³
		1000 ppm

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
Butane (CAS 106-97-8)	STEL	1000 ppm
Dimethyl Ether (CAS 115-10-6)	Ceiling	0.3 ppm
Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)	TWA	0.005 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

COMPONENTS	TYPE	VALUE
Butane (CAS 106-97-8)	TWA	1900 mg/m ³
		800 ppm
Dimethyl Ether (CAS 115-10-6)	Ceiling	0.1 ppm
	TWA	0.016 ppm
Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)	Ceiling	0.2 mg/m ³
		0.02 ppm
	TWA	0.05 mg/m ³

Propane (CAS 74-98-6)	TWA	0.005 ppm 1800 mg/m ³ 1000 ppm
US. Workplace Environmental Exposure Level (WEEL) Guides		
COMPONENTS	TYPE	VALUE
Dimethyl Ether (CAS 115-10-6)	TWA	1880 mg/m ³ 1000 ppm
BIOLOGICAL LIMIT VALUE:		
No biological exposure limits noted for the ingredient(s).		
ENGINEERING CONTROLS:		
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eyewash facilities and emergency shower must be available when handling this product.		
INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:		
		
EYE PROTECTION: Wear safety glasses with side shields (or goggles).		
SKIN PROTECTION: Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
RESPIRATORY PROTECTION: If permissible levels are exceeded, use NIOSH mechanical filter/organic vapor cartridge or an air-supplied respirator.		
THERMAL HAZARDS: Wear appropriate thermal protective clothing, when necessary.		
GENERAL HYGIENE CONSIDERATIONS: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.		

9. Physical & Chemical Properties

APPEARANCE:		FLAMMABILITY(solid/gas):	Not available.
Physical State:	Gas	Flammability Limit–lower (%)	Not available.
Form:	Aerosol.	Flammability Limit–upper (%)	Not available.
Color:	Not available.	Explosive Limit – lower (%)	Not available.
ODOR:	Not available.	Explosive Limit – upper (%)	Not available.
ODOR THRESHOLD:	Not available.	VAPOR PRESSURE:	5336.16 psig @70°F estimated
pH:	Not available.	VAPOR DENSITY:	Not available.
MELTING/FREEZING POINT:	Not available.	RELATIVE DENSITY:	Not available.
INITIAL BOILING POINT/RANGE:	-0.34°F (-17.97°C) estimated	SOLUBILITY (water):	Not available.
PARTITION COEFFICIENT (n-octanol/water):	Not available.	AUTO-IGNITION TEMP:	Not available.
VISCOSITY:	Not available.	DECOMPOSITION TEMP:	Not available.
SPECIFIC GRAVITY:	0.52 estimated	FLASH POINT:	-156.0°F (-104.4°C) Propellant estimated
EVAPORATION RATE:	Not available.		

10. Stability & Reactivity Information

REACTIVITY:	The product is stable and non-reactive under normal conditions of use, storage, and transport.
CHEMICAL STABILITY:	Material is stable under normal conditions.
POSSIBILITY OF HAZARDOUS REACTIONS:	Hazardous polymerization does not occur.
INCOMPATIBLE MATERIALS:	Strong oxidizing agents. Nitrates. Alkaline metals. Alcohols. Fluorine. Chlorine. Phenols.
CONDITIONS TO AVOID:	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
DECOMPOSITION PRODUCTS:	No hazardous decomposition products are known.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:	
EYES:	Causes serious eye irritation.
SKIN:	Causes skin irritation. May cause an allergic skin reaction.
INHALATION:	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
INGESTION:	Expected to be a low ingestion hazard.
SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:	
	Dermatitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.
ACUTE TOXICITY:	May cause an allergic skin reaction.
COMPONENTS	SPECIES TEST RESULTS

Butane (CAS 106-97-8)			
Acute			
<i>Inhalation</i>			
LC50	Mouse		1237 mg/l, 120 Minutes
	Rat		52 %, 120 Minutes
			1355 mg/l
Dimethyl Ether (CAS 115-10-6)			
Acute			
<i>Inhalation</i>			
NOEL	Rat		2 ppm, 6 Hours
<i>Oral</i>			
LD50	Rat		460 mg/kg
Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)			
Acute			
<i>Dermal</i>			
LD50	Rabbit		> 9400 mg/kg, 24 Hours
<i>Other</i>			
LD50	Mouse		100 mg/kg
Propane (CAS 74-98-6)			
Acute			
<i>Inhalation</i>			
LC50	Mouse		1237 mg/l, 120 Minutes
	Rat		52 %, 120 Minutes
			1355 mg/l
			658 mg/l/4 h
* Estimates for product may be based on additional component data notshown.			
SKIN CORROSION/IRRITATION:			
Causes skin irritation.			
SERIOUS EYE DAMAGE/IRRITATION:			
Causes serious eye irritation.			
RESPIRATORY SENSITIZATION:			
May cause allergy or asthma symptoms or breathing difficulties if inhaled.			
SKIN SENSITIZATION:			
May cause an allergic skin reaction.			
GERM CELL MUTAGENICITY:			
No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
CARCINOGENICITY:			
Suspected of causing cancer.			
IARC Monographs. Overall Evaluation of Carcinogenicity			
Methylene bisphenol isocyanate (MDI) (CAS 101-68-8) 3 Not classifiable as to carcinogenicity to humans.			
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.			
REPRODUCTIVE TOXICITY:			
This product is not expected to cause reproductive or developmental effects.			
SPECIFIC TARGET ORGAN TOXICITY (single exposure):			
Not classified.			
SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):			
Respiratory system. Eyes. May cause damage to organs through prolonged or repeated exposure.			
ASPIRATION HAZARD:			
Not likely, due to the form of the product.			
CHRONIC EFFECTS:			
Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.			

12. Ecological Information

ECOTOXICITY:

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

COMPONENTS	SPECIES	TEST RESULTS
Dimethyl Ether (CAS 115-10-6)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia pulex)
Fish	LC50	Striped bass (Morone saxatilis)
		4.3 - 7.8 mg/l, 48 hours
		10.302 - 16.743 mg/l, 96 hours

* Estimates for product may be based on additional component data notshown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:

No data available.

Partition coefficient n-octanol/water (log Kow)

Butane	2.89
Dimethyl Ether	0.1
Propane	2.36

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming)

potential) are expected from this component.

13. Disposal Consideration

DISPOSAL INSTRUCTIONS:

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

CONTAMINATED PACKAGING:

Empty containers should be taken to an approved waste-handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not reuse empty containers.

14. Transportation Information

DOT: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable
TRANSPORT HAZARD CLASS(ES)
Class: 2.1
Subsidiary Risk: --
Label(s): None.



PACKING GROUP: Not applicable.

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

SPECIAL PROVISIONS: N82

PACKAGING EXCEPTIONS: 306

PACKAGING NON BULK: None.

PACKAGING BULK: None.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable
TRANSPORT HAZARD CLASS(ES)
Class: 2.1
Subsidiary Risk: --
Label(s): None.



PACKING GROUP: Not applicable.

ENVIRONMENTAL HAZARDS: No.

ERG CODE: 10L

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

OTHER INFORMATION:

PASSENGER AND CARGO AIRCRAFT: Allowed.

CARGO AIRCRAFT ONLY: Allowed.

PACKAGING EXCEPTIONS: LTD QTY

IMDG: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: AEROSOLS
TRANSPORT HAZARD CLASS(ES)
Class: 2.1
Subsidiary Risk: --
Label(s): None.



PACKING GROUP: Not applicable.

ENVIRONMENTAL HAZARDS:

Marine pollutant: No.

EmS: F-D, S-U

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling. \

PACKAGING EXCEPTIONS: LTD QTY

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:

Not applicable.

15. Regulatory Information

US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4):

Methylene bisphenol isocyanate (MDI) (CAS 101-68-8) Listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

Hazard categories: Immediate Hazard - Yes

Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance: Not listed.

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting):

CHEMICAL NAME	CAS NO	% BY WT.
Diphenylmethane Diisocyanate [isomers And Homologues]	9016-87-9	10-20
Methylene bisphenol isocyanate (MDI)	101-68-8	10-20

OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:

Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Butane (CAS 106-97-8)

Dimethyl Ether (CAS 115-10-6)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

US STATE REGULATIONS

US. Massachusetts RTK - Substance List:

Butane (CAS 106-97-8)

Dimethyl Ether (CAS 115-10-6)

Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act:

Butane (CAS 106-97-8)

Dimethyl Ether (CAS 115-10-6)

Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law:

Butane (CAS 106-97-8)

Dimethyl Ether (CAS 115-10-6)

Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)

Propane (CAS 74-98-6)

US. Rhode Island RTK:

Butane (CAS 106-97-8)

Dimethyl Ether (CAS 115-10-6)

Methylene bisphenol isocyanate (MDI) (CAS 101-68-8)

Propane (CAS 74-98-6)

US. California Proposition 65:

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.