

FAST CLEAN #2298

All-Natural Asphalt Remover



Features:

- Penetrates, dissolves and removes the toughest tar and asphalt products
- Performs quickly and evaporates slowly to work for a longer period
- Non-flammable, non-hazardous
- 100% biodegradable.
- Can be used in both hot and cold working conditions
- Contains no VOC's



Description:

FAST CLEAN is an asphalt remover that works better and more quickly than diesel fuel or citrus-based products for dissolving asphalt. The evaporation rate of FAST CLEAN is slower than diesel fuel and orange-based products so it can continue cleaning for a longer period of time. Penetrating deep to soften more tar and leaving less redeposition makes this product the perfect choice for all asphalt removing jobs.

Applications:

- Chutes
- Rakes
- Beds
- Cones
- Tar Kettles
- Shovels
- Distributor Bars
- Grader Blades
- Hot Patch Trucks
- Pavers & Paving Equipment
- Tack Lines
- Over Spray on Concrete

Product Characteristics:

Data below based on aerosol concentrate only:

Appearance:	Amber, liquid
Odor:	Bland
Vapor Density:	Not established
Evaporation Rate:	Not established
Solubility (water):	Soluble
Flash Point:	None
VOC (g/L):	0
Relative Density (H2O=1):	1.085
Vapor Pressure:	Not available
Boiling Point/Range:	212°F (100°C)
Melting/Freezing Point:	32°F (0°C)
pH:	7
Flammable Limits:	Not applicable
Storage:	Store in cool, dry area. Prevent product from freezing. Keep out of the reach of children. Shelf life: 3 years as long as the product is kept in a clean, dry environment away from direct sunlight and/or excessive heat.
Transport Information:	
Proper Shipping Name:	Nonhazardous liquid
UN Number:	Not applicable
Class:	Not regulated

Directions:

REMOVAL APPLICATION: Do not dilute with water. For light buildup of asphalt, let sit for 5-10 minutes, then spray clean with water or wipe clean with a wet cloth. For heavy buildup of asphalt, let sit until asphalt has softened, then spray clean with water. For tough-to-remove, heavy buildup, apply FAST CLEAN and allow to sit for 15-20 minutes. Use a stiff-bristled brush to scrub the asphalt before spraying with clean water. Heavy buildup may require a second application.

Do not dilute with water.

Pictograms:



Signal Word:
WARNING

Personal Protective Equipment Required:



DOT Placard:
Not available.

VOC Compliant:
Yes.