

FUEL PLUS X-100 #2929

Gasoline and Off-Road Diesel Fuel Conditioner Concentrate



Features:

- Increases mileage by making combustion more efficient and cleaner
- Absorbs moisture
- Removes carbon and gum deposits
- Reduces downtime and maintenance cost
- Stops valves from sticking and burning
- Increases RPM's
- Acts as upper cylinder lubricant
- Removes sludge and varnish
- Neutralizes sulphur and acids
- Cleans injectors and carburetors
- Improves ring flexing



Description:

Fuel Plus X-100 is blended to neutralize harmful fuel acids, as well as eliminate the damage caused by sulfur, gum and varnish that is in all fuels. It is oxygen sensor safe. The antiwear, additives and penetrants are stable solutions that offer outstanding performance and are safe to use in engines that use all types of fuel, including engines equipped with catalytic converters. Recommended for use in off-road diesel, gasoline (leaded and unleaded), L.P.G. and kerosene fuel vehicles. This product can also be used to free frozen nuts and bolts or as a penetrating oil that will stay on the surface and prevent corrosion and oxidation on fishing tackle, farm implements, fertilizer equipment, weapons and other similar applications.

Applications:

- Gasoline Engines
- Stationary Engines
- Marine Engines (Except Outboard)
- Off-Road Diesel Engines
- Storage for Bunker Fuels
- 2-Cycle and Outboard Engines

Product Characteristics:

Appearance:	Clear, red liquid
Odor:	Characteristic
Boiling Point:	120°C
Vapor Pressure:	200 hPa
Solubility(water):	Negligible
Relative Vapor Density:	No data available
Flash Point:	23.3°C; Method: TCC
Density:	0.89 g/cm ³
pH:	No data available
Evaporation Rate:	2
Storage:	Store in a well-ventilated place. Keep cool. Store locked up.
Transport Information:	
UN Number:	UN1993
Proper Shipping Name:	Flammable liquid, n.o.s
Class:	3
Packing Group:	III

DOT Placard:

Not available.

Directions:

- Gasoline Engines – 1 gallon product per 200 gallons of fuel
- Diesel Engines – 1 gallon product per 200 gallons of fuel
- Marine Engines (except outboards) – 1 gallon product per 200 gallons of fuel.
- Stationary Engines – 1 gallon product per 200 gallons of fuel
- Storage for Bunker Fuels – 1 gallon product per 500 gallons of fuel.
- Two Cycle and Outboard Engines – 2 oz. product per each qt of oil used in fuel or, if premixed, use 1 oz. product per gallon.

NOTE: For L.P.G., propane, or natural gas engines, use with a Universal Top Oil.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:

