

FUEL PLUS X-100 #2929

Gasoline and Off-Road Diesel Fuel Conditioner Concentrate



Features:

- Increases mileage by making combustion more efficient and cleaner
- Absorbs moisture
- Removes carbon and gum deposits
- Reduces downtime and maintenance cost
- Stops valves from sticking and burning
- Increases RPM's
- Acts as upper cylinder lubricant
- Removes sludge and varnish
- Neutralizes sulphur and acids
- Cleans injectors and carburetors
- Improves ring flexing



Description:

Fuel Plus X-100 is blended to neutralize harmful fuel acids, as well as eliminate the damage caused by sulfur, gum and varnish that is in all fuels. It is oxygen sensor safe. The antiwear, additives and penetrants are stable solutions that offer outstanding performance and are safe to use in engines that use all types of fuel, including engines equipped with catalytic converters. Recommended for use in off-road diesel, gasoline (leaded and unleaded), L.P.G. and kerosene fuel vehicles. This product can also be used to free frozen nuts and bolts or as a penetrating oil that will stay on the surface and prevent corrosion and oxidation on fishing tackle, farm implements, fertilizer equipment, weapons and other similar applications.

Applications:

- Gasoline Engines
- Stationary Engines
- Marine Engines (Except Outboard)
- Off-Road Diesel Engines
- Storage for Bunker Fuels
- 2-Cycle and Outboard Engines

Product Characteristics:

Appearance:	Clear, red liquid
Odor:	Characteristic
Boiling Point:	120°C
Vapor Pressure:	200 hPa
Solubility(water):	Negligible
Relative Vapor Density:	No data available
Flash Point:	23.3°C; Method: TCC
Density:	0.89 g/cm ³
pH:	No data available
Evaporation Rate:	2
Storage:	Store in a well-ventilated place. Keep cool. Store locked up.
Transport Information:	
UN Number:	UN1993
Proper Shipping Name:	Flammable liquid, n.o.s
Class:	3
Packing Group:	III

Directions:

- Gasoline Engines – 1 gallon product per 200 gallons of fuel
- Diesel Engines – 1 gallon product per 200 gallons of fuel
- Marine Engines (except outboards) – 1 gallon product per 200 gallons of fuel.
- Stationary Engines – 1 gallon product per 200 gallons of fuel
- Storage for Bunker Fuels – 1 gallon product per 500 gallons of fuel.
- Two Cycle and Outboard Engines – 2 oz. product per each qt of oil used in fuel or, if premixed, use 1 oz. product per gallon.

NOTE: For L.P.G., propane, or natural gas engines, use with a Universal Top Oil.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:



DOT Placard:

Not available.






SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	2929	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	FUEL PLUS X-100	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	Gasoline and Diesel Fuel Conditioner Concentrate	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Flammable liquids: Category 3 Skin irritation: Category 2 Serious eye damage: Category 1 Specific target organ toxicity - single exposure: Category 2 Specific target organ toxicity - repeated exposure: Category 2 Aspiration hazard: Category 1	SIGNAL WORD: DANGER	SYMBOL:			
---	--------------------------------------	----------------	---	---	---

HAZARD STATEMENTS:

Flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye damage.
May cause damage to organs.
May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

Prevention:

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash skin thoroughly after handling.
Do not eat, drink, or smoke when using this product.
Wear protective gloves/eye protection/face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
IF EXPOSED OR YOU FEEL UNWELL: Call a POISON CENTER or doctor/physician.
Get medical advice/attention if you feel unwell.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.
IN CASE OF FIRE: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

STORAGE:

Store in a well-ventilated place. Keep cool.
Store locked up.

DISPOSAL:

Dispose of contents/container in accordance with local regulation.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 70 - < 90
butan-2-ol	78-92-2	>= 10 - < 20
Cresol	1319-77-3	>= 1 - < 5
Cyclohexanone	108-94-1	>= 1 - < 5

4. First Aid Measures

EMERGENCY OVERVIEW

WARNING: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.

EYES: Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

SKIN: If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

INHALATION:

Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.

INGESTION:

Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

UNSUITABLE FIRE EXTINGUISHING MEDIA:

High volume water jet.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon dioxide (CO₂). Carbon monoxide. Smoke.

SPECIFIC FIRE-FIGHTING METHODS:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons, in case of fire cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Wear self-contained breathing apparatus for firefighting if necessary.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Use personal protective equipment. Ensure adequate ventilation. Refer to protective measures listed in Sections 7 and 8.

ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP METHODS:

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see Section 13). Keep in suitable, closed containers for disposal.

7. Handling and Storage

SAFE HANDLING PRACTICES:

Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in workrooms. Container may be opened only under exhaust ventilation hood. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.

SAFE STORAGE:

No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations/working materials must comply with the technological safety standards.

MATERIALS TO AVOID:

Oxidizing agents. Do not freeze.

8. Exposure Controls / Personal Protection

Components	CAS #	Value Type (form of exposure)	Control Parameters/Permissible Concentration	Basis
butan-2-ol	78-92-2	TWA	100 ppm	ACGIH
		TWA	100 ppm	NIOSH REL
		ST	305 mg/m ³	NIOSH REL
		ST	150 ppm	NIOSH REL
		TWA	455 mg/m ³	OSHA Z-1
		TWA	150 ppm	OSHA Z-1
Cresol	1319-77-3	TWA	450 mg/m ³	OSHA P0
		TWA	100 ppm	OSHA P0
		TWA	305 mg/m ³	OSHA Z-1
Cyclohexanone	108-94-1	TWA	5 ppm	OSHA Z-1
		STEL	22 mg/m ³	ACGIH
		TWA	20 ppm	ACGIH
		TWA	50 ppm	NIOSH REL
		TWA	25 ppm	NIOSH REL
		TWA	100 mg/m ³	OSHA Z-1
		TWA	50 ppm	OSHA Z-1
		TWA	200 mg/m ³	OSHA P0
		TWA	25 ppm	OSHA P0
			100 mg/m ³	

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS

Components	CAS #	Control Parameters	Biological Specimen	Sampling Time	Permissible Concentration	Basis
CYCLOHEXANONE	108-94-1	1,2-	Urine	End of shift at end of workweek	80 mg/l	ACGIH BEI

CYCLOHEXANONE

Cyclohexanediol
Cyclohexanol

Urine

End of shift (As soon as possible
after exposure ceases)

8 mg/l

ACGIH BEI

PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Eyewash bottle with pure water. Tightly fitting safety goggles. Wear face-shield and protective suit for abnormal processing problems.

SKIN PROTECTION: Skin should be washed after contact. For prolonged or repeated contact use protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required. In case of insufficient ventilation, wear suitable respiratory equipment.

HYGIENE MEASURES: When using, do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

9. Physical & Chemical Properties

APPEARANCE:	Liquid.	FLASH POINT:	23.3°C; Method: TCC
Color:	Clear, red.	EVAPORATION RATE:	2
ODOR:	Characteristic.	Explosive Limit – lower (%):	No data available.
ODOR THRESHOLD:	No data available.	Explosive Limit – upper (%):	No data available.
pH:	No data available.	VAPOR PRESSURE:	200 hPa
MELTING/FREEZING POINT:	No data available.	RELATIVE VAPOR DENSITY:	No data available.
BOILING POINT:	120°C	DENSITY:	0.89 g/cm ³
PARTITION COEFFICIENT (n-octanol/water):	No data available.	SOLUBILITY (water):	Negligible.
VISCOSITY, KINEMATIC:	No data available.	AUTO-IGNITION TEMP:	Not determined.
SOLUBILITY (other solvents):	Not determined.	THERMAL DECOMPOSITION:	No data available.

10. Stability & Reactivity Information**REACTIVITY:**

Stable. No decomposition if stored and applied as directed.

CHEMICAL STABILITY:

Stable under normal conditions. No decomposition if stored and applied as directed.

POSSIBILITY OF HAZARDOUS REACTIONS:

No hazards to be specifically mentioned. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents.

CONDITIONS TO AVOID:

Heat, flames, and sparks.

DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide, and unburned hydrocarbons (smoke).

11. Toxicological Information**ACUTE TOXICITY:****Product:**

Acute oral toxicity estimate: 2,869 mg/kg.
Method: Calculation method/
> 40 mg/l.

Acute inhalation toxicity estimate: > 40 mg/l.
Exposure time: 4 h.
Test atmosphere: vapour.

Acute dermal toxicity estimate: > 5,000 mg/kg.
Method: Calculation method.

Components:**butan-2-ol:**

Acute oral toxicity: LD50 Oral rat: 2,193 mg/kg
Acute dermal toxicity: LD50 Dermal rat: > 2,000 mg/kg

SKIN CORROSION/IRRITATION:

Extremely corrosive and destructive to tissue.

SERIOUS EYE DAMAGE/EYE IRRITATION:

May cause irreversible eye damage.

RESPIRATORY OR SKIN SENSITIZATION:

No data available.

GERM CELL MUTAGENICITY:

No data available.

CARCINOGENICITY:

IARC: No component of this product presents at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product presents at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product presents at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

OSHA.

NTP: No component of this product presents at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by NTP.

REPRODUCTIVE TOXICITY:

No data available.

Distillates (petroleum), hydrotreated light naphthenic:

butan-2-ol:

cresol:

cyclohexanone:

STOT - single exposure:

No data available.

STOT - repeated exposure:

No data available.

ASPIRATION TOXICITY:

No data available.

FURTHER INFORMATION:

No data available. Symptoms of overexposure may be headache, dizziness, tiredness, nausea, and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

12. Ecological Information

ECOTOXICITY:

No data available.

PERSISTENCE AND DEGRADABILITY:

No data available.

BIOACCUMULATIVE POTENTIAL:

Product:

Partition coefficient: n-octanol/water: No data available.

Component:

butan-2-ol:

Partition coefficient: n-octanol/water: log Pow: 0.146.

cyclohexanone:

Partition coefficient: n-octanol/water: log Pow: 0.81.

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No data available.

Product:

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 40 CFR 82, Subpt. A, App.A + B).

ADDITIONAL ECOLOGICAL INFORMATION:

No data available.

13. Disposal Consideration

WASTE FROM RESIDUES:

Dispose of in accordance with local regulations. Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

CONTAMINATED PACKAGING:

Empty remaining contents. Dispose of as unused product. Do not reuse empty containers. Do not burn, or use a cutting torch on, the empty drum.

14. Transportation Information

INTERNATIONAL REGULATION:

IATA-DGR:

UN/ID No. 1993

Proper shipping name: Flammable liquid, n.o.s. (Distillates (petroleum), hydrotreated light naphthenic).

Class: 3

Packing group: III

Labels: 3

Packing instruction (cargo aircraft): 366

Packing instruction (passenger aircraft): 355

IMDG-CODE:

UN Number: 1993

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (distillates (petroleum), hydrtreated light naphthenic).

Class: 3

Packing group: III

Labels: 3

EmS code: F-E, S-E

Marine pollutant: No.

TRANSPORT IN BUL ACCORDING TO Annex II of MARPOL 73/78 and the IBC Code:

Not applicable for product as supplied.

NATIONAL REGULATIONS: 49 CFR:

UN/ID/NA #: 1993

Proper shipping name: Flammable liquids, n.o.s.

Class: 3

Packing group: III

Labels: 3

ERG CODE: 128

Marine pollutant: No.

SPECIAL PRECAUTIONS FOR USER:

Not applicable.

15. Regulatory Information

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

COMPONENTS	CAS #	COMPONENT RQ (lbs):	CALCULATED PRODUCT RQ (lbs)
Cresol	1319-77-3	100	4207

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards:

Fire Hazard

Acute Health Hazard

SARA 302:

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313:

The following components are subject to reporting levels established by SARA Title III, Section 313:

butan-2-ol 78-92-2 19.532 %

CALIFORNIA PROP 65:

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	All components of this product are on the Canadian DSL.
AICS	On the inventory, or in compliance with the inventory
NZIoC	On the inventory, or in compliance with the inventory
PICCS	On the inventory, or in compliance with the inventory
IECSC	On the inventory, or in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.



FUEL PLUS X-100 NEW & IMPROVED

DESCRIPTION

This product is a modern, concentrated fuel conditioner that is specifically engineered to answer the needs of today's high performance engines. It is blended to neutralize harmful fuel acids, as well as to eliminate the damage caused by sulphur, gum, varnish and moisture, which is found in all fuels.

COMPOSITION

This product is blended from high performance, specially selected neutrals, acid and sulphur neutralizers, moisture absorption additives, friction release agents, conditioners and pure mineral base oils. The antiwear, corrosion inhibitors and penetrants in this product are stable solutions that offer outstanding performance and are recommended for use with all grades of gasoline in all engines, including engines that are equipped with catalytic converters.

USES

This product is highly recommended for use in diesel, gasoline (including leaded and unleaded) L.P.G. and kerosene fuels. It is used in fuels at the concentration of 1 gallon to 200 to:

- Obtain Cleaner, More Complete Combustion • Increase Mileage
- Neutralize Sulphur and Acids • Absorb Moisture • Clean Injectors and Carburetors
- Improve Ring Flexing • Remove Sludge and Varnish
- Stop Valves from Sticking and Burning • Increase R.P.M.s • Remove Carbon and Gum Deposits
- And in general, to improve performance, and reduce downtime and maintenance costs

TYPICAL APPLICATIONS

Gasoline Engines:	1 gallon to 200 gallons of fuel
Diesel Engines:	1 gallon to 200 gallons of fuel
Marine Engines(except outboards):	1 gallon to 200 gallons of fuel
Stationary Engines:	1 gallon to 200 gallons of fuel
Storage for Bunker Fuels:	1 gallon to 500 gallons of fuel
Two Cycle and Outboard Engines:	2 ounces to each quart of oil used in fuel, or if premixed, use 1 ounce per gallon.

NOTE: For L.P.G., propane or natural gas engines, use with a Universal Top Oiler. This product can also be used to free frozen nuts and bolts, or as a penetrating oil that will stay on the surface and prevent corrosion and oxidation on fishing tackle, farm implements, fertilizer equipment, weapons and other similar applications.

Registered with the EPA in accordance with the regulations for fuel and fuel conditioners.

This diesel fuel additive does not comply with federal ultra-low sulfur content requirements for use in model year 2007 and newer diesel motor vehicles or model year 2011 and newer diesel nonroad equipment engines.

DANGER:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.

NET CONTENTS: 6 GALLONS (22.7 LITERS)



DANGER:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ eye protection/ face protection. **Response:** IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. IF exposed or you feel unwell: Call a POISON CENTER or doctor/ physician. Get medical advice/ attention if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. **Storage:** Store in a well-ventilated place. Keep cool. Store locked up. **Disposal:** Dispose of contents/container in accordance with local regulation.

1047703-1 04/15

DISPOSAL AND/OR SPILL INFORMATION: As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted to a collection vessel, and not allowed to soak into the ground or to enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, absorb product on an inert absorbent material, and deposit in a clean container for disposal as a hazardous waste. Thoroughly clean area with a detergent solution and rinse area well with water. **STORAGE:** Keep container tightly closed when not in use to decrease evaporation of volatile solvents. Keep this product away from food and food products. Exposure of this product to heat, flame, or electric arcs can generate toxic and corrosive vapors. Store container in dry area at temperatures between 40°F (4°C) and 120° F (49°C).

CAS Numbers: Petroleum Oil 64742-53-6; 2-Butanol 78-92-2; Cresol 1319-77-3; Cyclohexanone 108-94-1.

**KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY NOT FOR HOUSEHOLD USE OR RESALE**

FOR ADDITIONAL INFORMATION REFERENCE THE PRODUCT SAFETY DATA SHEET (SDS).

An Exclusive Product of:
PRO CHEM, INC.
1475 Bluegrass Lakes Parkway
Alpharetta, Georgia 30004
1-800-241-8180
www.procheminc.com

**MADE
IN
U.S.A.**

#2929

