

# FLEXI COAT #1453

Aerosol Undercoat, Sound Deadener, Roof Patch & Leak Sealer



## Features:

- Will not crack or peel
- Prevents rust and corrosion
- Seals out road salt
- Seals out water
- Seals tree pruning wounds
- Seals leaks in roofs, gutters, condenser pans and sinks
- No ozone depleting compounds
- 1 year+ shelf life

## Description:

FLEXI COAT is an undercoat and sound deadener that provides a durable, flexible, rubberized film that seals and acoustically reduces unwanted vibration and sound. It protects metal parts against the harmful effects of water, salt and road chemicals. This product stays pliable in the cold of winter, yet will not sag, melt or drip in summer heat. It resists cracking, peeling and abrasion. This product can also be used as an effective roof patch and leak sealer. It can be used on all roofs, flashings, gutters, downspouts and also on sink drains. It leaves a flexible coating that will not freeze or crack, is abrasion-resistant and won't peel. FLEXI COAT seals out rust and corrosion.



## Applications:

- Auto Underbodies
- Equipment
- Boats
- Roofs
- Air Conditioning Pans
- Ducts and Piping
- Stainless Steel Sinks
- Electrical Junction Boxes
- Flashings
- Gutters
- Leak Repairs
- Overlapping Seams

## For Use By:

- Parks & Recreation
- Municipalities
- Bus Fleets
- Marinas
- DOT
- Water & Sewer Treatment Plants

## Product Characteristics:

Appearance:	Black liquid
Odor:	Petroleum
Boiling Point/Range:	125.32°F (51.84°C) estimated
Vapor Pressure:	60 psig @70°F estimated
Specific Gravity:	0.865 estimated
Heat of Combustion (NFPA 30B):	22.22 kJ/g estimated
Flash Point:	-156.0°F (-104.4°C) Propellant estimated
Flammability Limit-lower:	1.3% estimated
Flammability Limit-upper:	8.2% estimated
VOC (Weight %):	39.3% estimated
Viscosity:	Not available
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Transport Information:</b>	
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1 L capacity)
UN Number:	UN1950
Class:	2.1
Packing Group:	Not applicable

## Directions:

Shake can vigorously until ball rattles freely for one minute. Shake occasionally during use. Hold cans 12 inches from surface. Spray a thin, even coat, building up desired thickness. Remove overspray with a cloth dampened with kerosene. Note: To prevent clogging of tip, turn can upside down and depress tip for 2 seconds. Wipe tip clean.

*\*Do not apply to hot equipment. Does contain flammable solvents and will run if applied to surfaces with temperatures above 300°F.*

## Pictograms:



## Signal Word:

DANGER

## Personal Protective Equipment Required:



## DOT Placard:



## VOC Compliant:

Yes.