SAFETY DATA SHEET

1. Product and Company Identification

 PRODUCT NUMBER:
 2408
 COMPANY PHONE:
 1-800-241-8180

PRODUCT NAME: LOCK DOWN EMERGENCY TELEPHONE: 1-800-535-5053

PRODUCT DESCRIPTION: Urinal & Drain Treatment INFOTRAC: 1-800-535-5053

COMPANY INFORMATION: PRO CHEM, INC.

1475 Bluegrass Lakes Parkway

Alpharetta, GA 30004

2. Hazards Identification

GHS CLASSIFICATION: ACUTE TOXICITY - DERMAL - Category 4 ACUTE

TOXICITY - DERMAL - Category 4 AT

DAMAGE/IRRITATION - Category 2A

SIGNAL WORD: SYMBOL:

Warning.



HAZARD STATEMENTS:

Causes serious eye irritation Harmful if swallowed. Harmful in contact with skin.

PRECAUTIONARY STATEMENTS:

Prevention: Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Wear protective gloves/protective clothing.

Response: Call a poison center/doctor/if you feel unwell. If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water/ Rinse mouth. Specific treatment (See on this label).

Storage: Not available.

Disposal: Dispose of contents/container in accordance with local/regional/international regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

No data available.

Ingredients of unknown toxicity:

0%

3. Composition / Information on Ingredients				
Chemical Name	CAS	Concentration % by Weight		
Soybean oil, Me ester	67784-80-9	90 %		
Occupational exposure limits, if available, are listed in Section 8.				

4. First Aid Measures

EMERGENCY OVERVIEW

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes

examined and tested by medical personnel.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing

before reuse.

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

INGESTION:

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Not available.

SPECIFIC FIRE-FIGHTING METHODS:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

LARGE SPILLS:

Stop leak at source and collect into suitable container, then treat as a small spill.

SMALL SPILLS:

Absorb with an inert solid and scoop up for disposal, then rinse soiled area with water.

7. Handling and Storage

SAFE HANDLING:

Use spark-proof tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Use only in a well-ventilated area. Follow all SDS/label precautions even after container is emptied because they may retain product residues.

SAFE STORAGE & INCOMPATIBILITIES:

Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition. Keep away from food and drinking water. Keep container closed when not in use.

Product Name: LOCK DOWN
Product Number: 2408
Revision Date: 10/9/2018
Pro Chem, Inc.
Page 1 of 3

8. Exposure Controls / Personal Protection

OCCUPATIONAL EXPOSURE LIMITS

 Ingredient Name
 ACGIH TLV
 OSHA PEL
 STEL

 Soybean oil, Me ester
 Not available.
 Not available.
 Not available.

PERSONAL PROTECTIVE EQUIPMENT: Goggles, Gloves, Face Shield



Eye/Face Protection: Chemical Splash goggle in compliance with OSHA regulations are advised: however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection: Wear rubber gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection: If workplace exposure limits of product or any component are exceeded (see exposure guidelines) NIOSH/OSHA approved air supplied respirator is advised in the absence of proper environmental control. OSHA relations also permit other NIOSH/OSHA respirators (negative pressure type) under specific conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

APPROPRIATE ENGINEERING CONTROLS:

Provide sufficient mechanical (general and local exhaust) ventilation to maintain exposure below level of overexposure (from known, suspected or apparent adverse effects).

9. Physical & Chemical Properties				
Physical State:	Liquid.	Flammability(solid/gas):	Not available.	
Color:	Green/clear.	LEL:	Not available.	
Odor:	Cucumber Melon.	UEL:	Not available.	
Odor Threshold:	Not available.	Vapor Density:	Not available.	
pH:	Not available.	Vapor Pressure:	Not available.	
Melting Point:	575°F	Solubility (water):	Not available.	
Boiling Point/Range:	Not available.	Auto-Ignition Temp:	Not available.	
Viscosity:	Not available.	Decomposition Temp:	Not available.	
Flash Point:	Not available.	Partition Coeff(n-octanol/water):	Not available.	
Specific Gravity:	0.91	VOC%:	Not available.	
Evaporation Rate:	Not available.	Pounds per Cubic Foot:	Not available.	
Density lbs/Gal:	Not available.	FP Method:	Not available.	

10. Stability & Reactivity Information

CHEMICAL STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

CONDITIONS TO AVOID:

Temperature Extremes.

INCOMPATIBLE MATERIALS:

Chlorine Bleach, Oxidizers, Acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will not occur.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY: Skin contact /absorption and inhalation.

Eyes: Exposure may cause noticeable pain and severe irritation.

Skin: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking and skin burns. Additional symptoms of skin contact may include: allergic reaction. Skin absorption is possible, but harmful effects are not expected from this route of exposure under normal handling and use.

Inhalation: Exposure to vapor or mist is possible. Short term inhalation is not likely to cause harmful effects: breathing large amounts may be harmful. Symptoms are more typically seen at air concentrations exceeding the recommended exposure limits.

Ingestion: Single dose oral toxicity is low. Swallowing small amounts during normal handling is not likely to cause harmful effects: swallowing large amounts may be harmful.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

Gastrointestinal irritation (nausea, vomiting, diarrhea), irritation to nose, throat and respiratory tract.

TARGET ORGAN EFFECTS:

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals and may aggravate pre-existing disorders or these organs in humans: chronic ingestion may cause kidney and liver lesions at high doses.

CARCINOGENICITY:

This material is not listed as a carcinogen by IARC, NTP or OSHA.

REPRODUCTIVE TOXICITY:

No data

CHRONIC EFFECTS:

No data

12. Ecological Information

No data available.

Product Name: LOCK DOWN
Product Number: 2408
Revision Date: 10/9/2018
Product Number: 2408
Product Number: 2408
Product Number: 2408

13. Disposal Consideration

DISPOSAL INSTRUCTIONS:

For proper disposal of waste, refer to federal and state regulations.

14. Transportation Information

DOT: UN Number: Not available.

UN Proper Shipping Name: Not available. **Transport Hazard Class(es):** Nonhazardous.

Packing Group: Not applicable.

15. Regulatory Information

US FEDERAL REGULATIONS:

TSCA (Toxic Substances Control Act) Status

TSCA (United States) The intentional ingredients of this product are listed. CERCLA RQ - 40 CFR 355 Appendix A: None

SARA 302 Components 40 CFR Appendix A: None Section 311/312 Hazard Class 40 CFR 370.2

Hazard categories:

Immediate Hazard – Yes. Delayed Hazard – Yes. Fire Hazard – Yes. Pressure Hazard – No. Reactivity Hazard – No.

SARA 313 Components - 40 CFR 372.65

US STATE REGULATIONS:

California Proposition 65: None

California SCAQMD Rule 443.1 VOC's: < 100g/L

North Carolina Administrative Code 2D.1104 and 2B.0610: None

South Carolina Regulation 62.5 Standard Number 8: None

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.

Product Name: LOCK DOWN
Product Number: 2408
Revision Date: 10/9/2018
Pro Chem, Inc.
Page 3 of 3