



SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1732	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	LONG LIFE	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	Aerosol Cutting & Tapping Fluid	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION:
Flammable aerosols: Category 1
Serious eye damage/eye irritation: Category 2A
Specific target organ toxicity, single exposure: Category 3 narcotic effects
OSHA defined hazards: Not classified.

SIGNAL WORD:
DANGER

SYMBOL:



HAZARD STATEMENTS:

Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS:

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye protection/face protection.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Acetone	67-64-1	40-60
Butane	106-97-8	10-20
Propane	74-98-6	2.5-10
Other components below reportable levels		20-40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

INHALATION:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

INGESTION:

In the unlikely event of swallowing, contact a physician or poison control center. Rinse mouth.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Powder. Alcohol resistant foam. Carbon dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

SPECIFIC FIRE-FIGHTING METHODS:

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

EXTREMELY FLAMMABLE AEROSOL.

6. Accidental Release Measures**PERSONAL PRECAUTIONS:**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP METHODS:

Avoid discharge into drains, watercourses or onto the ground. Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see Section 13 of the SDS.

7. Handling and Storage**SAFE HANDLING:**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not reuse empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge, which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

COMPONENTS	TYPE	VALUE
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

COMPONENTS	TYPE	VALUE
Acetone (CAS 67-64-1)	TWA	590 mg/m ³ 250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m ³ 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m ³ 1000 ppm

BIOLOGICAL LIMIT VALUE:**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Wear safety glasses with side shields (or goggles).

SKIN PROTECTION: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Wear suitable

protective clothing.

RESPIRATORY PROTECTION: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

THERMAL HAZARDS: Wear appropriate thermal protective clothing, when necessary.

GENERAL HYGIENE CONSIDERATIONS: When using, do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance:		Flammability(solid/gas):	Not available.
Physical State:	Gas.	Flammability Limit–lower (%):	2.6 % estimated
Form:	Aerosol.	Flammability Limit–upper (%):	12.8 % estimated
Color:	Not available.	Explosive Limit – lower (%):	Not available.
Odor:	Not available.	Explosive Limit – upper (%):	Not available.
Odor Threshold:	Not available.	Vapor Pressure:	238.12 psig @70°F estimated
pH:	Not available.	Vapor Density:	Not available.
Melting/Freezing Point:	Not available.	Relative Density:	Not available.
Initial Boiling Point/Range:	132.89°F (56.05°C) estimated	Solubility (water):	Not available.
Partition Coeff (n-octanol/water):	Not available.	Auto-Ignition Temperature:	Not available.
Viscosity:	Not available.	Decomposition Temperature:	Not available.
Specific Gravity:	0.031 estimated	Evaporation Rate:	Not available.
Flash Point:	-156.0°F (-104.4°C) Propellant estimated	Flame Extension:	48 in
Explosive Properties:	Not explosive.	Oxidizing Properties:	Not oxidizing.

10. Stability & Reactivity Information

REACTIVITY:

The product is stable and non-reactive under normal conditions of use, storage and transport.

CHEMICAL STABILITY:

Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

CONDITIONS TO AVOID:

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

EYES: Causes serious eye irritation.

SKIN: No adverse effects due to skin contact are expected.

INHALATION: May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

INGESTION: Expected to be a low ingestion hazard.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

ACUTE TOXICITY:

Narcotic effects.

COMPONENTS	SPECIES	TEST RESULTS
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
	Rabbit	> 9.4 ml/kg, 24 Hours
		> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
COMPONENTS	SPECIES	TEST RESULTS
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
<i>Oral</i>		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52%, 120 Minutes
		1355 mg/l

Propane (CAS 74-98-6)

Acute

Inhalation
LC50

Mouse

1237 mg/l, 120 Minutes

52%, 120 Minutes

Rat

1355 mg/l

658 mg/l/4 h

* Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Prolonged skin contact may cause temporary irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Causes serious eye irritation.

RESPIRATORY SENSITIZATION:

Not a respiratory sensitizer.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

CARCINOGENICITY:

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens: Not available.

REPRODUCTIVE TOXICITY:

This product is not expected to cause reproductive or developmental effects.

SPECIFIC TARGET ORGAN TOXICITY (single exposure):

May cause drowsiness and dizziness.

SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):

Not classified.

ASPIRATION HAZARD:

Not likely, due to the form of the product.

CHRONIC EFFECTS:

Prolonged inhalation may be harmful.

12. Ecological Information

ECOTOXICITY:

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

PRODUCT	SPECIES		TEST RESULTS
LONG LIFE			
Aquatic			
Crustacea	EC50	Daphnia	22251.1855 mg/l, 48 hours estimated
Fish	LC50	Fish	1096.5597 mg/l, 96 hours estimated
COMPONENTS	SPECIES		TEST RESULTS
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24

Butane 2.89

Propane 2.36

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration

DISPOSAL INSTRUCTIONS:

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

CONTAMINATED PACKAGING:

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transportation Information

DOT: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable.
TRANSPORT HAZARD CLASS(ES)
 Class: 2.1
 Subsidiary Risk: --
 Label(s): 2.1



PACKING GROUP: Not applicable.
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.
SPECIAL PROVISIONS: N82
PACKAGING EXCEPTIONS: 306
PACKAGING NON BULK: None
PACKAGING BULK: None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable.
TRANSPORT HAZARD CLASS(ES)
 Class: 2.1
 Subsidiary Risk: --
 Label(s): 2.1



PACKING GROUP: Not applicable.
ENVIRONMENTAL HAZARDS: No.
ERG CODE: 10L
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.
OTHER INFORMATION:

PASSENGER AND CARGO AIRCRAFT: Allowed with restrictions.
CARGO AIRCRAFT ONLY: Allowed with restrictions.
PACKAGING EXCEPTIONS: LTD QTY

IMDG: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: AEROSOLS
TRANSPORT HAZARD CLASS(ES)
 Class: 2.1
 Subsidiary Risk: --
 Label(s): 2.1



PACKING GROUP: Not applicable.
ENVIRONMENTAL HAZARDS:
Marine pollutant: No.
EmS: Not available.
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.
PACKAGING EXCEPTIONS: LTD QTY

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:
 Not applicable.

15. Regulatory Information**US FEDERAL REGULATIONS:**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4): Acetone (CAS 67-64-1) Listed.
SARA 304 Emergency release notification: Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

Hazard categories:
 Immediate Hazard – Yes.
 Delayed Hazard – No.
 Fire Hazard – Yes.
 Pressure Hazard – No.
 Reactivity Hazard – No.

SARA 302 Extremely hazardous substance: Not listed.
SARA 311/312 Hazardous chemical: No.

SARA 313 (TRI reporting):

OTHER FEDERAL REGULATIONS:

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)
 Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number
 Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US STATE REGULATIONS:**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100):** Not listed.**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)):**

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1) Listed: January 1, 1988

Ethylene Oxide (CAS 75-21-8) Listed: July 1, 1987

Propylene Oxide (CAS 75-56-9) Listed: October 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene Oxide (CAS 75-21-8) Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene Oxide (CAS 75-21-8) Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene Oxide (CAS 75-21-8) Listed: August 7, 2009

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information**DISCLAIMER:**

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.