

1. Product and Company Identification

 PRODUCT NUMBER:
 1733
 COMPANY PHONE:
 1-800-241-8180

PRODUCT NAME: LIKE NU EMERGENCY TELEPHONE: 1-800-241-8180

PRODUCT DESCRIPTION: Aerosol Acoustical Ceiling Tile Restorer INFOTRAC: 1-800-535-5053

COMPANY INFORMATION: PRO CHEM, INC.

1475 Bluegrass Lakes Parkway

Alpharetta, GA 30004

2. Hazards Identification GHS CLASSIFICATION:

Flammable aerosols: Category 1 Serious eye damage/eye irritation: Category 2A Reproductive toxicity (the unborn child): Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated exposure:

Category 2

OSHA defined hazards: Not classified.

SIGNAL WORD: SYMBOL: DANGER







HAZARD STATEMENTS:

Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF EXPOSED OR CONCERNED: Get medical advice/attention. Call a poison center/doctor if you feel unwell. IF EYE IRRITATION OCCURS: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

ENVIRONMENTAL HAZARDS:

Hazardous to the aquatic environment, acute hazard: Category 3

Hazardous to the aquatic environment, long-term hazard: Category 3

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients		
Chemical Name	CAS	Concentration % by Weight
Butane	106-97-8	20-40
Acetone	67-64-1	10-20
Ethyl Alcohol	64-17-5	10-20
Isopropyl Alcohol	67-63-0	10-20
Magnesium Silicate	14807-96-6	10-20
Propane	74-98-6	2.5-10
Titanium dioxide	13463-67-7	2.5-10
Toluene	108-88-3	2.5-10
Other components below reportable levels		10-20
*Designates that a specific chemical identity and/or percentage of	composition has been withheld as a trade se	ecret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: IF EXPOSED OR CONCERNED: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell

INGESTION: In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Product Name: LIKE NU
Product Number: 1733
Revision Date: 3/26/2018
Pro Chem Inc
Page 1 of 8

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision. Prolonged exposure may cause chronic effects.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Alcohol resistant foam. Powder. Carbon dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

SPECIFIC FIRE-FIGHTING METHODS:

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

MATERIALS AND METHODS FOR CLEANUP:

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

ENVIRONMENTAL PRECAUTIONS:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

SAFE HANDLING:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not reuse empty containers. Do not breathe gas. Avoid contact with eyes. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection			
Occupational exposure limits US. OSHA Table Z-1 Limits for Air Contaminants (20 CEP 1010 1000\		
COMPONENTS	TYPE	VALUE	FORM
Acetone (CAS 67-64-1)	PEL	2400 mg/m³ 1000 ppm	
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m³ 1000 ppm	
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m³ 400 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m³ 1000 ppm	
Titanium dioxide (CAS 13463-67-7) US. OSHA Table Z-2 (29 CFR1910.1000)	PEL	15 mg/m³	Total dust.
COMPONENTS	TYPE	VALUE	FORM
Toluene (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm	

Product Name: LIKE NU
Product Number: 1733
Revision Date: 3/26/2018
Pro Chem Inc
Page 2 of 8

otal dust.
Respirable.
Respirable.
ble fraction.
ble.
DIE.

BIOLOGICAL LIMIT VALUE:

ACGIH Biological Exposure Indices:

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in Urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

^{* -} For sampling details, please see the source document.

EXPOSURE GUIDELINES:

US - California OELs: Skin designation:

Toluene (CAS 108-88-3): Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies:

Toluene (CAS 108-88-3): Skin designation applies.

APPROPRIATE ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

100 ppm

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:



Eye Protection: Wear safety glasses with side shields (or goggles).

Skin Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Product Name: LIKE NU
Product Number: 1733
Revision Date: 3/26/2018
Pro Chem Inc
Page 3 of 8

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Proper	ties		
Physical State:	Gas.	Flammability (solid/gas):	Not available.
Form:	Aerosol.	Flammability Limit-lower (%)	2.9 % estimated.
Color:	Not available.	Flammability Limit-upper (%):	11.3 % estimated.
Odor:	Not available.	Explosive Limit – lower (%):	Not available.
Odor Threshold:	Not available.	Explosive Limit – upper (%):	Not available.
pH:	Not available.	Vapor Pressure:	45 - 65 psig @70°F estimated.
Melting/Freezing Point:	Not available.	Vapor Density:	Not available.
Initial Boiling Point/Range:	179.66 °F (82.04 °C) estimated.	Relative Density:	Not available.
Partition Coeff (n-octanol/water	r): Not available.	Solubility (water):	Not available.
Viscosity:	Not available.	Auto-Ignition Temperature:	748.4 °F (398 °C) estimated.
Specific Gravity:	0.877 estimated.	Decomposition Temperature:	Not available.
Flash Point: -156.0) °F (-104.4 °C) Propellant estimated.	Evaporation Rate:	Not available.
Explosive Properties:	Not explosive.	Oxidizing Properties:	Not oxidizing.

10. Stability & Reactivity Information

REACTIVITY:

The product is stable and nonreactive under normal conditions of use, storage and transport.

CHEMICAL STABILITY:

Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

INCOMPATIBLE MATERIALS:

Acids. Strong oxidizing agents. Nitrates. Isocyanates. Fluorine. Chlorine.

CONDITIONS TO AVOID:

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

Eyes: Causes serious eye irritation.

Skin: No adverse effects due to skin contact are expected.

Inhalation: May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness.

TEST DESILITE

Headache. Nausea, vomiting.

Ingestion: Expected to be a low ingestion hazard.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

CDECIEC

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision.

ACUTE TOXICITY: Narcotic effects

COMPONENTS	SPECIES	TEST RESULTS
Acetone (CAS 67-64-1)		
Acute Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
Inhalation		G.
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
Oral		3
LD50	Rat	5800 mg/kg 2.2 ml/kg
Butane (CAS 106-97-8)		
Acute Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes 52%, 120 Minutes
	Rat	1355 mg/l

Product Name: LIKE NU
Product Number: 1733
Revision Date: 3/26/2018
Pro Chem Inc
Page 4 of 8

Ethyl Alcohol (CAS 64-17-5)		
Acute		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
Oral		3 ,
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Pig	> 5000 mg/kg
	Rat	10470 mg/kg
	rtat	7800 ml/kg
Isopropyl Alcohol (CAS 67-63-0)		7 000 mi/kg
Acute		
Dermal		
LD50	Rabbit	16.4 ml/kg, 24 Hours
Inhalation	Nabbit	10.4 III/kg, 24 Hours
LC50	Rat	>10000 ppm, 6 Hours
Oral	Ital	>10000 ppin, 0 Hours
LD50	Rat	E 94 a/ka
Propane (CAS 74-98-6)	Nai	5.84 g/kg
Acute		
Inhalation		
LC50	Mouse	1007 mg/L 100 Minutes
LC50	Mouse	1237 mg/l, 120 Minutes
	Dot	52%, 120 Minutes
	Rat	1355 mg/l
Titonium dioxido (CAC 12462 67.7)		658 mg/l/4h
Titanium dioxide (CAS 13463-67-7) Acute		
Acute		
Inhalation		
LC50	Rat	> 2.28 mg/l, 4 Hours
Oral	r\al	~ 2.20 mg/i, 4 mours
LD50	Mouse	> 5000 ma/ka
LDSU	Rat	> 5000 mg/kg > 2000 mg/kg
	Rai	> 2000 mg/kg
Taluana (CAS 108 88 3)		
Toluene (CAS 108-88-3) Acute		
Dermal	Dobbit	5000 mg/kg 24 Hours
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation	Maria	C405 7400 mmm C11a
LC50	Mouse	6405 - 7436 ppm, 6 Hours
	Б.	5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours
0 1		25.7 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
*Estimates for product may be based of	on additional co	mponent data not shown.

Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Prolonged skin contact may cause temporary irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Causes serious eye irritation.

RESPIRATORY SENSITIZATION:

Not a respiratory sensitizer.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

CARCINOGENICITY:

Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity:

Magnesium Silicate (CAS 14807-96-6): 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7): 2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3): 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens: Not listed.

REPRODUCTIVE TOXICITY:

Suspected of damaging the unborn child.

SPECIFIC TARGET ORGAN TOXICITY (single exposure):

May cause drowsiness and dizziness.

Product Name: LIKE NU Pro Chem Inc Product Number: 1733 Revision Date: 3/26/2018 Page 5 of 8

SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):

Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.

ASPIRATION HAZARD:

Not likely, due to the form of the product.

CHRONIC EFFECTS:

May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecologic	al Information
ECOTOXICI7	TY: Harmful to a

XICITY: Harmful to aquatic life with long	g lasting ef		
COMPONENTS		SPECIES	TEST RESULTS
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Ethyl Alcohol (CAS 64-17-5)			_
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100.1 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)		, , ,	G .
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	>1400 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)		,	3 .
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
Toluene (CAS 108-88-3)		, , , , , , , , , , , , , , , , , , , ,	3,
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
2.22.2004		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
			J .,

Coho salmon, silver salmon (Oncorhynchus kisutch)

8.11 mg/l, 96 hours

LC50

PERSISTENCE AND DEGRADABILITY:

Fish

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Butane	2.89
Ethyl Alcohol	-0.31
Isopropyl Alcohol	0.05
Propane	2.36
Toluene	2.73

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration

DISPOSAL INSTRUCTIONS:

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (See: Disposal instructions).

CONTAMINATED PACKAGING:

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste-handling site for recycling or disposal. Do not reuse empty containers.

14. Transportation Information

DOT: UN Number: UN1950

UN Proper Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)

Transport Hazard Class(es)
Class: 2.1
Subsidiary Risk: Label(s): 2.1

Packing Group: Not applicable.



Product Name: LIKE NU
Product Number: 1733
Revision Date: 3/26/2018
Pro Chem Inc
Page 6 of 8

^{*} Estimates for product may be based on additional component data not shown.

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and

emergency procedures before handling.

Special Provisions: N82 Packaging Exceptions: 306 Packaging Nonbulk: None. Packaging Bulk: None.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D"

marking.

IATA: UN Number: UN1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es) Class: 2.1 Subsidiary Risk: -**Label(s):** 2.1

Packing Group: Not applicable. Environmental Hazards: No.

ERG Code: 10L

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Other Information:

Passenger and Cargo Aircraft: Allowed with restrictions.

Cargo Aircraft Only: Allowed with restrictions.

Packaging Exceptions: LTD QTY

IMDG: UN NUMBER: UN1950

UN Proper Shipping Name: AEROSOLS

Transport Hazard Class(es) **Class: 2.1** Subsidiary Risk: -Label(s): 2.1

Packing Group: Not applicable. **Environmental Hazards:** Marine pollutant: No.

EmS: F-D, S-U

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions: LTD QTY

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE: Not applicable

15. Regulatory Information

US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4):

Acetone (CAS 67-64-1) Listed. Toluene (CAS 108-88-3) Listed.

SARA 304 Emergency Release Notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

Immediate Hazard - Yes. Hazard categories: Delayed Hazard - Yes.

Fire Hazard - Yes. Pressure Hazard - Yes. Reactivity Hazard - No.

SARA 302 Extremely Hazardous Substance: Not listed.

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting):

Chemical Name CAS Number % by Weight Toluene 108-88-3 2.5-10

OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) Toluene (CAS 108-88-3)

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)):

Acetone (CAS 67-64-1) 35% WV Toluene (CAS 108-88-3) 35% WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532 Toluene (CAS 108-88-3) 594

Product Name: LIKE NU Pro Chem Inc Product Number: 1733 Revision Date: 3/26/2018 Page 7 of 8

US STATE REGULATIONS

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed. US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)):

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0) Magnesium Silicate (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7) Toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List:

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Isopropyl Alcohol (CAS 67-63-0) Magnesium Silicate (CAS 14807-96-6) Propane (CAS 74-98-6) Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Isopropyl Alcohol (CAS 67-63-0) Magnesium Silicate (CAS 14807-96-6) Propane (CAS 74-98-6) Titanium dioxide (CAS 13463-67-7) Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17-5) Isopropyl Alcohol (CAS 67-63-0) Magnesium Silicate (CAS 14807-96-6) Propane (CAS 74-98-6) Titanium dioxide (CAS 13463-67-7) Toluene (CAS 108-88-3)

US. Rhode Island RTK

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 67-63-0) Propane (CAS 74-98-6) Toluene (CAS 108-88-3)

US. California Proposition 65:

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011 US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

INTERNATIONAL INVESNTORIES:

Inventory name On inventory (yes/no)* Country(s) or region Australia Australian Inventory of Chemical Substances (AICS) Nο Canada Domestic Substances List (DSL) Yes Non-Domestic Substances List (NDSL) Canada No Inventory of Existing Chemical Substances in China (IECSC) China No European Inventory of Existing Commercial Chemical Substances (EINECS) Europe No European List of Notified Chemical Substances (ELINCS) Europe No Japan Inventory of Existing and New Chemical Substances (ENCS) No Existing Chemicals List (ECL) Korea No New Zealand New Zealand Inventory No Philippine Inventory of Chemicals and Chemical Substances (PICCS) **Philippines** No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.

Product Name: LIKE NU Pro Chem Inc Product Number: 1733 Revision Date: 3/26/2018 Page 8 of 8