

# LUB-ALL #1738

## Aerosol Gel Penetrating Lubricant with PTFE



### Features:

- Allows maximum penetration and rapid set up of the grease-like lubricant
- Helps prevent rust and corrosion
- Lasts longer than conventional lubricants
- Will withstand temperatures of -30°F to over 600°F
- Resists water washout
- Contains no CFC's

### Description:

LUB-ALL is a transparent, high pressure lubricant with high adhesive strength. It adheres to surfaces and resists throw-off and squeeze out when subjected to high pressures, vibrations, or repeated impact. A unique combination of natural and synthetic lubrication agents coupled with PTFE makes LUB-ALL one of the best aerosol lubricants available.



### Applications:

- Wire Ropes
- Chains
- Sprockets
- Door Hinges
- Open Gears
- Legs on Hoists
- Cables
- Conveyors

### Product Characteristics:

Appearance:	Clear spray/mist
Odor:	Hexane
Boiling Point:	Not available
Vapor Pressure:	Not available
Specific Gravity:	0.77
Water Solubility:	Insoluble
Vapor Density:	Not available
Flash Point:	<0°F. (liquid proportion)
pH:	Not applicable
VOC:	50
Boiling Range:	Not available
Viscosity:	Not available
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up.
<b>Transport Information:</b>	
Proper Shipping Name:	Aerosols, flammable
UN Number:	1950
Class:	2.1

### Directions:

1. Shake well.
2. Saturate area to be lubricated. LUB-ALL
3. If necessary, repeat application.

*Caution: Not to be used near heat, sparks or open flame.*

### Pictograms:



### Signal Word:

DANGER

### Personal Protective Equipment Required:



### DOT Placard:

