



SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1215	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	MAGIC	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	High Foaming, Heavy-Duty Aerosol Cleaner	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Flammable aerosols Category 1 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Environmental hazards: Not classified. OSHA defined hazards: Not classified.	SIGNAL WORD: DANGER	SYMBOL:	
---	-------------------------------	----------------	--

HAZARD STATEMENTS:

Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation.

PRECAUTIONARY STATEMENTS:

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves. Wear eye/face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Not available.

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Butane	106-97-8	2.5-10
Disodium Metasilicate	6834-92-0	1-2.5
Polyethylene Glycol Octylphenyl Ether	9036-19-5	1-2.5
Propane	74-98-6	1-2.5
Trisodium Phosphate	10101-89-0	1-2.5
2-Butoxyethanol	111-76-2	0.1-1
Other components below reportable levels		80-90

#: This substance has workplace exposure limit(s).
*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: Immediate medical attention is required. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

EYES: Call a physician or Poison Control Center immediately.

SKIN: Call a physician or Poison Control Center immediately.

INHALATION:

If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is greater than the TLV or health effects are noticed), immediately remove the affected person(s) to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.

INGESTION:

Rinse mouth. Get medical attention if symptoms occur.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Not available.

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use a solid water stream as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

SPECIFIC FIRE-FIGHTING METHODS:

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP METHODS:

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak, if you can do so without risk. Move the cylinder to a safe and open area, if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Use a non-combustible material like vermiculite, sand, or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements, or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see Section 13 of the SDS. Do not contaminate water. Avoid discharge into drains, watercourses or onto the ground.

7. Handling and Storage

SAFE HANDLING:

Will ignite if exposed to intensive heat or open air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not reuse empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not get this material on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate, or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B).

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
2-Butoxyethanol (CAS 11-76-2)	PEL	240 mg/m ³ 50 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
2-Butoxyethanol (CAS 11-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

COMPONENTS	TYPE	VALUE
2-Butoxyethanol (CAS 11-76-2)	TWA	24 mg/m ³ 5 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m ³ 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m ³ 1000 ppm

BIOLOGICAL LIMIT VALUE:

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 11-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

EXPOSURE GUIDELINES:**US - California OELs: Skin designation**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2)

Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eyewash facilities and emergency shower must be available when handling this product.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Wear tight-fitting goggles or face shield. Face shield is recommended. Wear safety glasses with side shields (or goggles).

SKIN PROTECTION: Wear appropriate chemical resistant gloves. Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended. It may provide little or no thermal protection.

RESPIRATORY PROTECTION: If permissible levels are exceeded, use NIOSH mechanical filter/organic vapor cartridge or an air-supplied respirator.

THERMAL HAZARDS: Wear appropriate thermal protective clothing, when necessary.

GENERAL HYGIENE CONSIDERATIONS: When using, do not eat, drink, or smoke. Do not get in eyes. Do not get this material in contact with skin. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance:		Flammability(solid/gas):	Not available.
Physical State:	Gas.	Flammability Limit-lower(%):	Not available.
Form:	Aerosol.	Flammability Limit-upper (%):	Not available.
Color:	Not available.	Explosive Limit – lower (%):	Not available.
Odor:	Not available.	Explosive Limit – upper (%):	Not available.
Odor Threshold:	Not available.	Vapor Pressure:	60 psig @70°F estimated
pH:	Not available.	Vapor Density:	Not available.
Melting/Freezing Point:	Not available.	Relative Density:	Not available.
Initial Boiling Point/Range:	212°F (100°C) estimated	Solubility (water):	Not available.
Viscosity:	Not available.	Auto-Ignition Temperature:	Not available.
Evaporation Rate:	Not available.	Decomposition Temperature:	Not available.
Partition Coeff(n-octanol/water):	Not available.	Flash Point:	-156.0°F (-104.4°C) Propellant estimated
Specific Gravity:	0.98 estimated		

10. Stability & Reactivity Information**REACTIVITY:**

The product is stable and non-reactive under normal conditions of use, storage, and transport.

CHEMICAL STABILITY:

Risk of ignition.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

INCOMPATIBLE MATERIALS:

Nitrates. Oxygen. Fluorine. Chlorine.

CONDITIONS TO AVOID:

Exposure to air. Heat, flames, and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information**PRIMARY ROUTE OF ENTRY:**

EYES: Causes serious eye irritation.

SKIN: Causes skin irritation.

INHALATION: Prolonged inhalation may be harmful.

INGESTION: Expected to be a low ingestion hazard.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

ACUTE TOXICITY:		
COMPONENTS	SPECIES	TEST RESULTS
2-Butoxyethanol (CAS 111-76-2)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	230 ml/kg, 24 Hours
	Rabbit	7.3 ml/kg, 4 Days
		450 ml/kg, 24 Hours
		435 mg/kg, 24 Hours
		0.63 ml/kg
		> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
<i>Oral</i>		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1200 mg/kg
	Rat	530 - 2800 mg/kg
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Disodium Metasilicate (CAS 6834-92-0)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 5000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 2.06 mg/l, 4 Hours
<i>Oral</i>		
LD50	Mouse	661.5 - 896.3 mg/kg
	Rat	600 mg/kg
Polyethylene Glycol Octylphenyl Ether (CAS 9036-19-5)		
Acute		
<i>Oral</i>		
LD50	Rat	4190 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Trisodium Orthophosphate (CAS Mixture)		
Acute		
<i>Oral</i>		
LD50	Rat	7400 mg/kg
* Estimates for product may be based on additional component data not shown.		
SKIN CORROSION/IRRITATION:		
Causes skin irritation. Prolonged skin contact may cause temporary irritation.		
SERIOUS EYE DAMAGE/IRRITATION:		
Harmful in contact with eyes. Causes serious eye irritation.		
RESPIRATORY SENSITIZATION:		
Not available.		
SKIN SENSITIZATION:		
This product is not expected to cause skin sensitization.		
GERM CELL MUTAGENICITY:		
No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
CARCINOGENICITY:		
This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
IARC Monographs. Overall Evaluation of Carcinogenicity		
2-Butoxyethanol (CAS 111-76-2)		3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
REPRODUCTIVE TOXICITY:		
This product is not expected to cause reproductive or developmental effects.		
SPECIFIC TARGET ORGAN TOXICITY (single exposure):		
Not classified.		
SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):		
Not classified.		
ASPIRATION HAZARD:		
Not likely, due to the form of the product.		

CHRONIC EFFECTS:

Prolonged inhalation may be harmful. Prolonged or repeated exposure may cause lung injury.

12. Ecological Information**ECOTOXICITY:**

Components of this product are hazardous to aquatic life.

PRODUCT	SPECIES	TEST RESULTS
MAGIC (CAS Mixture)		
Aquatic		
Fish	LC50	Fish
COMPONENTS	SPECIES	TEST RESULTS
2-Butoxyethanol (CAS 111-76-2)		
Aquatic		
Fish	LC50	Inland silverside (Menidia beryllina)
Polyethylene Glycol Octylphenyl Ether (CAS 9036-19-5)		
Aquatic		
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
* Estimates for product may be based on additional component data not shown.		7.2 mg/l, 96 hours
PERSISTENCE AND DEGRADABILITY:		
No data is available on the degradability of this product.		
BIOACCUMULATIVE POTENTIAL:		
No data available.		
Partition coefficient n-octanol / water (log Kow)		
2-Butoxyethanol		0.83
Butane		2.89
Propane		2.36
MOBILITY IN SOIL:		
No data available.		
OTHER ADVERSE EFFECTS:		
No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal Consideration**DISPOSAL INSTRUCTIONS:**

Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate, or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer, and the waste disposal company.

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

CONTAMINATED PACKAGING:

Empty containers should be taken to an approved waste-handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not reuse empty containers.

14. Transportation Information

DOT: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable, (each not exceeding 1 L capacity)
TRANSPORT HAZARD CLASS(ES)
Class: 2.1
Subsidiary Risk: -
Label(s): 2.1
PACKING GROUP: Not applicable.
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.
SPECIAL PROVISIONS: N82
PACKAGING EXCEPTIONS: 306
PACKAGING NON BULK: None.
PACKAGING BULK: None.



This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable
TRANSPORT HAZARD CLASS(ES)
Class: 2.1
Subsidiary Risk: -
Label(s): 2.1
PACKING GROUP: Not applicable.
ENVIRONMENTAL HAZARDS: No.



ERG CODE: 10L

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

OTHER INFORMATION:

PASSENGER AND CARGO AIRCRAFT: Allowed.

CARGO AIRCRAFT ONLY: Allowed.

PACKAGING EXCEPTIONS: LTD QTY

IMDG: UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS

TRANSPORT HAZARD CLASS(ES)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

PACKING GROUP: Not applicable.

ENVIRONMENTAL HAZARDS:

Marine pollutant: No.

EmS: F-D, S-U

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:

Not applicable.



15. Regulatory Information

US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Trisodium Phosphate (CAS 10101-89-0) Listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

Hazard categories Immediate Hazard – No.

Delayed Hazard – No.

Fire Hazard – Yes.

Pressure Hazard – No.

Reactivity Hazard – No.

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,4-Dioxane	123-91-1	0.01 - 0.1

OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

US STATE REGULATIONS

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Trisodium Phosphate (CAS 10101-89-0)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Trisodium Phosphate (CAS 10101-89-0)

US. Rhode Island RTK

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Trisodium Phosphate (CAS 10101-89-0)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-Dioxane (CAS 123-91-1)

Listed: January 1, 1988

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

N/A = Not Applicable; N/D = Not Determined

HMIS	Health Hazards: 2	Flammability: 2	Physical hazards: 0	Personal protection: X
-------------	-------------------	-----------------	---------------------	------------------------

DISCLAIMER:
To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.