



SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1221	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	MARK OUT	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	Aerosol Vandal Mark and Graffiti Remover	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Flammable aerosols: Category 1 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Reproductive toxicity Category 2 Specific target organ toxicity, single exposure Category 3 narcotic effects Specific target organ toxicity, repeated exposure: Category 2 Aspiration hazard Category 1 Environmental hazards: Not classified. OSHA defined hazards: Not classified.	SIGNAL WORD: DANGER	SYMBOL:	
---	-------------------------------	----------------	--

HAZARD STATEMENTS:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF SWALLOWED: Immediately call a poison center/doctor. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Toluene	108-88-3	40-60
Butane	106-97-8	10-20
Diacetone Alcohol	123-42-2	2.5-10
Isopropyl Alcohol	67-63-0	2.5-10
Propane	74-98-6	2.5-10
Other components below reportable levels		10-20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

EYES: Rinse with water. Get medical attention if irritation develops and persists.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists. Take off contaminated clothing and wash before reuse.

INHALATION:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

INGESTION:

In the unlikely event of swallowing, contact a physician or poison control center. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause

redness and pain. Prolonged exposure may cause chronic effects.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Powder. Foam. Carbon dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

SPECIFIC FIRE-FIGHTING METHODS:

Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP METHODS:

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak, if you can do so without risk. Move the cylinder to a safe and open area, if the leak is irreparable. Isolate area until gas has dispersed. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements, or confined areas. For waste disposal, see Section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage, if safe to do so. Avoid discharge into drains, watercourses or onto the ground.

7. Handling and Storage

SAFE HANDLING:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin, eyes, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate, or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in original tightly closed container. Refrigeration recommended. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
Diacetone Alcohol (CAS 123-42-2)	PEL	240 mg/m ³ 50 ppm
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m ³ 400 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
Butane (CAS 106-97-8)	STEL	1000 ppm
Diacetone Alcohol (CAS 123-42-2)	TWA	50 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

COMPONENTS	TYPE	VALUE
Butane (CAS 106-97-8)	TWA	1900 mg/m ³ 800 ppm

Diacetone Alcohol (CAS 123-42-2)	TWA	240 mg/m ³ 50 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m ³ 800 ppm
	TWA	980 mg/m ³ 400 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m ³ 1000 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m ³ 150 ppm
	TWA	375 mg/m ³ 100 ppm

BIOLOGICAL LIMIT VALUE:

ACGIH Biological Exposure Indices

COMPONENTS	VALUE	DETERMINANT	SPECIMEN	SAMPLING TIME
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

*For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:



EYE PROTECTION: Wear safety glasses with side shields (or goggles).

SKIN PROTECTION: Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

RESPIRATORY PROTECTION: If permissible levels are exceeded use NIOSH mechanical filter/organic vapor cartridge or an air-supplied respirator.

THERMAL HAZARDS: Wear appropriate thermal protective clothing, when necessary.

GENERAL HYGIENE CONSIDERATIONS: When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance:		Vapor Pressure:	35 - 55 psig @70°F estimated
Physical State:	Gas.	Vapor Density:	Not available.
Form:	Aerosol.	pH:	Not available.
Color:	White.	Viscosity:	Not available.
Odor:	Solvent.	Evaporation Rate:	Not available.
Odor Threshold:	Not available.	Flammability(solid/gas):	Not available.
Melting/Freezing Point:	Not available.	Upper Flammability Limit:	2.5% estimated
Boiling Point/Range:	257.08°F (125.05°C) estimated	Lower Flammability Limit:	12% estimated
Flash Point:	-156.0°F (-104.4°C) Propellant est	Upper Explosive Limit:	Not available.
Relative Density:	Not available.	Lower Explosive Limit:	Not available.
Solubility (water):	Not available.	Decomposition Temp:	Not available.
Auto-Ignition Temperature:	886.24°F (474.58°C) estimated	Specific Gravity:	0.817 estimated
Partition Coeff (n-octanol/water):	Not available.	Viscosity:	Not available.

10. Stability & Reactivity Information

REACTIVITY:

The product is stable and non-reactive under normal conditions of use, storage, and transport.

CHEMICAL STABILITY:

Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

CONDITIONS TO AVOID:

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

INCOMPATIBLE MATERIALS:

Acids. Strong oxidizing agents. Nitrates. Isocyanates. Fluorine. Chlorine.

DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

EYES: Causes serious eye irritation.

SKIN: Causes skin irritation.

INHALATION: May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.

INGESTION: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

ACUTE TOXICITY:

May be fatal if swallowed and enters airways. Narcotic effects. In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness, and central nervous system effects.

COMPONENTS	SPECIES	TEST RESULTS
Butane (CAS 106-97-8)		
Acute <i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Diacetone Alcohol (CAS 123-42-2)		
Acute <i>Dermal</i> LD50	Rabbit	14.5 ml/kg, 24 Hours
	Rat	> 1875 mg/kg, 24 Hours 13500 mg/kg
<i>Oral</i> LD50	Rat	3002 mg/kg
Isopropyl Alcohol (CAS 67-63-0)		
Acute <i>Dermal</i> LD50	Rabbit	16.4 ml/kg, 24 Hours
<i>Inhalation</i> LC50	Rat	> 10000 ppm, 6 Hours
<i>Oral</i> LD50	Rat	5.84 g/kg
Propane (CAS 74-98-6)		
Acute <i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h
Toluene (CAS 108-88-3)		
Acute <i>Dermal</i> LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i> LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 12.5 - 28.8 mg/l, 4 Hours
<i>Oral</i> LD50	Rat	5000 mg/kg

* Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Causes skin irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Causes serious eye irritation.

RESPIRATORY SENSITIZATION:

Not available.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

CARCINOGENICITY:

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

REPRODUCTIVE TOXICITY:

Suspected of damaging fertility or the unborn child.

SPECIFIC TARGET ORGAN TOXICITY (single exposure):

May cause drowsiness and dizziness.

SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):

Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.

ASPIRATION HAZARD:

May be fatal if swallowed and enters airways.

CHRONIC EFFECTS:

Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

12. Ecological Information**ECOTOXICITY:**

Toxic to aquatic life with long lasting effects.

COMPONENT		SPECIES	TEST RESULTS	
Diacetone Alcohol (CAS 123-42-2)	Aquatic			
	Fish	LC50	Bluegill (Lepomis macrochirus) 420 mg/l, 96 hours Fish 420 mg/l, 96 hours	
Isopropyl Alcohol (CAS 67-63-0)	Aquatic			
	Algae	IC50	1000.0001 mg/L, 72 Hours	
	Crustacea	EC50	Daphnia 13299 mg/L, 48 Hours	
	Fish	LC50	Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours	
Toluene (CAS 108-88-3)	Aquatic			
	Algae	IC50	433.0001 mg/L, 72 Hours	
	Crustacea	EC50	Daphnia 7.645 mg/L, 48 Hours	
	Fish	LC50	Water flea (Daphnia magna) Coho salmon, silver salmon (Oncorhynchus kisutch)	5.46 - 9.83 mg/l, 48 hours 8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:

No data available.

Partition coefficient n-octanol / water (log Kow)

Butane	2.89
Diacetone Alcohol	-0.098
Isopropyl Alcohol	0.05
Propane	2.36
Toluene	2.73

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration**DISPOSAL INSTRUCTIONS:**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate, or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways, or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer, and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Toluene (CAS 108-88-3) U220

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

CONTAMINATED PACKAGING:

Empty containers should be taken to an approved waste-handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not reuse empty containers.

14. Transportation Information

DOT: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable
TRANSPORT HAZARD CLASS(ES)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

PACKING GROUP: Not available.

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

LABELS REQUIRED: 2.1



SPECIAL PROVISIONS: N82
PACKAGING EXCEPTIONS: 306
PACKAGING NON BULK: None.
PACKAGING BULK: None.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable
TRANSPORT HAZARD CLASS(ES)
Class: 2.1
Subsidiary Risk: -
LABEL(S): 2.1



PACKING GROUP: Not applicable.

ENVIRONMENTAL HAZARDS: Yes.

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

OTHER INFORMATION:

PASSENGER AND CARGO AIRCRAFT: Forbidden.

CARGO AIRCRAFT ONLY: Forbidden.

PACKAGING EXCEPTIONS: LTD QTY

IMDG: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: AEROSOLS
TRANSPORT HAZARD CLASS(ES)
Class: 2.1
Subsidiary Risk: -
Label(s): 2.1



PACKING GROUP: Not applicable.

ENVIRONMENTAL HAZARDS:

Marine pollutant: Yes.

EmS: Not available.

SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

PACKAGING EXCEPTIONS: LTD QTY

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:
Not applicable.

15. Regulatory Information

US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Toluene (CAS 108-88-3) Listed.

SARA 304 Emergency release notification: Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

Hazard categories:
Immediate Hazard – Yes.
Delayed Hazard – Yes.
Fire Hazard – Yes.
Pressure Hazard – No.
Reactivity Hazard – No.

SARA 302 Extremely hazardous substance: No.

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting)

Chemical Name	CAS Number	% by Wt
Toluene	108-88-3	40-60

OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 % weight/volume

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US STATE REGULATIONS

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Diacetone Alcohol (CAS 123-42-2)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Diacetone Alcohol (CAS 123-42-2)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Diacetone Alcohol (CAS 123-42-2)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. Rhode Island RTK

Butane (CAS 106-97-8)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.