PRO CHEM, INC.

1475 BLUEGRASS LAKES PKWY. ALPHARETTA, GA 30004 EMERGENCY/INFO # (800) 241-8180 ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET

MECHANIC'S HELPER / 1286 SEPTEMBER 2009

PAGE 1

 HEALTH
 1

 FIRE
 1

 REACTIVITY
 0

 P.P.E.
 B

Not applicable

Complies With USDL Safety and Health Regulations, (29 CFR 1910.200)

SECTION 1 -	Chemical and	Company	y Identification
-------------	--------------	---------	------------------

CASE NO.: MIXTURE GENERAL DESCRIPTION: SILICONE

SECTION 2 – Composition on Ingredients

COMPONENT	CAS#	WT %	EXPOSURE LIMITS
Methyltriacetoxysilane	004253343	2	Observe limits. Acetic acid formed during curing
Silica, Amorphous	007631869	10	exposure to water or humid air.
Ethyltriacetoxysilane	017689779	2	OSHA PEL: TWA 10 PPM; ACGIH TLV: TWA 10 PPM; STEL: 15 PPM; OSHA PEL: TWA 20 MG/M3 TOTAL DUST.

SECTION 3 – Hazards Information

EFFECTS OF OVEREXPOSURE:

EYE: Direct contact irritates slightly to moderately with redness and swelling.

SKIN: A single short exposure (less than 24 hours) may irritate. Repeat prolonged contact (24 to 48 hours) may irritate moderately.

INHALATION: Vapor overexposure may irritate eyes, nose and throat.

ORAL: Small amounts transferred to the mouth by fingers during use, etc., should not injure.

Swallowing large amount may cause digestive discomfort.

COMMENTS: No injury from silica dust should occur during reasonable use. If use creates respirable particles, some respiratory system injury may occur. This product, as with any chemical, may enhance allergic conditions on certain people. We do not know of any medical conditions that might be aggravated by exposure to this product.

SECTION 4 - First Aid Measures

INGESTION: No first aid should be needed. SKIN: Wipe off and flush with water.

INHALATION: Remove to fresh air.

EYES: flush eyes with water for 15 minutes. Get medical attention if irritation develops.

COMMENT: None.

SECTION 5 – Fire Fighting Measures

FLASH POINT (Closed Cup): Above 212°F/100°C
AUTOIGNITION: Not determined
FLAMMABILITY LIMITS IN AIR: Lower: N/D Upper: N/D

EXTINGUISHING MEDIA: Carbon Dioxide (CO₂), Water fog, Dry Chemical, Foam.

SPECIAL FIRE FIGHTING PROCEDURES: Self contained breathing apparatus and protective clothing

should be worn in fighting fires involving chemicals.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Not known.

COMMENTS: Not determined.

SECTION 6 – Accidental Release Measures

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Remove product and contain for salvage or disposal.

SECTION 7 – Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store below 90°F/32°C. Keep container closed when not in use. Other precautions: None known. COMMENTS: None

SECTION 8 – Exposure Controls/Personal Protection

INHALATION: Use respiratory protections unless local exhaust ventilation is adequate or air sampling data show exposures are within TLV and PEL guidelines.

SUITABLE RESPIRATOR: Acid Gas/Organic vapor type.

SKIN: Washing at mealtime and end of shifts is adequate. Remove contaminated clothing and shoes as soon as practical and clean thoroughly before reuse. Rubber or plastic gloves are recommended.

EYES: Use proper protection -safety glasses, at a minimum.

VENTILATION: Local exhaust: May be needed. Mechanical (General): Recommended.

These precautions are for room temperature handling. Use at elevated temperatures, or aerosol/spray applications may require added precautions. * Good practice requires that gross amount of any chemical be removed from the skin as soon as practical, especially before eating or smoking.

EVAPORATION RATE (ether=1)

SECTION 9 – Physical and Chemical Properties

COLOR: Black PHYSICAL FORM: Paste SPECIFIC GRAVITY @ 25°C: ODOR: Acetic acid odor 1.04 **BOILING POINT** % VOLATILE BY WT: <5% (@760 mmHg): SOLUBILITY IN WATER: <0.1% Not applicable MELTING POINT: VAPOR PRESSURE @ 25°C: Not applicable <5mm

VAPOR DENSITY (air=1@25°C): >1

Note: The above information is not intended for use in preparing product specifications.

SECTION 10 - Stability and Reactivity

STABILITY: Stable

INCOMPATIBILITY (*material to avoid*): Oxidizing material can cause a reaction. Air or moisture causes curing and acetic acid vapors to form.

CONDITIONS TO AVOID: Exposure to air or moisture until ready to use.

HAZARDOUS DECOMPOSITION PRODUCTS: Silicone dioxide, carbon dioxide, and traces of

incompletely burned carbon products.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Not applicable

COMMENTS: None

SECTION 11 – Toxicological Information

No data available.

SECTION 12 – Ecological Information

No data available.

SECTION 13 – Disposal Consideration

DISPOSAL METHOD: Pro Chem suggests that all local, state and federal regulations concerning health and pollution be reviewed to determine approved disposal procedures. Contact Pro Chem if there are any disposal questions.

THIS INFORMATION MUST BE ON ALL MSDS'S COPIED AND DISTRIBUTED FOR THIS MATERIAL

NO WARRANTY IS EXPRESSED/IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE/USER ASSUMES ALL RISKS ASSOCIATED WITH USE.

PRO CHEM, INC.

1475 BLUEGRASS LAKES PKWY. ALPHARETTA, GA 30004 EMERGENCY/INFO # (800) 241-8180 ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET MECHANIC'S HELPER / 1286 SEPTEMBER 2009 PAGE 2

HEALTH	1
FIRE	1
REACTIVITY	0
P.P.E.	В

Complies With USDL Safety and Health Regulations, (29 CFR 1910.200)

SECTION 14 – Transport Information

PROPER SHIPPING NAME (49 CFR 172.101): None DOT HAZARD NAME (CFR 172.101): None DOT ID NUMBER (49 CFR 172.101): None DOT HAZARD CLASS(49 CFR 172.101): None

SECTION 15 – Regulatory Information

RCRA HAZARD CLASS (40 CFR 261)(IF DISCARDED): None EPA PRIORITY POLLUTANTS (40 CFR 122.53): None NFPA (NATIONAL FIRE PROTECTION ASSOCIATION) – 704: HEALTH (NFPA):1 FLAMMABILITY (NFPA):1 REACTIVITY (NFPA):0

D.O.T. (49 CFR 171.8) /EPA (40 CFR 117) Spill reporting information

HAZARDOUS SUBSTANCE: None REPORTABLE QUANTITY: Not applicable

REPORTABLE QUANTITY OF PRODUCT: Not applicable

COMMENTS: None

SECTION 16 – Other Information

Additional information: These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is made.

The recommended handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use.