

MEGA BLAST #1605

Aerosol Nonflammable Safety Solvent with Powerful Blast Valve



Features:

- VOC compliant
- Powerful flushing action
- Contains no chlorinated solvents, CFC's or HCFC's
- Nonflammable, rapid drying
- Residue free
- 26,800 volt dielectric strength
- Safe on most plastics*
- Safe for cleaning energized electrical equipment
- Level 1 storage rating

Description:

MEGA BLAST is a high performance, fast evaporating, nonflammable replacement for chlorinated and chlorofluorinated solvents. It is an excellent electrical contact cleaner and degreaser that dries quickly and residue free. With the powerful blast valve, it quickly removes grease, grime, wax and oil from motors, relays, switches, generators and control panels.



Applications:

- Motors
- Starters
- Gears
- Molds
- Relays
- Power Tools
- Aircraft Parts
- Engine Parts
- Generators
- Compressors
- Bearings
- Windings
- Marine Equipment
- Processing Equipment
- Energized Electrical Equipment
- Printing Equipment
- Production Machinery
- Gas, Water and Electric Meters
- Heating and Air Conditioning
- Refrigeration Equipment
- Industrial Equipment

Product Characteristics:

Appearance:	Clear, colorless gas
Odor:	Solvent
Vapor Density:	Not available
Evaporation Rate:	Not available
Solubility(water):	Not available
Flash Point:	Not available
Oxidizing Properties:	Not oxidizing
Relative Density:	Not available
Vapor Pressure:	14.8 psig @70°F estimated
Initial Boiling Point Range:	Not available
Auto-Ignition Temp:	Not available
pH:	Not available
Specific Gravity:	1.341 estimated
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.
Transport Information:	
Proper Shipping Name:	Aerosols, nonflammable
UN Number:	UN1950
Class:	2.2
Packing Group:	Not applicable

Directions:

Spray parts thoroughly, holding actuator close to surface. Use extension tube for hard-to-reach areas. Use only in well-ventilated areas. For heavily encrusted areas, brush, then rinse off with a second application.

*Safe on most plastic. Do not use on modern plastics; LEXAN®, ABS, NORYL, STYRENE and POLYSTYRENE PLASTICS. Pretesting on small inconspicuous area is suggested on questionable plastic surfaces.

Note: Energized equipment use only. Not to be used for motorized vehicle maintenance or their parts.

Pictograms:



Signal Word:

Warning.

Personal Protective Equipment Required:



DOT Placard:

