

MOLY-LUB #1714

Aerosol Anti-seize Lubricant



Features:

- Dry film lubricant withstands high temperatures and extreme pressure
- Resists salt water penetration
- Non-chlorinated
- Protects against moisture, rust and corrosion
- Non-corrosive and non-conductive
- Dry film will not attract dust or dirt
- Anti-seize, anti-friction
- Contains no silicone, grease, oil or graphite
- Contains no methylene chloride



Description:

MOLY-LUB is an extreme range lubricant and anti-seize coating that withstands temperatures from -110°F to +1050°F, resists pressures up to 100,000 psi and is resistant to water, oil, alkalis and many acids. It contains pure molybdenum disulfide particles, which burnish themselves into metal surfaces and provide a bonded lubricating film. This product will not attract dust and provides a tenaciously adherent coating, even under salt spray conditions. It adheres to metals, rubber, glass and most plastics.

Applications:

- Oil and Ore Drills
- Bearings
- Construction Equipment
- Conveyors
- Bolts
- Turbines
- Chains
- Nuts
- Boilers
- Engines
- Studs
- Motors
- Gears
- Pump Assemblies
- Compressors

Product Characteristics:

Appearance:	Liquid
Form:	Spray Aerosol
Odor:	No data available
Boiling Point:	No data available
Vapor Pressure:	3,102 - 3,792 hPa (20°C)
Vapor Density:	No data available
Flash Point:	Estimated -104.4°C
Solubility (water):	No data available
pH:	No data available
Self-Ignition Temperature:	No data available
Explosive Properties:	No data available
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
Proper Shipping Name:	Aerosols, flammable
UN Number:	UN1950
Hazard Class/Division:	2.1
Packing Group:	II

Directions:

Shake can vigorously before application. Surface must be free from loose rust, oil, grease and old paint. Hold can 8-10 inches from surface and spray in a sweeping motion to ensure a thin, uniform coating. Allow first application to dry 3 to 5 minutes before applying second coat.

Important: To prevent clogging, after each use invert can and spray a few short bursts to clear valve.

Caution: Do not use near heat, sparks or open flame.

Pictograms:



Signal Word:

DANGER

Personal Protective Equipment Required:



DOT Placard:

