

Features

- VOC Compliant
- Lengthens and protects life of all rubber parts
- High viscosity
- Formulated to leave a slippery, continuous film that facilitates a wide range of applications
- Protects metal finish from rust and corrosion.
- Non-drying formula
- Temperature range works from -58°F to +600°F
- Thick viscous film adheres to most surfaces like a magnet



Description

MP Silicone is a VOC compliant, high viscosity, heavy duty silicone that was specially formulated to provide superior all-purpose lubrication and protection without the use of ozone depleting chlorinated solvents. MP Silicone eliminates “Hang-up” in molding, casting and stamping dies. This product can be used on moving parts as a water and weather barrier, and as an electrical insulator. MP Silicone can also be used to prevent sticking, squeaking and freezing of doors, windows, locks and assemblies.

Applications

- Hinges
- Springs
- Ignitions
- Maintenance shops
- Battery terminals and cables
- Molds
- Dies
- Locks
- Cutting tables and conveyors

Directions

Clean surface to be treated. Remove cap and spray a thin film on surface from 8-10 inches away. Wipe away excess with a clean cloth. If used on sticking parts, work back and forth and reapply.

Note: Always test in an inconspicuous area before use.

Product Characteristics

Container Size	16 oz. Aerosol Can
Appearance	Clear lubricant
Odor	N/A
Flash Point	<0°F
Specific Gravity (H2O=1)	0.70 + 0.05
Solubility in water	Nil
Evaporation rate (water=1)	Slower than Ether
Boiling Point	1.75 to 388°F
pH	N/A
Vapor Density (Air = 1)	Heavier than air
VOC Content	59.0%
Storage	Do not store at temperatures above 120°F. Keep out of reach of children. Keep away from heat, sparks, or open flame.
Silicone Content	4.75
Transportation information	
Class #	55
NFMC	

Health	1
Flammability	3
Reactivity	0
Personal Protection	A