

# OXALL PLUS #2618

## Highly Concentrated Lime and Scale Remover



### Features:

- Quickly penetrates to break up and dissolve lime deposits, scale, mineral deposits and rust
- Provides same inhibited benefits for metal surfaces
- Highly concentrated formula dilutes with 4 to 8 parts water for most applications
- Free of noxious fumes
- Food Processing Acceptability: A3



### Description:

OXALL PLUS is great for use in removing mortar stains and film from bricks, masonry and stonework. The aggressive formula quickly penetrates and dissolves lime deposits, scale and rust from treated surfaces. Its special inhibitor provides “cling” power and slows down the drying process to prevent streaking. It is also an effective product to use to clean concrete handling equipment and water meters.

### Applications:

- Concrete Forms
- Heat Exchangers
- Water Meters
- Ready-Mix Concrete Trucks
- Air Conditioning Tanks
- Cement Industry Equipment

### Product Characteristics:

Appearance:	Clear liquid
Color:	Light amber
Odor:	Acid
Boiling Point:	Not available
Vapor Pressure:	Not available
Water Solubility:	Complete
Relative Density:	1.05
Flash Point:	None
VOC Content (Wt. %):	0
pH:	<1
Storage:	Store locked up in a well-ventilated place. Store in corrosive resistant plastic container.
<b>Transport Information:</b>	
UN Number:	UN3264
Proper Shipping Name:	Corrosive Liquid, Acidic, Inorganic, n.o.s. (CONTAINS HYDROCHLORIC (MURIATIC) ACID)
Class:	8
Packing Group:	II

### Directions:

**Cleaning Rust from Concrete:** Dilute with 4-8 parts water. Spray or brush on. Rinse well.

**Water Meters:** Using a stoneware or plastic container, soak the meter parts in the concentrate until the scale has dissolved. Remove and rinse thoroughly with water and store in a dry area away from where cleaning has taken place.

**Cleaning Equipment:** Concentrate should be used full strength on heavy deposits of lime, scale or cement. Rinse well with water after leaving concentrate on for a short time. For light deposits use concentrate diluted with an equal portion of water.

### NOTICE: KEEP FROM FREEZING

If concentrate is stored in cold or freezing weather it may separate or thicken. This will not affect the performance of the product. Before using, warm to room temperature and stir thoroughly.

**NOTE:** Do not use on aluminum, painted enamel surfaces and stainless steel or decorative brass.

### DOT Placard:



### VOC Compliance:

Not available.

### Pictograms:



### Signal Word:

Warning

### Personal Protective Equipment Required:

