

PRO CHEM, INC.

1475 BLUEGRASS LAKES PKWY.
ALPHARETTA, GA 30004
EMERGENCY/INFO # (800) 241-8180
ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET

PC 454 / 2487
NOVEMBER 2011
PAGE 1

HEALTH	2
FIRE	2
REACTIVITY	1
P.P.E.	B

Complies With USDL Safety and Health Regulations, (29 CFR 1910.1200)

SECTION 1 – Chemical and Company Identification

COMMON IDENTIFICATION: Superglue

USE OF THE SUBSTANCE/PREPARATION: Adhesive

SECTION 2 – Composition on Ingredients

COMPONENTS	CAS #	WEIGHT %	EINECS Number	EU Classification
Ethyl-2 Cyanoacrylate	7085-85-0	80-95	230-391-5	Xi: R36/37/38
Poly Methyl Methacrylate	9011-14-7	5-10	N/A	N/A

SECTION 3 – Hazards Information

EMERGENCY OVERVIEW- CAUTION: Clear liquid, with sharp irritating odor. Cyanoacrylate adhesives are a very fast setting and strong adhesive. It bonds human tissue and skin in seconds.

Avoid contact with skin and eyes. Avoid breathing vapors.

PRINCIPLE ROUTES OF EXPOSURE: Eyes and skin and inhalation.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: Irritating to eyes. Causes excessive tearing. Eyelids may bond.

SKIN CONTACT: Bonds to skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat during the cure process and, in rare instances; a large drop can burn the skin.

INHALATION: Exposure to vapors above the established exposure limit results in respiratory irritation which may lead to difficulty breathing and tightness in the chest.

INGESTION: Material is not harmful if ingested. Cyanoacrylates are almost impossible to swallow because they solidify in the mouth.

CARCINOGENIC EFFECTS: No data available on the product itself. Contains no known carcinogens.

SECTION 4 – First Aid Measures

EYES: Flush with warm water. If eye lids are bonded closed, release eyelashes with warm water by covering the eye with a wet pad. Do not force eye open.

SKIN: Soak in warm water. Do not pull skin apart.

INHALATION: Remove to fresh air. If symptoms persist, obtain medical attention.

INGESTION: Ingestion is unlikely. If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow Cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one to two days.

NOTES TO PHYSICIAN: Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue and skin in seconds. Experience has shown that accidents due to Cyanoacrylates are best handled by passive, non-surgical first aid.

SECTION 5 – Fire Fighting Measures

FLASH POINT: 150-200°F, Tag Closed Cup

EXPLOSION LIMITS IN AIR: LOWER %: Not established. UPPER %: Not established.

OSHA FLAMMABILITY CLASSIFICATION: Combustible.

AUTO-IGNITION TEMPERATURE: Not established.

EXTINGUISHER MEDIA: Dry chemical, CO₂, or foam.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS: Fire fighters should wear full turnout gear including self contained breathing apparatus in positive pressure mode.

SPECIFIC HAZARDS: None.

HAZARDOUS DECOMPOSITION AND/OR COMBUSTION PRODUCTS: Not established.

RISK OF DUST EXPLOSION: Not applicable.

SECTION 6 – Accidental Release Measures

PERSONAL PRECAUTIONS: Make sure spill area is well ventilated. Use adequate personal protective equipment.

METHODS FOR CLEANING UP: Do not use cloths for clean-up. Flood spilled material with water to polymerize. Cured material can be scraped up and disposed of as non-hazardous waste.

SECTION 7 – Handling and Storage

HANDLING: Avoid contact with skin, eyes, and clothing. Avoid breathing vapor or mist. Avoid contact with paper goods or fabric. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors.

STORAGE: Store away from heat and direct sunlight to maximize shelf life. Store inside in a dry location. Keep container tightly closed.

SECTION 8 – Exposure Controls/Personal Protection

EXPOSURE LIMITS: Exposure limits for those components with limits are stated below.

Ethyl-2 Cyanoacrylate:

US OSHA PEL: None

USACGIH – TLV: 0.2 ppm TWA

Poly Methyl Methacrylate:

US OSHA PEL: None

US ACGIH – TLV: None

PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit

US OSHA: United States Occupational Safety and Health Administration

TLV: Threshold Limit Value

TWA: Time Weighted Average

US ACGIH: United States American Conference of Governmental Industrial Hygienists

ENGINEERING CONTROLS: Local exhaust ventilation is recommended to maintain vapor level below TLV.

PERSONAL PROTECTIVE EQUIPMENT:

RESPIRATORY PROTECTION: Not applicable with good local exhaust. Use NIOSH approved respirator if there is a potential to exceed exposure limits.

HAND PROTECTION: Polyethylene or non reactive gloves. Do not use cotton, PVC, or wool.

EYE PROTECTION: Safety glasses or goggles with side shields.

SKIN AND BODY PROTECTION: Wear chemical resistant clothing when potential for skin contact exists.

OTHER: Eyewash and safety shower should be available for use in the immediate work area. Wash hands after using and before eating, drinking, smoking or using the lavatory.

SECTION 9 – Physical and Chemical Properties

pH: Not applicable

VISCOSITY: Not established

BOILING POINT/RANGE: > 300°F

EVAPORATION RATE: Not applicable

% VOLATILE

(SCQAMD Method 316B): less than 20 grams per liter, 2% (est.)

WATER SOLUBILITY: Negligible, Polymerized by water

MELTING POINT/RANGE: Not applicable

THIS INFORMATION MUST BE ON ALL MSDS'S COPIED AND DISTRIBUTED FOR THIS MATERIAL.

NO WARRANTY IS EXPRESSED/IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE/USER ASSUMES ALL RISKS ASSOCIATED WITH USE.

PRO CHEM, INC.

1475 BLUEGRASS LAKES PKWY.
ALPHARETTA, GA 30004
EMERGENCY/INFO # (800) 241-8180
ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET

PC 454 / 2487
NOVEMBER 2011
PAGE 2

HEALTH	2
FIRE	2
REACTIVITY	1
P.P.E.	B

Complies With USDL Safety and Health Regulations, (29 CFR 1910.1200)

SPECIFIC GRAVITY: 1.06 at 20° C
APPEARANCE: Clear liquid
ODOR: Sharp, irritating

VAPOR PRESSURE: Less than 0.2mm Hg @25°C
PARTITION COEFFICIENT (n-octanol/water): Not established

SECTION 10 – Stability and Reactivity

STABILITY: Stable under recommended storage conditions
HAZARDOUS POLYMERIZATION: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.
MECHANICAL SENSITIVITY (SHOCK): Not applicable
CONDITIONS TO AVOID: Polymerized by contact with water, alcohols, amines, and alkalis.
HAZARDOUS DECOMPOSITION AND/OR COMBUSTION PRODUCTS: Not established.

SECTION 11 – Toxicological Information**ACUTE TOXICITY**

Oral LD50: Acute oral LD50 >5000mg/kg (rat) (estimated).
Inhalation LC50: Not established.
Dermal LC50: Acute dermal LD50> 2000 mg/kg (rabbit) (estimated).
Eye Irritation: Not established.
Skin Irritation: Not established.

CHRONIC TOXICITY

Carcinogenic Effects: No data available on product itself.
Mutagenic Effects: No data available on product itself.
Reproductive Toxicity: No data available on product itself.
Sensitizing Effects: No data available on product itself.
Synergistic Materials: No data available on product itself.

SECTION 12 – Ecological Information

Information given is based on data on the components and the toxicology of similar products.

Aquatic Toxicity: No data available on product itself.

ENVIRONMENTAL FATE

Mobility: No data available on product itself.
Bioaccumulation: No data available on product itself.
Persistence / Degradability: No data available on product itself.
Distribution to Environmental Compartments: No data available on product itself.

SECTION 13 – Disposal Consideration

DISCLAIMER: Information in this section pertains to the product as shipped in its intended composition as described in Section 2 of this MSDS. Contamination or processing may change waste characteristics and requirements. Regulations may also apply to empty containers, liners or rinsate. State/provincial and local regulations may be different from federal regulations.
RCRA CLASSIFICATION (40 CFR 261): Dispose of in accordance with all federal, state and local regulatory requirements.

SECTION 14 – Transport Information**CFR:**

Proper shipping name: Combustible liquid, n.o.s. (more than 450 liters)
Hazard class or division: Combustible liquid (more than 450 liters)
Packing Group: III
Identification number: NA 1993 (More than 450 liters)
Exceptions: Unrestricted under 450 liters
Marine pollutant: No

SECTION 15 – Regulatory Information**Hazard Classification**

United States – OSHA (29 CFR 1910.1200): This product is considered hazardous under OSHA.
Canada – WHMIS Classification (CPR, SOR/88-66): B.3, D.2.B

International Inventories

All components of this product are listed on or exempt from the following inventories:
(yes) - Domestic Substances List (DSL)
(yes) - United States Toxic Substances Control Act (TSCA) Inventory

U.S. Federal Regulations

Clean Air Act amendments of 1990 (CAA, Section 11240: CFR 82): Contains no hazardous air pollutants.

Clean Water Act (CWA, 40 CFR 116): Contains no priority pollutants

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA, 40 CFR 302): None

Superfund Amendments and Reauthorization Act, Title III (SARA):

SARA Section 302 (40 CFR 355) Extremely Hazardous Substances: None

SARA Section 311/312 (40 CFR 370) Hazard Category: Immediate health hazard, Delayed health hazard, Fire, Reactive

SARA Section 313 (40 CFR 372) Toxics Release Inventory: None

U.S. State Regulations

California Proposition 65: None

SECTION 16 – Other Information

HMIS Index: *- chronic, 0 – Minimal, 1 – slight, 2- moderate, 3 – serious, 4 –severe

Health: 2

Flammability: 2

Physical Hazard: 1

The information contained herein is based on the data available to us and is believed to be correct. However, Pro Chem, Inc. makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their properties prior to use. Since conditions of use are beyond our control, all risks are assumed by the user.

THIS INFORMATION MUST BE ON ALL MSDS'S COPIED AND DISTRIBUTED FOR THIS MATERIAL.

NO WARRANTY IS EXPRESSED/IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE/USER ASSUMES ALL RISKS ASSOCIATED WITH USE.