

PEAK PERFORMANCE #1751

Aerosol Air Tool Lubricant and Cleaner



Features:

- Cleans, lubricates and reconditions
- Eliminates moisture
- Eliminates calcium buildup from moisture in air lines
- Prevents rust and corrosion
- Extends the life of air tools



Description:

PEAK PERFORMANCE is an oil that cleans, lubricates and reconditions air operated power tools. It enables air pressure to penetrate more freely, giving the tool more power. Eliminates calcium buildup from moisture in airlines and dissolves sludge, dirt and dust accumulation. This product protects all moving parts. Used regularly for preventative maintenance, PEAK PERFORMANCE will greatly reduce downtime and costly repairs.

Applications:

- Jackhammers
- Sanders
- Impact Wrenches
- Polishers
- Saws
- Air-Operated Tools
- Drills
- Grinders
- Air-Operated Motors

For Use By:

- Contractors
- Factories
- Fleet Operations
- Freight Carriers
- Industrial Plants
- Military Facilities
- Oil Fields
- Steel Mills
- Utility Companies

Product Characteristics:

Physical State:	Liquid
Form:	Spray Aerosol
Odor:	No data available
Boiling Point/Range:	Estimated 95°C
Explosive Limit – lower (%):	Estimated 1.9%(V)
Explosive Limit – upper (%):	Estimated 9.5%(V)
Vapor Pressure:	2,068 - 3,447 hPa (20°C)
Flash Point:	Estimated -104.4°C
pH:	No data available
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1 L capacity)
Class:	2.1
Packing Group:	Not applicable
Packaging Exceptions:	LTD QTY

Directions:

1. Spray into all openings including air inlet connection.
2. Allow product to penetrate for several seconds.
3. Run air tool at maximum RPM for 30 seconds.
4. Repeat above for severe conditions.
5. For long-term tool storage, repeat directions 1 – 3.

Pictograms:



Signal Word:

DANGER

Personal Protective Equipment Required:



DOT Placard:



VOC Compliant:

Yes.