

POLY FINISH #2102

Self-Polishing Floor Finish



Features:

- No initial buffing required
- 18% solids
- Excellent leveling ability and gloss
- Excellent firm formation and removability
- Resistant to scuff marks and heel marks
- Ready-to-use



Description:

POLY FINISH is a metal-crosslink, modified acrylic floor finish, which is designed to retain its glossy finish under even the most severe traffic and maintenance conditions. It defies water spills, detergents, scuffs marks, heel marks and provides exceptional slip resistance in all areas. Extremely economical covering between 1500 and 2000 square feet per gallon. POLY FINISH readily rebuffs.

Applications:

- All Resilient Floors
- Composition
- Linoleum
- Terrazzo
- Acrylic

Product Characteristics:

Appearance:	Emulsion
Odor:	Characteristic
Boiling Point:	Not available
Vapor Pressure:	Not available
Solubility (water):	Complete
Relative Density:	1.04
Flash Point:	None
VOC Content (Wt. %):	0
pH:	8-9
Storage:	Do not use or store near heat, sparks or open flame. Store in a cool, dry place.
Transport Information:	
UN Number:	Not regulated
Proper Shipping Name:	Not regulated
Class:	Not regulated
Packing Group:	Not regulated

Directions:

Thoroughly strip floor with a stripper. Rinse floor thoroughly with clean water. Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss. Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

Pictograms:

NOT A CONTROLLED



PRODUCT UNDER GHS

Signal Word:

No signal word.

DOT Placard:

Not regulated.

VOC Compliancy:

Yes.

Personal Protective Equipment Required:

