

PRESTO #1259

Aerosol Starting Fluid For All Gasoline & Diesel Engines



Features:

- Effective in temperatures as low as -65°F.
- Preserves batteries and ignition systems by minimizing crank time
- For use with 2- and 4-cycle engines

Description:

PRESTO stimulates engines for quick starts in extreme conditions. It contains high-endurance lubricants to protect engines from corrosion while preserving batteries and ignition systems by minimizing crank time during startup. This product quickly starts both 2-cycle and 4-cycle engines in difficult, damp and wet weather conditions.

Applications:

- 2-cycle Engines
- 4-cycle Engines
- Gasoline Engines
- Diesel Engines



Product Characteristics:

Appearance:	Aerosol, clean, colorless liquid
Odor:	Ether-like odor
Vapor Pressure:	No data available
Specific Gravity:	< 1 g/ml
Solubility (water):	Insoluble
Flash Point:	No data available
VOC Content:	> 90%
Viscosity:	< 20 cSt
NFPA Code 30B Rating:	Level 3 Aerosol
Storage:	Store in a cool area. Store away from heat.
Transport Information:	
Proper Shipping Name:	Consumer Commodity.
UN Number:	None.
Class:	ORM-D
Packing Group:	None.

Directions:

Do not flood engine before using. Spray PRESTO into air cleaner or carburetor once for 2 to 3 seconds. Stand clear because carburetor can backfire. Try starting engine in normal manner. If engine doesn't start, repeat above procedure up to three more times. If engine still fails to start, ignition should be checked by a professional.

NOTE: Avoid contact with battery terminals, solenoid, or other electrical components. Never spray while ignition is in "ON" position. Avoid overuse of product. Do not smoke while using product. *This diesel fuel additive complies with the Federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.*

DOT Placard:



VOC Compliant:

Yes.

Pictograms:



Signal Word:
Danger

Personal Protective Equipment Required:

