





SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1606	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	PRO STRIP	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	Paint Stripper	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION: Flammable aerosols: Category 1 Carcinogenicity: Category 2 Reproductive toxicity (the unborn child): Category 2 Specific target organ toxicity, single exposure: Category 2 Specific target organ toxicity, repeated exposure: Category 2 OSHA defined hazards: Not classified.	SIGNAL WORD: DANGER	SYMBOL:		
---	--------------------------------------	----------------	---	---

HAZARD STATEMENTS:

Extremely flammable aerosol. Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF EXPOSED OR CONCEREND: Call a poison center/doctor.

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

ENVIRONMENTAL HAZARDS:

Hazardous to the aquatic environment, acute hazard: Category 3

Hazardous to the aquatic environment, long-term hazard: Category 3

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

CHEMICAL NAME	CAS	Concentration % by Weight
Methylene Chloride	75-09-2	60-80
Isobutane	75-28-5	2.5-10
Methanol	67-56-1	2.5-10
Propane	74-98-6	2.5-10
Toluene	108-88-3	2.5-10
Other components below reportable levels		1-2.5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

EYES: Rinse with water. Get medical attention if irritation develops and persists.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

INHALATION:

If symptoms develop, move victim to fresh air. Get medical attention if symptoms persist.

INGESTION:

In the unlikely event of swallowing contact a physician or poison control center.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Dizziness. Nausea. Prolonged exposure may cause chronic effects.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

SPECIFIC FIRE-FIGHTING METHODS:

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure buildup. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion, do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during cleanup. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

MATERIALS AND METHODS FOR CLEANING UP:

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see Section 13 of the SDS.

ENVIRONMENTAL PRECAUTIONS:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

SAFE HANDLING:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind or expose containers to heat, flame, sparks or other sources of ignition. All equipment used when handling the product must be grounded. Do not reuse empty containers. Do not breathe mist or vapor. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection

OCCUPATIONAL EXPOSURE LIMITS

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

COMPONENTS	TYPE	VALUE
Methylene Chloride (CAS 75-09-2)	STEL	125 ppm
	TWA	25 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
Methanol (CAS 67-56-1)	PEL	260 mg/m ³
		200 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³
		1000 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Methylene Chloride (CAS 75-09-2)	TWA	50 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

COMPONENTS	TYPE	VALUE
Isobutane (CAS 75-28-5)	TWA	1900 mg/m ³ 800 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m ³ 250 ppm
	TWA	260 mg/m ³ 200 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m ³ 1000 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m ³ 150 ppm
	TWA	375 mg/m ³ 100 ppm

BIOLOGICAL LIMIT VALUE:

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
Methylene Chloride (CAS 75-09-2)	0.3 mg/l	Dichloromethane	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

EXPOSURE GUIDELINES:

US - California OELs: Skin designation:

Methanol (CAS 67-56-1): Can be absorbed through the skin.

Toluene (CAS 108-88-3): Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies:

Methanol (CAS 67-56-1): Skin designation applies.

Toluene (CAS 108-88-3): Skin designation applies.

US - Tennessee OELs: Skin designation:

Methanol (CAS 67-56-1): Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation:

Methanol (CAS 67-56-1): Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation:

Methanol (CAS 67-56-1): Can be absorbed through the skin.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:



Face/Eye Protection: Chemical respirator with organic vapor cartridge and full facepiece.

Skin Protection: Hand protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other: Use of an impervious apron is recommended.

Respiratory Protection: Chemical respirator with organic vapor cartridge and full facepiece.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

APPROPRIATE ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

9. Physical & Chemical Properties

Physical State:	Liquid.	Flammability (solid/gas):	Not applicable.
Form:	Aerosol.	Flammability Limit-lower (%):	10.5% estimated.
Color:	Not available.	Flammability Limit-upper (%):	17.6% estimated.
Odor:	Not available.	Explosive Limit - lower (%):	Not available.
Odor Threshold:	Not available.	Explosive Limit - upper (%):	Not available.
pH:	Not available.	Vapor Pressure:	2386.71 psig @70°F estimated.
Melting/Freezing Point:	Not available.	Vapor Density:	Not available.
Boiling Point and Range:	-16.28°F (-26.82°C) estimated.	Relative Density:	Not available.
Partition Coefficient (n-octanol/water):	Not available.	Solubility (water):	Not available.
Specific Gravity:	0.156 estimated.	Auto-Ignition Temperature:	1007.48°F (541.93°C) estimated.
Flash Point:	15.0°F (-9.4°C) estimated.	Decomposition Temperature:	Not available.
Viscosity:	Not available.	Evaporation Rate:	Not available.
Density:	0.16 g/cm ³ estimated.	Flammability Class:	Flammable IA estimated.
Explosive Properties:	Not explosive.	Heat of Combustion:	9.8 kJ/g estimated.
Oxidizing Properties:	Not oxidizing.	Heat of Combustion (NFPA 30B):	9.8 kJ/g estimated.
Percent Volatile:	98.4% estimated.	VOC (Weight %):	98.4% estimated

10. Stability & Reactivity Information

REACTIVITY:

The product is stable and nonreactive under normal conditions of use, storage and transport.

CHEMICAL STABILITY:

Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

CONDITIONS TO AVOID:

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

Eyes: Direct contact with eyes may cause temporary irritation.

Skin: No adverse effects due to skin contact are expected.

Inhalation: May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation.

Ingestion: Expected to be a low ingestion hazard.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

Dizziness. Nausea.

ACUTE TOXICITY:

Components	Species	Test Results
Isobutane (CAS 75-28-5)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52%, 120 Minutes 1355 mg/l
Methanol (CAS 67-56-1)		
Acute		
<i>Inhalation</i>		
LC50	Cat	85.41 mg/l, 4.5 Hours
	Mouse	43.68 mg/l, 6 Hours
	Rat	79.43 mg/l, 134 Minutes
		> 115.9 mg/l, 4 Hours
<i>Oral</i>		
LD50	Monkey	82.1 mg/l, 6 Hours
	Pig	6000 mg/kg
	Rat	>5000 mg/kg 1187 - 2769 mg/kg
Methylene Chloride (CAS 75-09-2)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg, Days
<i>Inhalation</i>		
Vapor		
LC50	Mouse	49000 mg/m ³ , 7 Hours
<i>Oral</i>		
LD50	Rat	>2000 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52%, 120 Minutes 1355 mg/l 658 mg/l/4 h
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	6405 - 7436 ppm, 6 Hours
	Rat	5320 ppm, 8 Hours
		5879 - 6281 ppm, 6 Hours
		25.7 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	>5000 mg/kg

* Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Prolonged skin contact may cause temporary irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Direct contact with eyes may cause temporary irritation.

RESPIRATORY SENSITIZATION:

Not a respiratory sensitizer.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

CARCINOGENICITY:

Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity:

Methylene Chloride (CAS 75-09-2) 2A Possibly carcinogenic to humans.
Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Methylene Chloride (CAS 75-09-2) Cancer.

US. National Toxicology Program (NTP) Report on Carcinogens:

Methylene Chloride (CAS 75-09-2) Reasonably anticipated to be a human carcinogen.

REPRODUCTIVE TOXICITY:

Suspected of damaging the unborn child.

SPECIFIC TARGET ORGAN TOXICITY (single exposure):

May cause damage to organs.

SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):

May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

ASPIRATION HAZARD:

Not an aspiration hazard.

CHRONIC EFFECTS:

May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological Information

ECOTOXICITY: Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
Methanol (CAS 67-56-1)		
Aquatic		
Crustacea EC50	Water flea (<i>Daphnia magna</i>)	> 10000 mg/l, 48 hours
Fish LC50	Fathead minnow (<i>Pimephales promelas</i>)	> 100 mg/l, 96 hours
Methylene Chloride (CAS 75-09-2)		
Aquatic		
Algae IC50	Algae	500.0001 mg/L, 72 Hours
Crustacea EC50	Daphnia	1689.5 mg/L, 48 Hours
	Water flea (<i>Daphnia magna</i>)	1250 mg/l, 48 hours
Fish LC50	Fathead minnow (<i>Pimephales promelas</i>)	140.8 - 277.8 mg/l, 96 hours
Toluene (CAS 108-88-3)		
Aquatic		
Algae IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea EC50	Daphnia	7.645 mg/L, 48 Hours
	Water flea (<i>Daphnia magna</i>)	5.46 - 9.83 mg/l, 48 hours
Fish LC50	Coho salmon, silver salmon (<i>Oncorhynchus kisutch</i>)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:**Partition coefficient n-octanol / water (log Kow):**

Isobutane 2.76
Methanol -0.77
Methylene Chloride 1.25
Propane 2.36
Toluene 2.73

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration**DISPOSAL INSTRUCTIONS:**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (See: Disposal instructions).

CONTAMINATED PACKAGING:

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not reuse empty containers.

14. Transportation Information

DOT: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable
TRANSPORT HAZARD CLASS(ES)
 Class: 2.1
Subsidiary Risk: -
Label(s): 2.1
PACKING GROUP: Not applicable.
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.
SPECIAL PROVISIONS: N82.
PACKAGING EXCEPTIONS: 306.
PACKAGING NON BULK: None.
PACKAGING BULK: None.



This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: Aerosols, flammable, containing substances in Division 6.1, Packing Group III
TRANSPORT HAZARD CLASS(ES)
 Class: 2.1
Subsidiary Risk: 6.1(PGIII)
Label(s): 2.1, 6.1



PACKING GROUP: Not applicable.
ENVIRONMENTAL HAZARDS: No.
ERG CODE: 10P.
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.

OTHER INFORMATION:
PASSENGER AND CARGO AIRCRAFT: Allowed with restrictions.
CARGO AIRCRAFT ONLY: Allowed with restrictions.
PACKAGING EXCEPTIONS: LTD QTY.

IMDG: **UN NUMBER:** UN1950
UN PROPER SHIPPING NAME: AEROSOLS.
TRANSPORT HAZARD CLASS(ES)
 Class: 2.1
Subsidiary Risk: 6.1 (PGIII).
Label(s): 2.1 + 6.1



PACKING GROUP: Not applicable.
ENVIRONMENTAL HAZARDS:
Marine pollutant: No.
EmS: F-D, S-U
SPECIAL PRECAUTIONS FOR USER: Read safety instructions, SDS and emergency procedures before handling.
PACKAGING EXCEPTIONS: NOT a LTD QTY.
TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:
 Not applicable.

15. Regulatory Information**US FEDERAL REGULATIONS:**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4):

Methanol (CAS 67-56-1): Listed.
 Methylene Chloride (CAS 75-09-2): Listed.
 Toluene (CAS 108-88-3): Listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Methylene Chloride (CAS 75-09-2): Cancer.
 Heart.
 Central nervous system.
 Liver.
 Skin irritation.
 Eye irritation.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA):

Hazard categories: Immediate Hazard – Yes.
 Delayed Hazard – Yes.
 Fire Hazard – Yes.
 Pressure Hazard – No.
 Reactivity Hazard – No.

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting)

Chemical Name	CAS Number	% by wt.
Methylene Chloride	75-09-2	60-80
Methanol	67-56-1	2.5-10
Toluene	108-88-3	2.5-10

OTHER FEDERAL REGULATIONS:**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:**

Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Isobutane (CAS 75-28-5)
Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number:

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)):

Toluene (CAS 108-88-3) 35%WV

DEA Exempt Chemical Mixtures Code Number:

Toluene (CAS 108-88-3) 594

US STATE REGULATIONS

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.(a)):

Isobutane (CAS 75-28-5)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List:

Isobutane (CAS 75-28-5)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act:

Isobutane (CAS 75-28-5)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law:

Isobutane (CAS 75-28-5)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Toluene (CAS 108-88-3)

US. Rhode Island RTK:

Isobutane (CAS 75-28-5)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Toluene (CAS 108-88-3)

US. California Proposition 65:

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance:

Methylene Chloride (CAS 75-09-2) Listed: April 1, 1988
Propylene Oxide (CAS 75-56-9) Listed: October 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin:

Methanol (CAS 67-56-1) Listed: March 16, 2012
Toluene (CAS 108-88-3) Listed: January 1, 1991

INTERNATIONAL INVENTORIES:

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.