

For
COMMERCIAL
& INDUSTRIAL

PRO EARTH PAINT STRIPPER

Paint and Polyurethane Remover

PRO EARTH PAINT STRIPPER, a soy-based paint and polyurethane remover, is an environmentally friendly alternative to methylene chloride. This product is formulated to fully remove a wide range of coatings, including oil and latex paints, polyurethanes, lacquers, concrete sealers and adhesives. This product will work on wood, metal, masonry, and most other surfaces. PRO EARTH PAINT STRIPPER will also remove graffiti from stone, metal, aluminum, wood, or powder-coated surfaces.

DIRECTIONS

Test all surfaces before using by applying a small amount in an inconspicuous area. If surface discolors, mars, ripples, bubbles, or softens, do not use. For best results, use in temperatures over 45°F. **Will damage some plastics.**

1. Apply a uniform layer over the coating to be removed. The product can be sprayed, poured, or applied with a natural bristle brush.
2. Allow the product to remain on the surface for a minimum of 20 minutes. Some coatings may take 4-6 hours to completely loosen. Pro Earth Paint Stripper will remain wet and active for 24 hours.
3. Remove the softened coating using an appropriate scraping or stripping tool. Take care not to damage wood surfaces when removing coatings from furniture, cabinets or hardwood floors.
4. Use steel wool to remove any stubborn areas. Reapplication may be required when removing more than 5 layers of paint or coating material.
5. Wash and rinse surface using warm water. Use a mild cleaner, if desired.
6. Rinse with clean water to remove any additional residue.

SEE OTHER PANEL FOR CAUTIONS

AN EXCLUSIVE PRODUCT OF:

**PRO
CHEM**

P.O. BOX 1309,
ALPHARETTA, GA 30009-1309
TO REORDER CALL
1-800-241-8180
www.procheminc.com



**PRO
CHEM**

PRO EARTH PAINT STRIPPER

SOY-BASED PAINT & POLYURETHANE STRIPPER



- Safely removes 5+ layers of paint
- Clings to vertical surface for superior penetration
- Non-flammable
- Low VOC's
- Low odor – no harsh fumes
- Biodegradable

32 FL. OZ. (946 ml)

PRO EARTH PAINT STRIPPER

Paint and Polyurethane Remover

DANGER

Causes skin irritation; causes serious eye irritation; may cause respiratory irritation; may damage fertility of the unborn child. (Contains: 1-Methyl-2-pyrrolidone)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing fume, mist, vapours. Wash hands, forearms and face thoroughly after handling. Wear protective gloves, eye protection, protective clothing. If on skin: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical attention. Call a doctor, a POISON CENTER if you feel unwell. Specific treatment (see first aid instructions on this label). If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash before reuse.

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

See Safety Data Sheets for additional information.

KEEP OUT OF REACH OF CHILDREN

HMS RATING:

| | |
|--------------|-------------|
| HEALTH | 2 |
| FLAMMABILITY | 1 |
| REACTIVITY | 0 |
| Minimal - 0 | Slight - 1 |
| Moderate - 2 | Serious - 3 |
| Severe - 4 | |



Personal Protection: B
B = Safety Glasses and Gloves