

Prime Time #1630

Aerosol One-Step Rust Neutralizer & Metal Primer



Features:

- Converts rust to a durable coating that turns black where the rust was
- Prolongs the life of ferrous metal
- Eliminates the need for scraping and sandblasting
- Nonflammable when dry
- No major surface preparation required
- Prevents future rusting
- Paintable after curing
- Food Processing Acceptability: R2



Description:

PRIME TIME is a one-step rust converter and corrosion neutralizing spray. It chemically neutralizes rust and leaves a tough, long-term, rust-preventative coating. It seals, protects and prolongs the life of ferrous metal. Once it dries, the treated area will be black and more uniform in appearance with a durable, protective finish that protects the surface and prevents new rust from forming. It is in a convenient aerosol that penetrates into hard to reach places, as well as eliminates cleanup of brushes and containers.

Applications:

- Bottling & Packaging Equipment
- Public Transportation Vehicles
- Fences
- Playground Equipment
- Tanks/Pipes/Valves/Fittings
- Outdoor Advertising
- Guard Rails
- Metal Casings
- Motor Housings
- Agricultural equipment
- Transmission Line Supports
- Construction Equipment

For Use By:

- Industrial Plants
- Bus Garages
- Municipalities
- Utility Companies
- Fleet Maintenance
- DOT's
- Oil Fields
- Railroads
- Parks & Rec

Product Characteristics:

Physical State:	Gas.
Initial Boiling Point/Range:	138.79 °F (59.33 °C) estimated
Flash Point:	-156.0 °F (-104.4 °C) propellant estimated
Flammability Limit-lower (%):	2.6% estimated
Flammability Limit-upper (%):	12.8% estimated
Viscosity:	Not available.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
Proper Shipping Name:	Aerosols, flammable, (each not exceeding 1 L capacity)
UN Number:	UN1950
Class:	2.1
Packing Group:	Not applicable.

DOT Placard:



Directions:

For best results, workpiece and can should be at room temperature (above 65°F). Surfaces must be clean, dry and free of grease, dirt and oil. Remove loose rust and paint with coarse sandpaper or a wire brush. Before using, shake can until ball rattles freely for at least one minute. Holding the can 8-10 inches from the surface, spray a thin, even coating onto the rusted metal. Avoid over application, sagging and dripping. A second application is advised only after allowing for complete drying of initial application. Final application will dry to a black finish. May be painted after curing for approximately 6 hours.

Pictograms:



Signal Word:
DANGER

Personal Protective Equipment Required:

