

PRO TOOLS NF SOLVENT DEGREASER #1494

Aerosol Non-flammable Degreaser



Features:

- Non-flammable
- Dielectric strength of 30,000 volts
- Dries quickly and leaves no residue

Description:

PRO TOOLS NF SOLVENT DEGREASER is a highly aggressive solvent blend that is ideal for the most demanding degreasing applications. Excellent for use on equipment and machinery while in operation. It has a high dielectric strength of 30,000 volts and is potent enough to remove dust, dirt, oil and tar without leaving any residue.



Applications:

- Electric Motors
- Vending Machines
- Power Tools
- Refrigeration Units
- Ice Machines
- Generators

Product Characteristics:

Appearance:	Aerosol. Clear, colorless liquid
Odor:	Characteristic
Boiling Point:	188.95°F estimated
Specific Gravity:	1.47 g/cm ³ estimated
Solubility:	Insoluble in water
Flash Point:	None estimated
VOC:	< 97% estimated
Viscosity:	No data available
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.
Transport Information:	
UN Number:	UN1950
Proper Shipping Name:	Aerosol
Hazard Class:	2.2 - Nonflammable compressed gas 49 CFR 173.115
Packing Group:	III - Minor Danger

Directions:

Important: Prolonged contact with aluminum will cause discoloration.

Always test in an inconspicuous area to check product for comparability. Not to be used for motorized vehicle maintenance or their parts.

Remove cap and point actuator toward surface to be cleaned.

Saturate to desired level. For the cleaning of confined areas and small exact spots, insert the plastic extension tube provided into the valve opening until it bottoms, then spray. Allow solvent to remain in contact for 30 seconds to 1 minute and then wipe or air dry. Repeat as necessary to achieve desired results. Extra heavy deposits may require brushing. Check to be sure the bristles are compatible with the solvent before use.

Note: While overspray will not damage most durable plastics and rubber, the solvent in this product will soften and eventually dissolve, polystyrenes (such as Styrofoam) and polycarbonate (such as Lexan, Merlan, etc.)

DOT Placard:



VOC Compliant:

Yes.

Pictograms:



Signal Word:

DANGER.

Personal Protective Equipment Required:

