

RUST BUSTER #2604

Rust Control Neutralizer



Features:

- Prepares metal surfaces to accept paint
- No sandblasting, grinding or etching required
- Water-based, non-flammable formula
- Converts rust into a durable, long lasting, protective coating
- Ready-to-use – no thinning required

Description:

RUST BUSTER is a water-based solution containing penetrants and a polymeric barrier coating that chemically neutralizes rust into a neutral, organic protective coating. Dried RUST BUSTER is an excellent primer for all types of industrial and automotive topcoats. This product is less toxic than most latex paints and may be used safely indoors or outdoors. It converts iron oxide into a black protective coating that seals out moisture and prevents further corrosion. This tough primer extends paint life up to five times longer than normal.



Applications:

- Machinery
- Cars
- Decorative Metal
- Trucks
- Structural Steel
- Snow Removal Equipment

Product Characteristics:

Appearance:	Beige, opaque emulsion
Odor:	Bland odor
pH:	1.5 – 3
Specific Gravity:	1.13 g/ml
Solubility (water):	Soluble.
Flash Point:	> 200°F
VOC:	< 3%
Viscosity:	No data available
Storage:	Keep container closed when not in use. Keep only in original container. Store in a cool area. Store in a well-ventilated area.
Transport Information:	
Proper Shipping Name:	Not regulated for transport
UN Number:	Not regulated for transport
Class:	Not regulated for transport

Directions:

Shake or stir well. Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease. Use on dry or damp rusted metal surfaces. Do not apply if surface temperature is below 50°F. Apply a coating using a brush or roller or by dipping. Use soap and water for cleanup. Dries to a tack free finish in 20 minutes, after which a second coat can be applied. One gallon will treat up to 300 sq. feet or 500 sq. feet per gallon on smooth non-porous surfaces. Let cure for 48 hours before ready to apply oil-based paint.

Note: This product will not withstand freezing temperatures or temperatures above 100°F. Do not use with water-based paints.

DOT Placard:

Not regulated for transport.

VOC Compliant:

Yes.

Pictograms:

NOT A CONTROLLED



PRODUCT UNDER GHS

Signal Word:

None.

Personal Protective Equipment Required:

Use appropriate personal protective equipment when risk assessment indicates this is necessary.

