

SLIP-EZ #1263

Aerosol Food-Grade Silicone Lubricant



Features:

- Non-staining – colorless, odorless and fast drying
- Heat stable from -40°F to over 392°F
- Reduces friction and wear
- Non-chlorinated, safe on plastics, fabrics, metals and rubber
- High viscosity
- Stops sticking
- Food Processing Acceptability: H1

Description:

SLIP-EZ is a silicone aerosol that lubricates, protects, reduces friction and makes everything slide and glide easier. It forms a slick, water-repellent, non-adherent surface coating. SLIP-EZ deposits a stick-free surface wherever needed. It saves time, money, cleanup and aids in the prevention of corrosion. When using this product, there is less jamming. It will not discolor or damage fabrics, metals, rubber or plastic surfaces. Can be used to lubricate moving parts in food processing and packaging plants. Can be used on non-food contact surfaces of ovens and grills to prolong time between cleaning. Dry silicone formula prevents jamming and production slowdown on bottling and packaging lines.



Applications:

- Conveyers
- Ovens
- Locks
- Cutting Dies
- Guide Rails
- Dairies
- Slicing Equipment
- Vending Machines
- Sewing Machine
- Bottling Plants
- Mold Releases
- Grocery Stores
- Heating Equipment
- Sealing Equipment
- Scrambler Tables
- Packaging Plants
- Meat and Poultry Plants
- Container Molding Operations

Product Characteristics:

Appearance:	Colorless, gas.
Odor:	Mild solvent.
Vapor Density:	Not available.
Evaporation Rate:	Not available.
Auto Ignition Temperature:	658°F (347.78°C) estimated.
Flash Point:	-156.0 °F (-104.4 °C) Propellant estimated.
Oxidizing Properties:	Not oxidizing.
Relative Density:	Not available.
Vapor Pressure:	60 - 70 psig @70°F estimated.
Initial Boiling Point Range:	Not available.
Viscosity:	Not available.
pH:	Not available.
Specific Gravity:	0.785 – 0.795 estimated.
Storage:	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Transport Information:	
Proper Shipping Name:	Aerosols, flammable.
UN Number:	UN1950.
Class:	2.1
Packing Group:	Not applicable.

Directions:

Thoroughly clean surfaces to be treated. Use steel wool on metals and wipe with a good, compliant cleaning solvent if necessary. Clean rubber and plastic surfaces with detergent solution, rinse and dry thoroughly. Spray a thin, light silicone film; avoid over spraying. Remove excess with a clean cloth. Renew when necessary.

ATTENTION: Do not allow spray, mist or coating to cover floors; they may become slippery, especially when wet.

Pictograms:



Signal Word:
DANGER.

Personal Protective Equipment Required:



DOT Placard:



VOC Compliant:
Yes.