






# SAFETY DATA SHEET

## 1. Product and Company Identification

<b>PRODUCT NUMBER:</b>	1727	<b>COMPANY PHONE:</b>	1-800-241-8180
<b>PRODUCT NAME:</b>	SLITHER	<b>EMERGENCY TELEPHONE:</b>	1-800-241-8180
<b>PRODUCT DESCRIPTION:</b>	Penetrant/Lubricant Oil	<b>INFOTRAC:</b>	1-800-535-5053
<b>COMPANY INFORMATION:</b>	<b>PRO CHEM, INC.</b> 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

## 2. Hazards Identification

<b>GHS CLASSIFICATION:</b> Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) - Category 3 Specific Target Organ Toxicity - Repeated Exposure - Category 2 Aspiration Hazard - Category 1 Skin Irritation - Category 2 Eye Irritation - Category 2A Germ Cell Mutagenicity - Category 1B Carcinogenicity - Category 1B Reproductive Toxicity - Category 2 Aerosols Category 1 Acute aquatic toxicity - Category 3 Chronic aquatic toxicity - Category 3 Acute toxicity, Dermal - Category 4 Acute toxicity, Oral - Category 4	<b>SIGNAL WORD:</b> <b>DANGER</b>	<b>SYMBOL:</b>			
---	--------------------------------------	----------------	---	---	---

### HAZARD STATEMENTS:

**Physical:**

- H222 - Extremely flammable aerosol.
- H229 - Pressurized container: May burst if heated.

**Health:**

- H312 - Harmful in contact with skin.
- H302 - Harmful if swallowed.
- H304 - May be fatal if swallowed and enters airways.
- H350 - May cause cancer.
- H319 - Causes serious eye irritation.
- H340 - May cause genetic defects.
- H361 - Suspected of damaging fertility or an unborn child.
- H315 - Causes skin irritation.
- H373 - May cause damage to organs through prolonged or repeated exposure.
- H335 - May cause respiratory irritation.

**Environmental**

- H402 - Harmful to aquatic life.
- H412 - Harmful to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS:

**General:**

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.
- P103 - Read label before use.

**Prevention:**

- P273 - Avoid release to the environment.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P264 - Wash thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 - Do not spray on an open flame or other ignition source.
- P251 - Do not pierce or burn, even after use.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 - Use only outdoors or in a well-ventilated area.
- P233 - Keep container tightly closed.

**Response:**

- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P312 - Call a POISON CENTER/doctor if you feel unwell.
- P321 - For specific treatment see section 4.
- P362 + P364 - Take off contaminated clothing. And wash it before reuse.
- P301 + P312 - IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.  
 P308 + P313 - IF exposed or concerned: Get medical advice/attention.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 - If eye irritation persists: Get medical advice/attention.  
 P332 + P313 - If skin irritation occurs: Get medical advice/attention.  
 P314 - Get Medical advice/attention if you feel unwell.  
 P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**Storage:**  
 P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P405 - Store locked up.  
 P403 + P405 - Store in a well-ventilated place. Store locked up.

**Disposal:** P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

**HAZARDS NOT OTHERWISE SPECIFIED:**

Acute toxicity of 25.0205% of the mixture is unknown.

**3. Composition / Information on Ingredients**

CHEMICAL NAME	CAS	Concentration % by Weight
AROMATIC HYDROCARBON MIXTURE >C9	0064742-95-6	19-31
1,2,4-TRIMETHYLBENZENE	0000095-63-6	15-24
Non Hazardous Volatile	NA-ERAEnviro	7-15
Non-hazardous liquid	NA_Cycan	7-15
ETHYLENE GLYCOL MONOBUTYL ETHER	0000111-76-2	5-10
MESITYLENE	0000108-67-8	3-5
CO2	0000124-38-9	2-4
MINERAL OIL, SLAB OIL	0008042-47-5	2-3
DIETHYLBENZENE	0025340-17-4	1-2
XYLENE	0001330-20-7	1-2
CUMENE	0000098-82-8	1-2
PINE OIL	0008002-09-3	1-2
Naphthalenesulfonic acid, dinonyl-, barium salt	0025619-56-1	0.1-1.3

**4. First Aid Measures**

**EMERGENCY OVERVIEW**

**EYES:** Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

**SKIN:** Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use. IF exposed or concerned: Get medical advice/attention.

**INHALATION:** Remove source of exposure or move person to fresh air and keep comfortable for breathing. If exposed/feel unwell/concerned: Call a POISON CENTER/doctor. Eliminate all ignition sources if safe to do so.

**INGESTION:** Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Do not give anything.

**5. Fire-Fighting Measures**

**SUITABLE FIRE EXTINGUISHING MEDIA:**

Dry chemical, foam, carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only. Do not direct a solid stream of water or foam into hot, burning pools this may result in frothing and increase fire intensity.

**UNSUITABLE FIRE EXTINGUISHING MEDIA:**

Not available.

**SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:**

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Product is highly flammable and forms explosive mixtures with air, oxygen, and all oxidizing agents. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a buildup of internal pressures. Cool with water. DO NOT cut, drill, grind, or weld near full, partially full, or empty product containers. Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.

**SPECIFIC FIRE-FIGHTING METHODS:**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## 6. Accidental Release Measures

### EMERGENCY PROCEDURE:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

### RECOMMENDED EQUIPMENT:

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

### PERSONAL PRECAUTIONS:

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### ENVIRONMENTAL PRECAUTIONS AND CLEAN-UP METHODS:

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Cover spills with inert absorbent and place in closed chemical waste containers.

## 7. Handling and Storage

### GENERAL:

Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored.

### VENTILATION REQUIREMENTS:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

### STORAGE ROOM REQUIREMENTS:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them. Store at temperatures below 120°F.

## 8. Exposure Controls / Personal Protection

### PERSONAL PROTECTIVE EQUIPMENT:



**EYE PROTECTION:** Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

**SKIN PROTECTION:** Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

**RESPIRATORY PROTECTION:** If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

### ENGINEERING CONTROLS:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m <sup>3</sup> )	OSHA STEL (ppm)	OSHA STEL (mg/m <sup>3</sup> )	OSHA Tables Z1,2,3	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m <sup>3</sup> )	NIOSH STEL (ppm)	NIOSH STEL (mg/m <sup>3</sup> )	NIOSH Carcinogen
1,2,4-TRIMETHYLBENZENE								25	125			
AROMATIC HYDROCARBON MIXTURE >C9	500	2000										
CO <sub>2</sub>	5000	9000			1			5000	9000	3000	54000	
CUMENE	50	245			1		1	50	245			
ETHYLENE GLYCOL MONOBUTYL ETHER	50	240			1		1	5	24			
MESITYLENE								25	125			
Naphthalenesulfonic acid, dinonyl-, barium salt		0.5										
XYLENE	100	435			1			100	435	150	655	

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m <sup>3</sup> )	ACGIH STEL (ppm)	ACGIH STEL (mg/m <sup>3</sup> )
1,2,4- TRIMETHYLBENZEN E				
AROMATIC HYDROCARBON MIXTURE >C9				
CO2	5000	9000	30000	54000
CUMENE	50	246		
ETHYLENE GLYCOL MONOBUTYL ETHER	20	97		
MESITYLENE				
Naphthalenesulfonic acid, dinonyl-, barium salt		0.5		
XYLENE	100	434	150	651

### 9. Physical & Chemical Properties

<b>Appearance:</b>	Red Liquid	<b>Flammability:</b>	Not available.
<b>Flash Point Symbol:</b>	Not available.	<b>Low Boiling Point:</b>	Not available.
<b>Flash Point:</b>	Not available.	<b>High Boiling Point:</b>	Not available.
<b>Evaporation Rate:</b>	>1 (butyl acetate=1)	<b>Explosive Limit – lower (%):</b>	Not available.
<b>Odor:</b>	Pine	<b>Explosive Limit – upper (%):</b>	Not available.
<b>Odor Threshold:</b>	Not available.	<b>Vapor Pressure:</b>	Not available.
<b>pH:</b>	Not available.	<b>Vapor Density:</b>	Not available.
<b>Melting/Freezing Point:</b>	Not available.	<b>Solubility (ies):</b>	Not available.
<b>VOC Composite Partial Pressure:</b>	Not available.	<b>Auto-Ignition Temperature:</b>	Not available.
<b>Viscosity:</b>	Not available.	<b>Density:</b>	7.70668 lb/gal
<b>% Solids by Wt:</b>	5.73230%	<b>Density VOC:</b>	5.25613 lb/gal
<b>VOC Actual:</b>	5.25613 lb/gal	<b>VOC Actual:</b>	629.84213 g/l
<b>Density VOC less H2O &amp; Exempts:</b>	0.15428 lb/gal	<b>% VOC:</b>	68.20230%

### 10. Stability & Reactivity Information

<b>REACTIVITY:</b>	Material is stable at standard temperature and pressure.
<b>HAZARDOUS REACTIONS/POLYMERIZATION:</b>	Will not occur.
<b>INCOMPATIBLE MATERIALS:</b>	Avoid strong oxidizers, reducers, acids, and alkalis.
<b>CONDITIONS TO AVOID:</b>	Keep away from direct sunlight and other sources of ignition. Dropping containers may cause bursting.
<b>DECOMPOSITION PRODUCTS:</b>	No data available.

### 11. Toxicological Information

<b>PRIMARY ROUTE OF ENTRY:</b>	
<b>ACUTE/POTENTIAL HEALTH EFFECTS:</b>	
<b>EYES:</b>	Eye contact may lead to permanent damage if not treated promptly. Liquid or vapors may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly. Causes serious eye irritation.
<b>SKIN:</b>	Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin. Causes skin irritation.
<b>INHALATION:</b>	No Data Available.
<b>GERM CELL MUTAGENICITY:</b>	May cause genetic defects.
<b>TARGET ORGAN EFFECTS:</b>	
<b>Single Exposure:</b>	May cause respiratory irritation.
<b>Repeated Exposure:</b>	Prolonged exposure may cause damage to her central nervous system, lungs, skin and eyes. May cause damage to organs through prolonged or repeated exposure.
<b>REPRODUCTIVE/DEVELOPMENTAL INFORMATION:</b>	Suspected of damaging fertility or an unborn child.
<b>CARCINOGENIC INFORMATION:</b>	May cause cancer.
<b>ASPIRATION HAZARD:</b>	May be fatal if swallowed and enters airways
<b>ACUTE TOXICITY VALUES:</b>	If inhaled, may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heartbeats.
<b>0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER</b>	
LC50 (female rat):	450 ppm (4-hour exposure) (2)
LC50 (male rat):	486 ppm (4-hour exposure) (2)
LD50 (oral, male weanling rat):	3000 mg/kg (1)
LD50 (oral, 6-week old male rat):	2400 mg/kg (1)
LD50 (oral, yearling male rat):	560 mg/kg (1)
LD50 (oral, female rat):	530 mg/kg (1)
LD50 (oral, male mouse):	1230 mg/kg (1)
LD50 (oral, rabbit):	320 mg/kg (1)
LD50 (dermal, male rabbit):	406 mg/kg (cited as 0.45 mL/kg) (1)
<b>0000095-63-6 1,2,4-TRIMETHYLBENZENE</b>	
LC50 (rat):	18 g/m <sup>3</sup> (4-hour exposure) (1)

LD50 (oral, rat): 5 g/kg (1)

**0000098-82-8 CUMENE**

LC50 (inhalation, mouse): 10 mg/L; (2000 ppm); 7-hr exposure (1,3)

LC50 (inhalation, rat): 39 mg/L (8000 ppm); 4-hr exposure (1,3,6)

LD50 (oral, rat): Reported as 1.4 g/kg and 2.26 g/kg (1,3,4)

LD50 (skin, rabbit): 10627 mg/kg (4)

**0000108-67-8 MESITYLENE**

LC50 (rat): 24 g/m<sup>3</sup> (4-hour exposure) (2)

**0001330-20-7 XYLENE**

LC50 (rat): 6350 ppm (4-hour exposure) (unspecified isomers and ethylbenzene) (1) LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2) ethylbenzene (1)

LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2)

LD50 (oral, rat): 5400 mg/kg (52% m-, 19% o-, 24% p-) (1) LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

**CHRONIC EXPOSURE:**

**0000098-82-8 CUMENE**

TERATOGENIC EFFECTS: Cumene has been Classified as POSSIBLE for humans.

**0001330-20-7 XYLENE**

Xylene in high concentrations has caused embryotoxic effects in laboratory animals. High exposure to Xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus.

**POTENTIAL HEALTH EFFECTS – Miscellaneous**

**0000111-76-2 ETHYLENE GLYCOL MONOBUTYL ETHER**

Can be absorbed through the skin in harmful amounts. May cause injury to the kidneys, liver, blood and/or bone marrow. Repeated overexposure may result in damage to the blood. Eye contact may cause corneal injury. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

**0001330-20-7 XYLENE**

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

**0064742-95-6 AROMATIC HYDROCARBON MIXTURE >C9**

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

**12. Ecological Information**

**TOXICITY:**

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

**PERSISTENCE AND DEGRADABILITY:**

No data available.

**BIOACCUMULATIVE POTENTIAL:**

No data available.

**MOBILITY IN SOIL:**

No data available.

**OTHER ADVERSE EFFECTS:**

No data available.

**13. Disposal Consideration**

**WASTE DISPOSAL;**

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

**14. Transportation Information**

**US DOT INFORMATION:**

Ground Transportation: (Continental United States, Canada & Mexico): Limited Quantity

**IMDG Information:**

Shipping Name: Aerosols, flammable. UN/NA #: 1950. Hazard Class: 2.1. Required Placard: Limited Quantity. Marine Pollutant: No data available.

**IATA Information:**

We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

## 15. Regulatory Information

Chemical Name	CAS	% BY WT	REGULATION LIST
1,2,4- TRIMETHYLBENZENE	0000095-63-6	15-24	SARA312,SARA313,VOC,TSCA
CUMENE	0000098-82-8	1-2	CERCLA,HAPS,SARA312,SARA313,VHAPS,VOC,TSCA,RCRA,CA_Prop65 - California Proposition 65
MESITYLENE	0000108-67-8	3-5	SARA312,VOC,TSCA
ETHYLENE GLYCOL MONOBUTYL ETHER	0000111-76-2	5-10	CERCLA,SARA312,SARA313,VOC,TSCA
CO2	0000124-38-9	2-4	SARA312,TSCA
XYLENE	0001330-20-7	1-2	CERCLA,HAPS,SARA312,SARA313,VHAPS,VOC,TSCA,RCRA
PINE OIL	0008002-09-3	1-2	SARA312,VOC,TSCA
MINERAL OIL, SLAB OIL	0008042-47-5	2-3	SARA312,TSCA
DIETHYLBENZENE	0025340-17-4	1-2	SARA312,VOC,TSCA
Naphthalenesulfonic acid, dinonyl-, barium salt	0025619-56-1	0.1-1.3	SARA312,SARA313,TSCA
AROMATIC HYDROCARBON MIXTURE >C9	0064742-95-6	19-31	SARA312,VOC,TSCA
Non Hazardous Volatile	NA-ERAEnviro	7-15	SARA312

## 16. Other Information

### GLOSSARY:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ - Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

### DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.