PRO CHEM. INC.

1475 BLUEGRASS LAKES PKWY. ALPHARETTA, GA 30004 EMERGENCY/INFO # (800) 241-8180 ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET

SUPER WAX OFF / 2113

FEBRUARY 2010 PAGE 1

HEALTH 3 FI AMMABILITY 1 REACTIVITY 1 PERSONAL PROTECTION G

Complies With USDL Safety and Health Regulations, (29 CFR 1910.200)

SECTION 1 – Chemical Product and Company Identification

CHEMICAL FAMILY: Floor finish remover

SECTION 2 – Composition Information on Ingredients
--

CHEMICAL NAME	% BY WT.	OSHA PEL/ACGIH TLV		SARA 313 (2)*	STATE INFO (3)(4)	CERCLA RQ
2-Butoxyethanol	< 11.0	25 ppm - skin / 25 ppm – skin	ΝÓ	YES	NO	
Potassium Hydroxide	< 6.0	2 mg/m3 / 2 mg/m3	NO	NO	NO	1000 lbs
Šodium Metasilicate	< 4.0	15 mg/m3 / 10 mg/m3	NO	NO	NO	
Monoethanolamine on 15 for more informati	< 15.0 on	3 ppm n/e = none estal	NO olished	NO n/a = not appli	NO cable	
	2-Butoxyethanol Potassium Hydroxide Sodium Metasilicate Monoethanolamine	2-Butoxyethanol < 11.0 Potassium < 6.0 Hydroxide Sodium < 4.0 Metasilicate	CHEMICAL NAME % BY WT. OSHA PEL/ACGIH TLV 2-Butoxyethanol < 11.0	CHEMICAL NAME % BY WT. OSHA PEL/ACGIH TLV 302/ 304 TLV 302/ 304 TLV (1)* 2-Butoxyethanol < 11.0	CHEMICAL NAME % BY WT. OSHA PEL/ACGIH TLV SARA 302/ 304 313 (2)* 2-Butoxyethanol < 11.0	CHEMICAL NAME % BY WT. OSHA PEL/ACGIH TLV (1)* SARA 313 (2)* STATE INFO (3)(4) 2-Butoxyethanol < 11.0

SECTION 3 – Hazards Information

EMERGENCY OVERVIEW: DANGER. Corrosive. May cause moderate to severe eye and skin

irritation. May be absorbed through skin. May cause irritation of the respiratory tract. Clear, light amber liquid with sassafras fragrance.

PRIMARY ROUTE OF ENTRY: Eye contact, skin contact/absorption, inhalation

ACUTE/POTENTIAL HEALTH EFFECTS:

Causes severe irritation, experienced as discomfort or pain, excess blinking and EYES:

tear production, with redness and swelling of the conjunctiva.

SKIN: Brief contact may cause slight irritation. Prolonged contact may cause more

severe irritation with pain, local redness and swelling and possible tissue

INHALATION: High concentrations of vapor or mists may cause irritation of the respiratory tract.

INGESTION: May cause headache, dizziness, incoordination, nausea, vomiting, diarrhea and

general weakness.

CHRONIC/LONG TERM EFFECTS: 2-Butoxyethanol has caused red blood cell hemolysis in lab animals and

secondary injury to the liver and kidney.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Dermal exposure may cause local redness and swelling.

pain and discomfort. Prolonged skin contact may result in absorption of harmful amounts.

TARGET ORGAN EFFECTS: Liver, kidney

REPRODUCTIVE/DEVELOPMENTAL INFORMATION: No Data

CARCINOGENIC INFORMATION: This material is not listed as a carcinogen by IARC, NTP, or OSHA.

SECTION 4 – First Aid Measures

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention

SKIN: Immediately flush skin with plenty of water for at least 15 minutes while removing

contaminated clothing and shoes. Wash clothing before reuse. Get medical attention

immediately.

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

INHALATION:

INGESTION:

Seek medical attention immediately. Call a poison control center or doctor for treatment

advice. Have person drink large quantities of water if able to swallow. Never give anything

by mouth to an unconscious person.

SECTION 5 – Fire Fighting Measures

FLASH POINT: No flash METHOD USED: Standard

EXTINGUISHING MEDIA: Use appropriate methods for combating surrounding fire. SPECIAL FIRE FIGHTING INSTRUCTIONS: Wear a self-contained breathing apparatus with a full-face

piece operated in the positive pressure demand mode.

Chemical resistant PPE is recommended.

SECTION 6 – Accidental Release Measures

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Absorb spill with inert material (e.g. dry sand, earth). Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb unrecoverable product, Transfer contaminated absorbent, soil and other materials to containers for disposal.

SECTION 7 – Handling and Storage

Follow all MSDS/label precautions even after container is emptied because they may contain product residues. Use with adequate ventilation. Do not get in eyes, on skin or clothing. Store in a cool, dry place. Keep container closed when not in use. Keep out of reach of children.

SECTION 8 – Exposure Controls and Personal Protection

ENGINEERING CONTROLS: Good general ventilation required. EYE PROTECTION: Wear safety glasses or goggles.

SKIN PROTECTION: Wear impervious gloves (made from rubber, nitrile or neoprene),

clothing and boots.

RESPIRATORY PROTECTION: When respiratory protection is required, use an organic vapor &

particulate cartridge. All respiratory programs must meet OSHA's 29

CFR 1910.34 & ANSI Z88.2 requirements.

SECTION 9 – Physical and Chemical Properties

APPEARANCE/ODOR: Clear, light amber liquid with sassafras fragrance

EVAPORATION RATE (BUTYL ACETATE=1):

SOLUBILITY IN WATER: SPECIFIC GRAVITY (H20=1): Complete 1.09 VAPOR PRESSURE (mm Hg): pH CONCENTRATE: 13.5 N/e **BOILING POINT:** VAPOR DENSITY (AIR=1): N/e > 212°F

SECTION 10 – Stability and Reactivity

STABILITY: Stable

INCOMPATIBILITY: Strong acids, alkalis, oxidizing agents

CONDITIONS TO AVOID: High temperature **HAZARDOUS POLYMERIZATION:** Will not occur None

HAZARDOUS DECOMPOSITION AND PRODUCTS:

SECTION 11 – Toxicological Information

2-Butoxyethanol: SKIN-Rabbit; 24 hr uncovered-minimal erythema in 2/5; no irritation 3/5

THIS INFORMATION MUST BE ON ALL MSDS'S COPIED AND DISTRIBUTED FOR THIS MATERIAL.

NO WARRANTY IS EXPRESSED/IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE/USER ASSUMES ALL RISKS ASSOCIATED WITH USE.

PRO CHEM. INC.

1475 BLUEGRASS LAKES PKWY. ALPHARETTA, GA 30004 EMERGENCY/INFO # (800) 241-8180 ADDITIONAL EMERGENCY # INFO TRAC 1-800-535-5053

MATERIAL SAFETY DATA SHEET SUPER WAX OFF / 2113 FEBRUARY 2010 PAGE 2

| HEALTH 3 | FLAMMABILITY 1 | REACTIVITY 1 | PERSONAL PROTECTION G

Complies With USDL Safety and Health Regulations, (29 CFR 1910.200)

SECTION 12 – Ecological Information

2-Butoxyethanol: Toxicity to fish-fathead minnow; 96h; LC50 Results: 1700 mg/l

SECTION 13 – Disposal Consideration

WASTE DISPOSAL METHOD:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

SECTION 14 – Transport Information

DOT SHIPPING NAME/CLASS:

Corrosive Liquid, Basic, Inorganic, N.O.S., 8 UN 3266, II (Contains Potassium Hydroxide)

SECTION 15 – Regulatory Information

U.S. Federal Regulations:

TSCA (Toxic Substances Control Act): The intentional ingredients of product are listed.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire () Pressure () Reactive () Not Applicable ()

- (1) Title III Section 302/304 Extremely Hazardous Substances 40 CFR 355 Appendix A
- (2) Title III Section 313 Toxic Chemicals 40 CFR 372.65

If indicated under Section 2 of this MSDS, this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right to Know Act of 1986. This information must be included in all MSDS that are copied and distributed for this material.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes a hazardous waste it would be assigned RCRA Code(s) D002

State and Local Regulations: Certain states maintain their own ingredient, which differ slightly from the Federal standards. If indicated under Section 2 of this MSDS, states listed below may have regulations on ingredients contained in this product. Check with your state for any additional regulations.

- (3) California proposition 65 (Safe Drinking Water & Toxic Enforcement Act of 1986)
- (4) Massachusetts (Hazardous Substance Disclosure by Employers)

SECTION 16 – Other Information

This information was compiled from current manufacturer's MSDS's of the component parts of the product.

Disclaimer: The Manufacturer believes that the information contained in the Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS EXPRESSED/IMPLIED REGARDING THE ACCURACY OF THIS DATA OR RESULTS OBTAINED FROM USE. PROCHEM ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO USER. VENDEE/USER ASSUMES ALL RISKS ASSOCIATED WITH USE.