



SAFETY DATA SHEET

1. Product and Company Identification

PRODUCT NUMBER:	1263	COMPANY PHONE:	1-800-241-8180
PRODUCT NAME:	SLIP-EZ	EMERGENCY TELEPHONE:	1-800-241-8180
PRODUCT DESCRIPTION:	Aerosol Food Grade Silicone Lubricant	INFOTRAC:	1-800-535-5053
COMPANY INFORMATION:	PRO CHEM, INC. 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

2. Hazards Identification

GHS CLASSIFICATION:
Flammable aerosols: Category 1
Aspiration hazard: Category 1
OSHA defined hazards: Not classified.

SIGNAL WORD:
DANGER

SYMBOL:



HAZARD STATEMENTS:

Extremely flammable aerosol. May be fatal if swallowed and enters airways.

PRECAUTIONARY STATEMENTS:

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Response: IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting.
Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

HAZARDS NOT OTHERWISE SPECIFIED:

None known.

SUPPLEMENTAL INFORMATION:

None.

3. Composition / Information on Ingredients

Chemical Name	CAS	Concentration % by Weight
Butane	106-97-8	40-60
Propane	74-98-6	20-40
Naphtha (petroleum), Heavy Alkylate	64741-65-7	10-20
Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9	2.5-10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First Aid Measures

EMERGENCY OVERVIEW

GENERAL: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

EYES: Rinse with water. Get medical attention if irritation develops and persists.

SKIN: Wash off with soap and water. Get medical attention if irritation develops and persists.

INHALATION:

If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

INGESTION:

Rinse mouth. Get medical attention if symptoms occur.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Aspiration may cause pulmonary edema and pneumonitis.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

SUITABLE FIRE EXTINGUISHING MEDIA:

Water spray. Alcohol resistant foam. Powder. Carbon dioxide (CO₂).

UNSUITABLE FIRE EXTINGUISHING MEDIA:

Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

SPECIFIC FIRE-FIGHTING METHODS:

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

GENERAL FIRE HAZARDS:

Extremely flammable aerosol.

6. Accidental Release Measures

PERSONAL PRECAUTIONS:

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during cleanup. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

MATERIALS AND METHODS FOR CLEANUP:

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see Section 13 of the SDS.

ENVIRONMENTAL PRECAUTIONS:

Avoid discharge into drains, watercourses or onto the ground.

7. Handling and Storage

SAFE HANDLING:

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not reuse empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

SAFE STORAGE & INCOMPATIBILITIES:

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
Propane (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm

US. ACGIH Threshold Limit Values

COMPONENTS	TYPE	VALUE
Butane (CAS 106-97-8)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

COMPONENTS	TYPE	VALUE
Butane (CAS 106-97-8)	TWA	1900 mg/m ³ 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m ³ 1000 ppm

BIOLOGICAL LIMIT VALUE:

No biological exposure limits noted for the ingredient(s).

APPROPRIATE ENGINEERING CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:



Eye Protection: Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin Protection: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Wear suitable protective clothing.

Respiratory Protection: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal Hazards: Wear appropriate thermal protective clothing, when necessary.

General Hygiene Considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Physical State:	Gas.	Flammability (solid/gas):	Not available.
Form:	Aerosol.	Flammability Limit–lower (%):	1% estimated.
Color:	Not available.	Flammability Limit–upper (%):	7% estimated.
Odor:	Not available.	Explosive Limit – lower (%):	Not available.
Odor Threshold:	Not available.	Explosive Limit – upper (%):	Not available.
pH:	Not available.	Vapor Pressure:	60 - 70 psig @70°F estimated
Melting/Freezing Point:	Not available.	Vapor Density:	Not available.
Initial Boiling Point/Range:	Not available.	Relative Density:	Not available.

Partition Coeff (n-octanol/water):	Not available.	Solubility (water):	Not available.
Viscosity:	Not available.	Auto-Ignition Temperature:	658°F (347.78°C) estimated
Specific Gravity:	0.785 – 0.795 estimated.	Decomposition Temperature:	Not available.
Flash Point:	-156.0 °F (-104.4 °C) Propellant estimated	Evaporation Rate:	Not available.
Explosive Properties:	Not explosive.	Flame Extension:	35 in estimated.
Heat of Combustion (NFPA):	42.06 kJ/g estimated.	Oxidizing Properties:	Not oxidizing.
VOC (Weight %):	96% estimated.		

10. Stability & Reactivity Information

REACTIVITY:

The product is stable and non-reactive under normal conditions of use, storage and transport.

CHEMICAL STABILITY:

Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

INCOMPATIBLE MATERIALS:

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

CONDITIONS TO AVOID:

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

11. Toxicological Information

PRIMARY ROUTE OF ENTRY:

Eyes: Direct contact with eyes may cause temporary irritation.

Skin: No adverse effects due to skin contact are expected.

Inhalation: No adverse effects due to inhalation are expected.

Ingestion: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

Aspiration may cause pulmonary edema and pneumonitis.

ACUTE TOXICITY:

May be fatal if swallowed and enters airways.

COMPONENTS	SPECIES	TEST RESULTS
<u>Butane (CAS 106-97-8)</u>		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52 %, 120 Minutes
		1355 mg/l
<u>Propane (CAS 74-98-6)</u>		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
	Rat	52 %, 120 Minutes
		1355 mg/l
		658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

SKIN CORROSION/IRRITATION:

Prolonged skin contact may cause temporary irritation.

SERIOUS EYE DAMAGE/IRRITATION:

Direct contact with eyes may cause temporary irritation.

RESPIRATORY SENSITIZATION:

Not a respiratory sensitizer.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

GERM CELL MUTAGENICITY:

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

CARCINOGENICITY:

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity: Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens: Not listed.

REPRODUCTIVE TOXICITY:

This product is not expected to cause reproductive or developmental effects.

SPECIFIC TARGET ORGAN TOXICITY (single exposure):

Not classified.

SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):

Not classified.

ASPIRATION HAZARD:

May be fatal if swallowed and enters airways.

12. Ecological Information

ECOTOXICITY:

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

COMPONENTS	SPECIES	TEST RESULTS
Naphtha (petroleum), Heavy Alkylate (CAS 64741-65-7)		
Aquatic		
Algae	IC50	Algae
		30000 mg/L, 72 hours

* Estimates for product may be based on additional component data not shown.

PERSISTENCE AND DEGRADABILITY:

No data is available on the degradability of this product.

BIOACCUMULATIVE POTENTIAL:

Partition coefficient n-octanol / water (log Kow):

Butane	2.89
Propane	2.36

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS:

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Consideration

DISPOSAL INSTRUCTIONS:

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

LOCAL DISPOSAL REGULATIONS:

Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE:

The waste code should be assigned in discussion between the user, the producer and the waste-disposal company.

WASTE FROM RESIDUES/UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

CONTAMINATED PACKAGING:

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste-handling site for recycling or disposal. Do not reuse empty containers.

14. Transportation Information

DOT: UN Number: UN1950

UN Proper Shipping Name: Aerosols, flammable.

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

Packing Group: Not applicable.

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Special Provisions: N82

Packaging Exceptions: 306

Packaging Nonbulk: None.

Packaging Bulk: None.

IATA: UN Number: UN1950

UN Proper Shipping Name: Aerosols, flammable.

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

Packing Group: Not applicable.

Environmental Hazards: No.

ERG Code: 10L

Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Other Information:

Passenger and Cargo Aircraft: Allowed with restrictions.

Cargo Aircraft Only: Allowed with restrictions.

Packaging Exceptions: LTD QTY

IMDG: UN NUMBER: UN1950

UN Proper Shipping Name: AEROSOLS

Transport Hazard Class(es)

Class: 2.1

Subsidiary Risk: -

Label(s): 2.1

Packing Group: Not applicable.

Environmental Hazards:

Marine pollutant: No.

EmS: F-D, S-U



Special Precautions for User: Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions: LTD QTY

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:

Not applicable.

15. Regulatory Information

US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not regulated.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA):

Hazard categories: Immediate Hazard – Yes.

Delayed Hazard – No.

Fire Hazard – Yes.

Pressure Hazard – No.

Reactivity Hazard – No.

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous Chemical: No.

SARA 313 (TRI reporting): Not regulated.

OTHER FEDERAL REGULATIONS

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA): Not regulated.

US STATE REGULATIONS

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100): Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)):

Butane (CAS 106-97-8)

Naphtha (petroleum), Heavy Alkylate (CAS 64741-65-7)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. California Proposition 65: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

INTERNATIONAL INVENTORIES:

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

DISCLAIMER:

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.